



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Wax & Grease Remover

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Manufacturer or supplier's details

Company : Univar Solutions USA, Inc - Arpol®
Address : 3075 Highland Pkwy Suite 200
Downers Grove, IL 60515
United States of America

Emergency telephone number:

Univar Solutions USA, Inc - Arpol®:-CHEMTREC: 1-800-424-9300
CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Phone: 1-855-429-2661
Regulatory Information Number: 1-855-429-2661
Email: SDSNA@univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.



Safety Data Sheet

Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	Weight percent
68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated lt AND/OR Solvent naphtha (pet), lt aliph.	90 - 100
111-65-9	**Octane	5 - 10
142-82-5	**Heptane	5 - 10

Actual concentration is withheld as a trade secret

Any Concentration shown as a range is due to batch variation.



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type	Control parameter	Basis
---------	------------	------------	-------------------	-------



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

		(Form of exposure)	ters / Permissible concentration	
68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, It dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated It AND/OR Solvent naphtha (pet), It aliph.	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
111-65-9	**Octane	TWA	300 ppm	ACGIH
		TWA	75 ppm 350 mg/m ³	NIOSH REL
		C	385 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,350 mg/m ³	OSHA Z-1
		TWA	300 ppm 1,450 mg/m ³	OSHA P0
		STEL	375 ppm 1,800 mg/m ³	OSHA P0
		TWA	300 ppm	ACGIH
142-82-5	**Heptane	TWA	85 ppm 350 mg/m ³	NIOSH REL
		C	440 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		STEL	500 ppm 2,000 mg/m ³	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

Appearance	: liquid
Colour	: Clear, Colorless
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Freezing Point (Melting point/freezing point)	: < -60 °C (-76 °F)
Boiling Point (Boiling point/boiling range)	: 118 - 150 °C (244 - 302 °F)
Flash point	: 14 - 18 °C (57 - 64 °F) Method: closed cup
Evaporation rate	: < 1 (Butyl Acetate = 1)
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7.6 %(V)
Lower explosion limit	: 0.9 %(V)
Vapour pressure	: 11 - 16.00 mmHg @ 20 °C (68 °F)
Relative vapour density	: > 4 @ 20 - 25 °C (68 - 77 °F) (Air = 1.0)
Relative density	: 0.74 - 0.76 @ 15.6 °C (60.1 °F) Reference substance: (water = 1)
Density	: 0.7601 g/cm ³ @ 15.6 °C (60.1 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 246 - 470 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: < 0.01 mm ² /s @ 40 °C (104 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Acids Bases



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

Hazardous decomposition products : Oxidizing agents
Carbon oxides
Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Skin corrosion/irritation

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Species: Rabbit

Exposure time: 4 h

Result: Irritating to skin.

Germ cell mutagenicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Germ cell mutagenicity - Assessment : Mutagenicity classification not possible from current data

Carcinogenicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

STOT - single exposure

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Aspiration toxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l
Exposure time: 96 h
Test Type: semi-static test

LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test Type: Immobilization

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h

EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to fish (Chronic tox- : NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l



Safety Data Sheet

Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

icity) Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l
Exposure time: 21 d

Chronic aquatic toxicity- Assessment : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Partition coefficient: n-octanol/water : log Pow: 2.13 - 4.85 (25 °C)

111-65-9:

Partition coefficient: n-octanol/water : log Pow: 5.15

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922

Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922



Safety Data Sheet

Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

IATA (International Air Transport Association):
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

IMDG (International Maritime Dangerous Goods):
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, Marine Pollutant (MIXTURE OF PETROLEUM DISTILLATES) , Flash Point:14 - 18 °C(57 - 64 °F)

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B2: Flammable liquid
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Benzene	71-43-2	10	101010
**Toluene	108-88-3	1000	*
**Ethylbenzene	100-41-4	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act



Safety Data Sheet Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	**Toluene
100-41-4	**Ethylbenzene
71-43-2	**Benzene
91-20-3	**Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	**Toluene
100-41-4	**Ethylbenzene
71-43-2	**Benzene
91-20-3	**Naphthalene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Massachusetts Right To Know

111-65-9	**Octane
142-82-5	**Heptane
71-43-2	**Benzene

Pennsylvania Right To Know

68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, It dist hydrotreat process, low-boil AND/OR Naphtha (pet), hy- drotreated It AND/OR Solvent naphtha (pet), It aliph.
111-65-9	**Octane
142-82-5	**Heptane
108-88-3	**Toluene
100-41-4	**Ethylbenzene

California Prop 65

⚠ WARNING: This product can expose you to chemicals including **Ethylbenzene, **Benzene, **Naphthalene, which is/are known to the State of California to cause cancer, and **Toluene, **Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory



Safety Data Sheet

Wax & Grease Remover

Version 1.6


Revision Date: 09/02/2022

PHIL : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 =Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Revision Date : 09/02/2022

Material number:

16186814, 16058026, 16058027, 16058025, 16058024, 16061154

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chem-	PEL	Permissible Exposure Limit



Safety Data Sheet
Wax & Grease Remover

Version 1.6

Revision Date: 09/02/2022

	icals Association		
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		