ASHLAND	Page: 1
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : FINISHING CREAM

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Adhesives

Industrial chemical

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Dermal) : Category 4

Skin corrosion : Category 1A

Serious eye damage : Category 1

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms :







Signal Word : Danger

Hazard Statements : Harmful in contact with skin.

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

In case of inadequate ventilation wear respiratory protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

PART A

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
POLYMER	800986-5211P	Skin Sens. 1B; H317	>= 40.00 - < 50.00

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

ACRYLATE	254504001-5696	Eye Irrit. 2A; H319	>= 20.00 - < 30.00
		Skin Sens. 1; H317	
CALCIUM COMPOUND	254504001-5840		>= 20.00 - < 30.00

The identity of one or more component(s) is being withheld under business confidentiality.

PART B

Substance / Mixture : Mixture

Hazardous components

Hazardous components			
Chemical Name	CAS-No.	Classification	Concentration (%)
PHYLOSILICATES	254504001-5903	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	>= 20.00 - < 30.00
ALIPHATIC DIAMINE	800986-5576P	Flam. Liq. 4; H227 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335	>= 10.00 - < 15.00

The identity of one or more component(s) is being withheld under business confidentiality.

AILKYLPHENOLS / POLYAMINES MIXTURE	Acute Tox. 4; H302	36.69
	Acute Tox. 3; H311	
	Skin Corr. 1B; H314	

ASHLAND	Page: 4
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

	Eye Dam. 1; H318	
	Resp. Sens. 1; H334	
	Skin Sens. 1; H317	
	Aquatic Acute 1; H400	
	Aquatic Chronic 1; H410	
84852-15-3	Acute Tox. 4; H302	14.22
	Skin Corr. 1B; H314	
	Eye Dam. 1; H318	
	Repr. 2; H361	
	84852-15-3	84852-15-3 Acute Tox. 4; H302 Skin Corr. 1B; H314

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Call a physician or poison control centre immediately.

Keep patient warm and at rest.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

If swallowed : Get medical attention immediately.

Do NOT induce vomiting.

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Cough wheezing

Harmful in contact with skin.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Suspected of damaging fertility or the unborn child.

Causes severe burns.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

phenols

Nitrogen oxides (NOx) acrid smoke and fumes

In a sustained fire, sizing and binders may decompose, releasing combustion products including carbon dioxide, carbon monoxide, various hydrocarbons, and water.

Hydrogen corrosive vapors toxic fumes formaldehyde

Specific extinguishing

methods

:

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : P

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Observe label precautions.

Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

PART B

Components	CAS-No.	Value type	Control	Basis
•		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
PHYLOSILICATES	254504001-	TWA	2 mg/m3	ACGIH
	5903		Respirable	
			fraction.	
		REL	2 mg/m3	NIOSH/GUID
			Respirable.	E
		TWA	0.1 mg/m3	Z3
			Respirable.	
		TWA	0.3 mg/m3	Z3
			Total dust.	

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection Remarks

: The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles and face shield when there is

potential for exposure of the eyes or face to liquid, vapor or

mist.

ASHLAND	Page: 8
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Maintain eye wash station in immediate work area.

Skin and body protection : Wear as appropriate:

impervious clothing Chemical resistant apron

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink.

Ensure that eyewash stations and safety showers are close to

the workstation location. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PART A

Appearance : viscous

Physical state : liquid

Colour : blue

Odour : not significant

Odour Threshold : No data available

pH : No data available

No data available

Boiling point/boiling range : $> 500 \, ^{\circ}\text{F} / > 260 \, ^{\circ}\text{C}$

Flash point : $> 212 \, ^{\circ}\text{F} / > 100 \, ^{\circ}\text{C}$

Method: Closed Cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.04 hPa (25 °C)

Calculated Vapor Pressure

ASHLAND	Page: 9
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Relative vapour density : No data available

Relative density : No data available

Density : 1.22 g/cm3 (77 °F)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

PART B

Appearance : viscous

Physical state : liquid

Colour : yellow

Odour : No data available

Odour Threshold : No data available

pH : No data available

No data available

Boiling point/boiling range : 378 °F / 192 °C

Flash point : $> 212 \,^{\circ}\text{F} / > 100 \,^{\circ}\text{C}$

Method: Closed Cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : 0.8 %(V)

Calculated Explosive Limit

ASHLAND	Page: 10
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Vapour pressure : 173.3333333 hPa (135 °C)

Calculated Vapor Pressure

Relative vapour density : > 1(Air = 1.0)

Relative density : No data available

Density : 1.0303 g/cm3 (77 °F)

Solubility(ies)

Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Blanketing with inert gas. Freezing temperatures.

None known.

Direct heating, dirt, chemical contamination, sunlight, UV or

ionising radiation. Exposure to moisture

Incompatible materials : None known.

Acids Amines Bases

Strong oxidizing agents strong reducing agents

water

ASHLAND	Page: 11
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Hazardous decomposition

products carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

phenols

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

: Inhalation Skin Absorption

Skin contact
Eye Contact
Ingestion

Acute toxicity

Harmful in contact with skin.

Components: POLYMER:

Acute oral toxicity : LD 50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: No adverse effect has been observed in acute

oral toxicity tests.

Acute dermal toxicity : LD 50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

ALIPHATIC DIAMINE:

Acute oral toxicity : LD50 (Rat, male): 1,690 mg/kg

Method: OECD Test Guideline 401

GLP: no

Acute inhalation toxicity : LC50 (Rat, male and female): 4.9 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): 1,870 mg/kg

Method: OECD Test Guideline 402

GLP: no

Remarks: Information given is based on data obtained from

similar substances.

Components:

AILKYLPHENOLS / POLYAMINES MIXTURE:

Acute oral toxicity : LD 50 (Rat): 1,300 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): 675 mg/kg

NONYLPHENOL.:

ASHLAND	Page: 12
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Acute oral toxicity : LD 50 (Rat): 1,412 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: May cause skin irritation in susceptible persons., Causes severe skin burns and eye

damage.

Components:

POLYMER:

Result: Slightly irritating to skin

ACRYLATE:

Result: Possibly irritating to skin

PHYLOSILICATES:

Result: Possibly irritating to skin

CALCIUM COMPOUND: Result: Slightly irritating to skin

ALIPHATIC DIAMINE:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive after 3 minutes or less of exposure

Components:

AILKYLPHENOLS / POLYAMINES MIXTURE:

Result: Corrosive to skin

NONYLPHENOL.: Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

POLYMER:

Result: Slightly irritating to eyes

ACRYLATE:

Result: Irritating to eyes

PHYLOSILICATES:

Result: Possibly irritating to eyes

CALCIUM COMPOUND:

Result: Slightly irritating to eyes

ALIPHATIC DIAMINE:

ASHLAND	Page: 13
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Species: Rabbit

Result: Corrosive to eyes

Components:

AILKYLPHENOLS / POLYAMINES MIXTURE:

Result: Corrosive to eyes

NONYLPHENOL.: Species: Rabbit

Result: Corrosive to eyes

Method: OECD Test Guideline 405

GLP: no

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

Components:

POLYMER:

Test Type: Local lymph node assay Method: OECD Test Guideline 429

Result: The product is a skin sensitiser, sub-category 1B.

ACRYLATE:

Result: May cause sensitization by skin contact.

ALIPHATIC DIAMINE: Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Components:

AILKYLPHENOLS / POLYAMINES MIXTURE:

Assessment: May cause sensitisation by skin contact.

Assessment: May cause sensitisation by inhalation.

NONYLPHENOL.:

Test Type: Maximisation Test (GPMT)

Exposure routes: Dermal Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Method: OECD Test Guideline 406

GLP: no

Germ cell mutagenicity

Not classified based on available information.

Components: POLYMER:

Genotoxicity in vitro : Test Type: in vitro assay

Test species: Rodent cell line

Metabolic activation: without metabolic activation

Result: positive

: Test Type: in vitro assay

ASHLAND	Page: 14
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Test species: Rodent cell line

Metabolic activation: with metabolic activation

Result: negative

: Test Type: Ames test

Metabolic activation: with and without metabolic activation

Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Test species: Mouse (male) Application Route: Ingestion

Result: negative

ALIPHATIC DIAMINE:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test species: Human lymphocytes

Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 (In vitro Mammalian

Chromosome Aberration Test)

Result: negative

GLP: yes

: Test species: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Test species: Mouse (male and female)
Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Components:

NONYLPHENOL.:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

GLP: no

Test Type: Chromosome aberration test in vitro Test species: Chinese hamster ovary cells

Result: negative

GLP: no

Test Type: In vitro mammalian cell gene mutation test

Test species: Chinese hamster fibroblasts

Method: OECD Test Guideline 476

Result: negative

ASHLAND	Page: 15
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

GLP: yes

: Test Type: comet assay

Test species: Chinese hamster ovary cells

Result: positive

GLP: no

: Test Type: chromosome aberration assay Genotoxicity in vivo

Test species: Mouse Cell type: Bone marrow

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

NONYLPHENOL .:

Reproductive toxicity -: Some evidence of adverse effects on sexual function and Assessment

fertility, based on animal experiments., Some evidence of

adverse effects on development, based on animal

experiments.

STOT - single exposure

Not classified based on available information.

Components:

ALIPHATIC DIAMINE: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

> **TALC** 14807-96-6

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ASHLAND	Page: 16
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

POLYMER:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.7 mg/l

Exposure time: 96 h
Test Type: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Water flea (Daphnia magna)): 2.8 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 4.2

mg/l

Exposure time: 72 h

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Water flea (Daphnia magna)): 0.3 mg/l

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

ALIPHATIC DIAMINE:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 130 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 50 mg/l

Exposure time: 48 h Test Type: static test Method: EPA-660/3-75-009

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: Information given is based on data obtained from

similar substances.

NOEC (Pseudokirchneriella subcapitata (green algae)): 10

mg/l

Exposure time: 72 h Test Type: static test

ASHLAND	Page: 17
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Method: OECD Test Guideline 201

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 4.16 mg/l

Exposure time: 21 d

End point: Reproduction Test Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to bacteria : EC20 (Pseudomonas putida): 30 mg/l

End point: Growth rate Exposure time: 18 h Test Type: Static

AILKYLPHENOLS / POLYAMINES MIXTURE:

Toxicity to fish : LC 50 (Bluegill (Lepomis macrochirus)): 0.1351 mg/l

Exposure time: 96 h

NONYLPHENOL.:

Toxicity to fish : LC 50 (Fish): 0.017 - 5.44 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Aquatic invertebrates): 0.02 - 0.596 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.3

mg/l

End point: Growth inhibition

Exposure time: 96 h Test Type: static test

GLP: yes

M-Factor (Acute aquatic

toxicity)

: 10

Toxicity to fish (Chronic

toxicity)

: NOEC (Oncorhynchus mykiss (rainbow trout)): 0.006 mg/l

Exposure time: 91 d
End point: Growth rate

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

(Daphnia magna (Water flea)): 0.024 mg/l

Exposure time: 21 d

End point: Reproduction Test Test Type: semi-static test

Persistence and degradability

Components:

POLYMER:

ASHLAND	Page: 18
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Biodegradation: 82 % Exposure time: 28 d

Method: Abiotic degradation

Physico-chemical

removability

Remarks: The product can be degraded by abiotic (e.g.

chemical or photolytic) processes.

ALIPHATIC DIAMINE:

: Result: Readily biodegradable Biodegradability

Biodegradation: 100 % Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

Bioaccumulative potential

Components:

ALIPHATIC DIAMINE:

: log Pow: <= 1 (25 °C) Partition coefficient: n-

pH: 9 octanol/water GLP: yes

NONYLPHENOL.:

Partition coefficient: n-: log Pow: 5.4 (23 °C)

octanol/water pH: 5.7

Method: OECD Test Guideline 117

Mobility in soil **Components:** No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life

with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

ASHLAND	Page: 19
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

UN	3267	Corrosive liquid, basic, organic, n.o.s. (TRIETHYLENETETRAMINE, POLYALKYLAMINE)	8	II	LIMITED QUANTITY

U.S. DOT - RAIL

UN	3267	Corrosive liquid, basic, organic, n.o.s. (TRIETHYLENETETRAMINE, POLYALKYLAMINE)	8	II	LIMITED QUANTITY

U.S. DOT - INLAND WATERWAYS

UN	3267	Corrosive liquid, basic, organic,	8	II	LIMITED
		n.o.s.			QUANTITY
		(TRIETHYLENETETRAMINE,			
		POLYALKYLAMINE)			
		·			

TRANSPORT CANADA - ROAD

UN	3267	CORROSIVE LIQUID, BASIC,	8	II	LIMITED
		ORGANIC, N.O.S.			QUANTITY
		(TRIETHYLENETETRAMINE,			
		POLYALKYLAMINE)			
		,			

TRANSPORT CANADA - RAIL

	HI AR				Page: 20
SAFETY C	ATA SHEET	9		Revis	sion Date: 05/26/2015
	-				Print Date: 6/1/2015
				SDS No	ımber: 000000093521
FINISHING CF	REAM				Version: 1.1
507274					
UN 3267	CORROSIVE LIQU ORGANIC, N.O.S. (TRIETHYLENETE POLYALKYLAMINE	TRAMINE,	8	II	LIMITED QUANTITY
RANSPORT C	ANADA - INLAND WA	TERWAYS			
UN 3267		ID, BASIC, TRAMINE,	8	II	LIMITED QUANTITY
NTERNATION	AL MARITIME DANGE	POUS GOOD	.		
UN 3267		ID, BASIC, TRAMINE,	8	II	MARINE POLLUTANT:(EPOXY RESIN)LIMITE D QUANTITY
NTERNATION/	AL AIR TRANSPORT A	ASSOCIATION	I - CARGO		
UN 3267	Corrosive liquid, bas n.o.s. (TRIETHYLENETE POLYALKYLAMINE	TRAMINE,	8	II	
NTERNATION/	AL AIR TRANSPORT A	ASSOCIATION	I - PASSENGER		
UN 3267	Corrosive liquid, bas n.o.s. (TRIETHYLENETE POLYALKYLAMINE	sic, organic, TRAMINE,	8	II	
_	ULATION FOR THE LA	AND TRANSP	ORT OF HAZARDOU	S MATERIALS A	ND
VASTES UN 3267	LIQUIDO CORROS BASICO, ORGANIC (TRIETHYLENETE POLYALKYLAMINE	CO, N.E.P. TRAMINE,	8	II	
ORM = ORM-D	, CBL = COMBUSTIBL	E LIQUID			
– O D	ollutant	yes			

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

ASHLAND	Page: 21
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

SECTION 15. REGULATORY INFORMATION

PART A

SARA 311/312 Hazards : Acute Health Hazard

SARA 313

Component(s)SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.
GLASS SPHERE 65997-17-3

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

TOLUENE 108-88-3

PART B

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 313

Component(s)SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.
GLASS SPHERE 65997-17-3

QUARTZ / SAND 14808-60-7

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

DIISODECYL 26761-40-0

PHTHALATE

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

ENCS : Exempt

ASHLAND	Page: 22
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

Registration: Trade Secret


Chemical Name	Identification number
POLYMER	800986-5211P
ACRYLATE	254504001-5696
PHYLOSILICATES	254504001-5903
CALCIUM COMPOUND	254504001-5840
ALIPHATIC DIAMINE	800986-5576P

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/26/2015

PART A NFPA:



Special hazard.

HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic


NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

PART B

ASHLAND	Page: 23
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	





Special hazard.

HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

PART A

H227	Combustible liquid.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.

PART B

H227	Combustible liquid.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

ASHLAND	Page: 24
SAFETY DATA SHEET	Revision Date: 05/26/2015
	Print Date: 6/1/2015
	SDS Number: 000000093521
FINISHING CREAM	Version: 1.1
507274	

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System