



## 1 Identification

- **Product identifier**
- **Trade name:** FleetSpec 1510CB Clear Binder Satin
- **Article number:** 1510CB
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Baril Coating USA, LLC  
401 Growth Parkway  
Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

**Trade name: FleetSpec 1510CB Clear Binder Satin**

(Contd. of page 1)

Keep container tightly closed.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wash thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Specific treatment (see on this label).  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If skin irritation occurs: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.**3 Composition/information on ingredients**· **Chemical characterization: Mixtures**· **Description:** Hazardous substances listed below.· **Dangerous components:**

1330-20-7	xylene	>10-≤25%
110-19-0	isobutyl acetate	>2.5-≤10%
123-86-4	n-butyl acetate	≤2.5%
108-65-6	2-methoxy-1-methylethyl acetate	≤2.5%

**4 First-aid measures**· **Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Trade name: **FleetSpec 1510CB Clear Binder Satin**

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

1330-20-7	xylene	130 ppm
110-19-0	isobutyl acetate	450 ppm
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>

### · PAC-2:

1330-20-7	xylene	920* ppm
110-19-0	isobutyl acetate	1300* ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>

### · PAC-3:

1330-20-7	xylene	2500* ppm
110-19-0	isobutyl acetate	7500** ppm
123-86-4	n-butyl acetate	3000* ppm

(Contd. on page 4)

Printing date 12/03/2024

Reviewed on 12/03/2024

**Trade name: FleetSpec 1510CB Clear Binder Satin**

(Contd. of page 3)

108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

### · Components with limit values that require monitoring at the workplace:

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

#### 110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

(Contd. on page 5)

- US -

Trade name: FleetSpec 1510CB Clear Binder Satin

(Contd. of page 4)

· **Ingredients with biological limit values:****1330-20-7 xylene**

BEI	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Liquid

**Color:**

According to product specification

· **Odor:**

Solvent-like

(Contd. on page 6)

Trade name: FleetSpec 1510CB Clear Binder Satin

(Contd. of page 5)

· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b> <b>Melting point/Melting range:</b> <b>Boiling point/Boiling range:</b>	Undetermined. 137-143 °C (278.6-289.4 °F)
· <b>Flash point:</b>	25 °C (77 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	500 °C (932 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b> <b>Lower:</b> <b>Upper:</b>	1.1 Vol % 7 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	6.7-8.2 hPa (5-6.2 mm Hg)
· <b>Density at 20 °C (68 °F):</b> · <b>Relative density</b> · <b>Vapor density</b> · <b>Evaporation rate</b>	1.41 g/cm <sup>3</sup> (11.77 lbs/gal) Not determined. Not determined. Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Fully miscible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not determined. Not determined.
· <b>Solvent content:</b> <b>Organic solvents:</b> <b>VOC content:</b>	26.2 % 26.24 % 370.0 g/l / 3.09 lb/gal
<b>Solids content:</b> · <b>Other information:</b>	73.6 % (by weight) No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Trade name: FleetSpec 1510CB Clear Binder Satin

(Contd. of page 6)

**11 Toxicological information**· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** No irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.

US

(Contd. on page 8)



Printing date 12/03/2024

Reviewed on 12/03/2024



Trade name: FleetSpec 1510CB Clear Binder Satin

(Contd. of page 7)

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

- |   |   |
|---|---|
| · <b>UN-Number</b>  | UN1263  |
| · <b>DOT, IMDG, IATA</b>  |   |
| · <b>UN proper shipping name</b>  | Paint   |
| · <b>DOT</b>  | PAINT   |
| · <b>IMDG, IATA</b>   |   |
| · <b>Transport hazard class(es)</b>   |   |
| · <b>DOT</b>  |   |
|   |   |
| · <b>Class</b>  | 3 Flammable liquids   |
| · <b>Label</b>  | 3   |
| · <b>IMDG, IATA</b>   |   |
|  |   |
| · <b>Class</b>  | 3 Flammable liquids   |
| · <b>Label</b>  | 3   |
| · <b>Packing group</b>  | III   |
| · <b>DOT, IMDG, IATA</b>  |   |
| · <b>Environmental hazards:</b>   | Not applicable.   |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids  |
| · <b>Danger code (Kemler):</b>  | 30  |
| · <b>EMS Number:</b>  | F-E, S-E  |
| · <b>Stowage Category</b>   | A   |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>    | Not applicable.   |
| · <b>Transport/Additional information:</b>  |   |
| · <b>DOT</b>  |   |
| · <b>Quantity limitations</b>   | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L |

(Contd. on page 9)



Printing date 12/03/2024

Reviewed on 12/03/2024

Trade name: FleetSpec 1510CB Clear Binder Satin

(Contd. of page 8)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7 | xylene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

14808-60-7 | Quartz (SiO<sub>2</sub>)

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7 | xylene

I

- **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 | xylene

A4

14808-60-7 | Quartz (SiO<sub>2</sub>)

A2

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7 | Quartz (SiO<sub>2</sub>)

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard statements**

Flammable liquid and vapor.

(Contd. on page 10)

Printing date 12/03/2024

Reviewed on 12/03/2024

**Trade name: FleetSpec 1510CB Clear Binder Satin**

(Contd. of page 9)

*Causes skin irritation.***Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Wash thoroughly after handling.**Wear protective gloves/protective clothing/eye protection/face protection.**Specific treatment (see on this label).**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If skin irritation occurs: Get medical advice/attention.**Take off contaminated clothing and wash it before reuse.**In case of fire: Use for extinction: CO2, powder or water spray.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information***This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***Department issuing SDS:** Environment protection department.**Contact:** Mr. Williams**Date of preparation / last revision** 12/03/2024 / -**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2