



## 1 Identification

- **Product identifier**
- **Trade name:** Steelkote 800 High Build Epoxy Primer Gray
- **Article number:** 800B060
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Baril Coating USA, LLC  
401 Growth Parkway  
Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 1)

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

titanium dioxide

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

Solvent naphtha (petroleum), light arom.

4-methylpentan-2-one

· **Hazard statements***Flammable liquid and vapor.**Causes skin irritation.**Causes serious eye irritation.**May cause an allergic skin reaction.**May cause genetic defects.**May cause cancer.*· **Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**If exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = \*2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Trade name: Steelkote 800 High Build Epoxy Primer Gray

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Hazardous substances listed below.

- **Dangerous components:**

7727-43-7	barium sulphate, natural	>10-≤25%
13463-67-7	titanium dioxide	>10-≤25%
1330-20-7	xylene	>2.5-<10%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
108-10-1	4-methylpentan-2-one	0.1-≤2.5%
78-92-2	butanol	≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-≤2.5%
123-86-4	n-butyl acetate	≤2.5%
1333-86-4	Carbon black	0.1-≤2.5%
14808-60-7	Quartz (SiO <sub>2</sub> )	0.1-≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

US

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

25036-25-3	Diglycidyl ether of bisphenol A	12 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700$ )	90 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
108-10-1	4-methylpentan-2-one	75 ppm
78-92-2	butanol	150 ppm
123-86-4	n-butyl acetate	5 ppm
1344-28-1	aluminium oxide	15 mg/m <sup>3</sup>
107-98-2	1-methoxy-2-propanol	100 ppm
110-43-0	Methyl n-amyl ketone	150 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	14 mg/m <sup>3</sup>
546-93-0	Magnesite	45 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>

### · PAC-2:

25036-25-3	Diglycidyl ether of bisphenol A	130 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700$ )	990 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm

(Contd. on page 5)

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 4)

108-10-1	4-methylpentan-2-one	500 ppm
78-92-2	butanol	220 ppm
123-86-4	n-butyl acetate	200 ppm
1344-28-1	aluminium oxide	170 mg/m <sup>3</sup>
107-98-2	1-methoxy-2-propanol	160 ppm
110-43-0	Methyl n-amyl ketone	670 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	110 mg/m <sup>3</sup>
546-93-0	Magnesite	260 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>

**PAC-3:**

25036-25-3	Diglycidyl ether of bisphenol A	790 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	5,900 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
78-92-2	butanol	10000** ppm
123-86-4	n-butyl acetate	3000* ppm
1344-28-1	aluminium oxide	990 mg/m <sup>3</sup>
107-98-2	1-methoxy-2-propanol	660 ppm
110-43-0	Methyl n-amyl ketone	4000* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	680 mg/m <sup>3</sup>
546-93-0	Magnesite	1,600 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>

**7 Handling and storage****Handling:****Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

**Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** No special requirements.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 6)

Trade name: Steelkote 800 High Build Epoxy Primer Gray

(Contd. of page 5)

· **Specific end use(s)** No further relevant information available.**8 Exposure controls/personal protection**· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**7727-43-7 barium sulphate, natural**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**108-10-1 4-methylpentan-2-one**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI

**78-92-2 butanol**

PEL	Long-term value: 450 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 455 mg/m <sup>3</sup> , 150 ppm Long-term value: 305 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 300 mg/m <sup>3</sup> , 100 ppm

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**1333-86-4 Carbon black**

PEL	Long-term value: 3.5 mg/m <sup>3</sup>
-----	--

(Contd. on page 7)

Printing date 11/15/2024

Reviewed on 11/15/2024

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 6)

REL	Long-term value: 3.5* mg/m <sup>3</sup> *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m <sup>3</sup> *inhalable fraction
<b>14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
PEL	Long-term value: 0.05* mg/m <sup>3</sup> *resp. dust; 30mg/m <sup>3</sup> / %SiO <sub>2</sub> +2
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction
<b>Ingredients with biological limit values:</b>	
<b>1330-20-7 xylene</b>	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
<b>108-10-1 4-methylpentan-2-one</b>	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)



Trade name: Steelkote 800 High Build Epoxy Primer Gray

(Contd. of page 7)

## · Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

## · Information on basic physical and chemical properties

## · General Information

## · Appearance:

Form:	Liquid
Color:	Grey
Odor:	Solvent-like
Odor threshold:	Not determined.

· pH-value: Not determined.

## · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137-143 °C (278.6-289.4 °F)

· Flash point: 30 °C (86 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 500 °C (932 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

## · Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure: Not determined.

· Density at 20 °C (68 °F): 1.6 g/cm<sup>3</sup> (13.35 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

## · Solubility in / Miscibility with

Water: Miscible

· Partition coefficient (n-octanol/water): Not determined.

## · Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

## · Solvent content:

Organic solvents:	17.8 %
VOC content:	17.81 %
	285.0 g/l / 2.38 lb/gal

Solids content: 82.2 % (by weight)

(Contd. on page 9)



Trade name: Steelkote 800 High Build Epoxy Primer Gray

(Contd. of page 8)

· **Other information:** No further relevant information available.**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Carcinogenic.  
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc ( $Mg_3H_2(SiO_3)_4$ )	3
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
108-10-1	4-methylpentan-2-one	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
14808-60-7	Quartz ( $SiO_2$ )	1

- **NTP (National Toxicology Program)**

14808-60-7	Quartz ( $SiO_2$ )	K
------------	--------------------	---

(Contd. on page 10)

Trade name: Steelkote 800 High Build Epoxy Primer Gray

(Contd. of page 9)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.


**14 Transport information**

- |   |                     |
|---|---------------------|
| · <b>UN-Number</b>  | UN1263              |
| · <b>DOT, IMDG, IATA</b>  |                     |
| · <b>UN proper shipping name</b>  | Paint               |
| · <b>DOT</b>  | PAINT               |
| · <b>IMDG, IATA</b>   |                     |
| · <b>Transport hazard class(es)</b>   |                     |
| · <b>DOT</b>  |                     |
|  |                     |
| · <b>Class</b>  | 3 Flammable liquids |

(Contd. on page 11)

Trade name: Steelkote 800 High Build Epoxy Primer Gray

(Contd. of page 10)

· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural

1330-20-7 xylene

108-10-1 4-methylpentan-2-one

78-92-2 butanol

1344-28-1 aluminium oxide

### · TSCA (Toxic Substances Control Act):

All ingredients are listed.

### · Proposition 65

### · Chemicals known to cause cancer:

13463-67-7 titanium dioxide

(Contd. on page 12)

Printing date 11/15/2024

Reviewed on 11/15/2024

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 11)

108-10-1	4-methylpentan-2-one
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-10-1 4-methylpentan-2-one

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
1330-20-7	xylene	I
108-10-1	4-methylpentan-2-one	I

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
1344-28-1	aluminium oxide	A4
1333-86-4	Carbon black	A4
1314-23-4	zirconium dioxide	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO <sub>2</sub> )

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labeling:**

titanium dioxide

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

Solvent naphtha (petroleum), light arom.

4-methylpentan-2-one

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

(Contd. on page 13)

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 12)

**· Precautionary statements**

*If medical advice is needed, have product container or label at hand.*  
*Keep out of reach of children.*  
*Read label before use.*  
*Obtain special instructions before use.*  
*Do not handle until all safety precautions have been read and understood.*  
*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
*Keep container tightly closed.*  
*Ground/bond container and receiving equipment.*  
*Use explosion-proof electrical/ventilating/lighting/equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Avoid breathing dust/fume/gas/mist/vapors/spray*  
*Wash thoroughly after handling.*  
*Contaminated work clothing must not be allowed out of the workplace.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
*IF exposed or concerned: Get medical advice/attention.*  
*Specific treatment (see on this label).*  
*Take off contaminated clothing and wash it before reuse.*  
*If skin irritation or rash occurs: Get medical advice/attention.*  
*If eye irritation persists: Get medical advice/attention.*  
*Wash contaminated clothing before reuse.*  
*In case of fire: Use for extinction: CO2, powder or water spray.*  
*Store in a well-ventilated place. Keep cool.*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**· National regulations:****· Information about limitation of use:**

*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

**· Department issuing SDS:** Environment protection department.**· Contact:** Mr. Williams**· Date of preparation / last revision** 11/15/2024 / -**· Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 14)

Printing date 11/15/2024

Reviewed on 11/15/2024

**Trade name: Steelkote 800 High Build Epoxy Primer Gray**

(Contd. of page 13)

vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flam. Liq. 3: Flammable liquids – Category 3  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Skin Sens. 1: Skin sensitisation – Category 1  
Muta. 1B: Germ cell mutagenicity – Category 1B  
Carc. 1A: Carcinogenicity – Category 1A

US