



## 1 Identification

- **Product identifier**
- **Trade name:** 853 Epoxy Primer Medium Gray Part A
- **Article number:** 853G
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Baril Coatings USA  
401 Growth Parkway  
Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 1)

· **Hazard-determining components of labeling:**

titanium dioxide

Quartz (SiO<sub>2</sub>)· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 2

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = \*2

Fire = 2

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

US

(Contd. on page 3)

Trade name: 853 Epoxy Primer Medium Gray Part A

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

13463-67-7	titanium dioxide	>10-≤25%
7727-43-7	barium sulphate, natural	>10-≤25%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>10-≤25%
110-43-0	Methyl n-amyl ketone	>10-≤25%
1330-20-7	xylene	>2.5-<10%
108-10-1	4-methylpentan-2-one	≥0.1-≤2.5%
100-41-4	ethylbenzene	≥0.1-≤2.5%
14808-60-7	Quartz (SiO <sub>2</sub> )	≥0.1-≤2.5%
1333-86-4	Carbon black	≥0.1-≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 3)

*Do not flush with water or aqueous cleansing agents***Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***Protective Action Criteria for Chemicals****PAC-1:**

13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
25036-25-3	Diglycidyl ether of bisphenol A	12 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	150 ppm
1330-20-7	xylene	130 ppm
7779-90-0	trizinc bis(orthophosphate)	12 mg/m <sup>3</sup>
1314-13-2	zinc oxide	10 mg/m <sup>3</sup>
1344-28-1	aluminium oxide	15 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one	75 ppm
112926-00-8	amorphous silica (silica gel, precipitated silica)	18 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	14 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m <sup>3</sup>
108-38-3	m-xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm

**PAC-2:**

13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
25036-25-3	Diglycidyl ether of bisphenol A	130 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	670 ppm
1330-20-7	xylene	920* ppm
7779-90-0	trizinc bis(orthophosphate)	36 mg/m <sup>3</sup>
1314-13-2	zinc oxide	15 mg/m <sup>3</sup>
1344-28-1	aluminium oxide	170 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one	500 ppm
112926-00-8	amorphous silica (silica gel, precipitated silica)	200 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	110 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m <sup>3</sup>
108-38-3	m-xylene	920 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>

(Contd. on page 5)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 4)

123-86-4	n-butyl acetate	200 ppm
<b>PAC-3:</b>		
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
25036-25-3	Diglycidyl ether of bisphenol A	790 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	4000* ppm
1330-20-7	xylene	2500* ppm
7779-90-0	trizinc bis(orthophosphate)	220 mg/m <sup>3</sup>
1314-13-2	zinc oxide	2,500 mg/m <sup>3</sup>
1344-28-1	aluminium oxide	990 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one	3000* ppm
112926-00-8	amorphous silica (silica gel, precipitated silica)	1,200 mg/m <sup>3</sup>
1314-23-4	zirconium dioxide	680 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m <sup>3</sup>
108-38-3	m-xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

(Contd. on page 6)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 5)

**7727-43-7 barium sulphate, natural**

PEL Long-term value:  $15 \times 5^{**} \text{ mg/m}^3$   
\*total dust \*\*respirable fraction

REL Long-term value:  $10 \times 5^{**} \text{ mg/m}^3$   
\*total dust \*\*respirable fraction

TLV Long-term value:  $5 \times \text{mg/m}^3$   
\*inhalable fraction; E

**110-43-0 Methyl n-amyl ketone**

PEL Long-term value:  $465 \text{ mg/m}^3$ , 100 ppm

REL Long-term value:  $465 \text{ mg/m}^3$ , 100 ppm

TLV Long-term value:  $233 \text{ mg/m}^3$ , 50 ppm

**1330-20-7 xylene**

PEL Long-term value:  $435 \text{ mg/m}^3$ , 100 ppm

REL Short-term value:  $655 \text{ mg/m}^3$ , 150 ppm  
Long-term value:  $435 \text{ mg/m}^3$ , 100 ppm

TLV Short-term value:  $651 \text{ mg/m}^3$ , 150 ppm  
Long-term value:  $434 \text{ mg/m}^3$ , 100 ppm  
BEI

**108-10-1 4-methylpentan-2-one**

PEL Long-term value:  $410 \text{ mg/m}^3$ , 100 ppm

REL Short-term value:  $300 \text{ mg/m}^3$ , 75 ppm  
Long-term value:  $205 \text{ mg/m}^3$ , 50 ppm

TLV Short-term value:  $307 \text{ mg/m}^3$ , 75 ppm  
Long-term value:  $82 \text{ mg/m}^3$ , 20 ppm  
BEI

**100-41-4 ethylbenzene**

PEL Long-term value:  $435 \text{ mg/m}^3$ , 100 ppm

REL Short-term value:  $545 \text{ mg/m}^3$ , 125 ppm  
Long-term value:  $435 \text{ mg/m}^3$ , 100 ppm

TLV Long-term value:  $87 \text{ mg/m}^3$ , 20 ppm  
BEI

**14808-60-7 Quartz (SiO<sub>2</sub>)**

PEL Long-term value:  $0.05 \times \text{mg/m}^3$   
\*resp. dust;  $30 \text{ mg/m}^3 / \% \text{SiO}_2 + 2$

REL Long-term value:  $0.05 \times \text{mg/m}^3$   
\*respirable dust; See Pocket Guide App. A

TLV Long-term value:  $0.025 \times \text{mg/m}^3$   
\*as respirable fraction

**1333-86-4 Carbon black**

PEL Long-term value:  $3.5 \text{ mg/m}^3$

REL Long-term value:  $3.5 \times \text{mg/m}^3$   
\*0.1 in presence of PAHs; See Pocket Guide Apps. A+C

TLV Long-term value:  $3 \times \text{mg/m}^3$   
\*inhalable fraction

(Contd. on page 7)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 6)

**Ingredients with biological limit values:****1330-20-7 xylene**

BEI 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

**108-10-1 4-methylpentan-2-one**

BEI 1 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: MIBK

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical  
 Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

US

(Contd. on page 8)



Trade name: 853 Epoxy Primer Medium Gray Part A

(Contd. of page 7)

**9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Liquid

**Color:**

Grey

· **Odor:**

Solvent-like

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition****Melting point/Melting range:**

Undetermined.

**Boiling point/Boiling range:**

139 °C (282.2 °F)

· **Flash point:**

41 °C (105.8 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

533 °C (991.4 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:****Lower:**

1 Vol %

**Upper:**

5.5 Vol %

· **Vapor pressure at 20 °C (68 °F):**

3.5 hPa (2.6 mm Hg)

· **Density at 20 °C (68 °F):**1.7 g/cm<sup>3</sup> (14.19 lbs/gal)· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with****Water:**

Miscible

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:****Dynamic:**

Not determined.

**Kinematic:**

Not determined.

· **Solvent content:****Organic solvents:**

18.1 %

**VOC content:**

18.11 %

307.9 g/l / 2.57 lb/gal

**Solids content:**

69.0 % (by weight)

· **Other information:**

No further relevant information available.

**10 Stability and reactivity**· **Reactivity** No further relevant information available.

(Contd. on page 9)



Trade name: 853 Epoxy Primer Medium Gray Part A

(Contd. of page 8)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
- **7779-90-0 trizinc bis(orthophosphate)**
- Oral | LD50 | >5,000 mg/kg (rat)
- **1314-13-2 zinc oxide**
- Oral | LD50 | >5,000 mg/kg (rat)
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
108-10-1	4-methylpentan-2-one	2B
100-41-4	ethylbenzene	2B
7631-86-9	silicon dioxide, chemically prepared	3
108-38-3	m-xylene	3
106-42-3	p-xylene	3
95-47-6	o-xylene	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
1333-86-4	Carbon black	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.		
------------------------------------	--	--

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 10)

**Trade name: 853 Epoxy Primer Medium Gray Part A**




(Contd. of page 9)

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Danger not to drinking water if even small quantities leak into the ground.*  
*Also poisonous for fish and plankton in water bodies.*  
*Toxic for aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.


**14 Transport information**

- |   |   |
|---|---|
| · <b>UN-Number</b>  | UN1263  |
| · <b>DOT, IMDG, IATA</b>  |   |
| · <b>UN proper shipping name</b>  | Paint   |
| · <b>DOT</b>  | PAINT (trizinc bis(orthophosphate), zinc oxide), MARINE POLLUTANT |
| · <b>IMDG</b>   | PAINT   |
| · <b>IATA</b>   |   |
| · <b>Transport hazard class(es)</b>   |   |
| · <b>DOT</b>  |   |
|    |   |
| · <b>Class</b>  | 3 Flammable liquids   |
| · <b>Label</b>  | 3   |
| · <b>IMDG</b>   |   |
|   |   |
| · <b>Class</b>  | 3 Flammable liquids   |

(Contd. on page 11)

Trade name: 853 Epoxy Primer Medium Gray Part A

(Contd. of page 10)

· <b>Label</b>	3
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	Symbol (fish and tree)
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

7727-43-7	barium sulphate, natural
1330-20-7	xylene
7779-90-0	trizinc bis(orthophosphate)
1314-13-2	zinc oxide
1344-28-1	aluminium oxide
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene
108-38-3	m-xylene

(Contd. on page 12)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 11)

106-42-3	p-xylene
95-47-6	o-xylene
<b>· TSCA (Toxic Substances Control Act):</b>	
13463-67-7	titanium dioxide
7727-43-7	barium sulphate, natural
25036-25-3	Diglycidyl ether of bisphenol A
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
110-43-0	Methyl n-amyl ketone
1330-20-7	xylene
7779-90-0	trizinc bis(orthophosphate)
1314-13-2	zinc oxide
1344-28-1	aluminium oxide
108-10-1	4-methylpentan-2-one
1314-23-4	zirconium dioxide
100-41-4	ethylbenzene
7631-86-9	silicon dioxide, chemically prepared
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane
108-38-3	m-xylene
64742-47-8	Distillates (petroleum), hydrotreated light
106-42-3	p-xylene
95-47-6	o-xylene
108-65-6	2-methoxy-1-methylethyl acetate
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black
123-86-4	n-butyl acetate
1119-40-0	Pentanedioic acid, 1,5-dimethyl ester

**· Proposition 65****· Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

108-10-1	4-methylpentan-2-one
----------	----------------------

**· Carcinogenic categories****· EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
1330-20-7	xylene	I
7779-90-0	trizinc bis(orthophosphate)	D, I, II

(Contd. on page 13)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 12)

1314-13-2	zinc oxide	D, I, II
108-10-1	4-methylpentan-2-one	I
100-41-4	ethylbenzene	D
108-38-3	m-xylene	I
106-42-3	p-xylene	I
95-47-6	o-xylene	I

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
1344-28-1	aluminium oxide	A4
1314-23-4	zirconium dioxide	A4
100-41-4	ethylbenzene	A3
108-38-3	m-xylene	A4
106-42-3	p-xylene	A4
95-47-6	o-xylene	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

titanium dioxide

Quartz (SiO<sub>2</sub>)

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 14)

**Trade name: 853 Epoxy Primer Medium Gray Part A**

(Contd. of page 13)

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Mr. Williams

· **Date of preparation / last revision** 05/22/2024 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 1A: Carcinogenicity – Category 1A