

Page 1/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 12/13/2024

Reviewed on 12/13/2024 1 Identification · Product identifier · Trade name: Activator 9100 · Article number: ACT9100 · Details of the supplier of the safety data sheet · Manufacturer/Supplier: Baril Coating USA, LLC 401 Growth Parkway Angola, IN 46703 · Information department: Product safety department · Emergency telephone number: During normal opening times: +1 (260) 665-8431 2 Hazard(s) identification · Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapor. GHS08 Health hazard H361 Suspected of damaging fertility or the unborn child. Repr. 2 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS07 Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US

Page 2/12

Printing date 12/13/2024

#### Trade name: Activator 9100

· Hazard pictograms

Reviewed on 12/13/2024

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS


GHS02 GHS07 GHS08 · Signal word Warning · Hazard-determining components of labeling: Methvl n-amvl ketone Hexamethylene Diisocyanate Homopolymer toluene xylene Hazard statements Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)

#### Trade name: Activator 9100

Safety Data Sheet acc. to OSHA HCS

Reviewed on 12/13/2024

(Contd. of page 2)



### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Hazardous substances listed below.

· Dangerous components:		
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>50-≤100%
28182-81-2	Hexamethylene Diisocyanate Homopolymer	20-≤25%
	Methyl n-amyl ketone	>10-≤25%
1330-20-7	•	≤2.5%
123-86-4	n-butyl acetate	≤2.5%
108-88-3	toluene	0.1-≤2.5%

## 4 First-aid measures

#### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/13/2024

Trade name: Activator 9100

Reviewed on 12/13/2024

(Contd. of page 3)

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

Wear protect Environment Methods ar Absorb with Dispose cor Ensure adect Do not flush Reference at See Section See Section See Section	recautions, protective equipment and emergency procedures trive equipment. Keep unprotected persons away. Intal precautions: Do not allow to enter sewers/ surface or ground water. Ind material for containment and cleaning up: liquid-binding material (sand, diatomite, acid binders, universal binders, sawo ataminated material as waste according to item 13. quate ventilation. with water or aqueous cleansing agents to other sections 7 for information on safe handling. 8 for information on personal protection equipment. 13 for disposal information. Action Criteria for Chemicals	lust).
· PAC-1:		
	Hexamethylene Diisocyanate Homopolymer	7.8 mg/m³
	Methyl n-amyl ketone	150 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
108-88-3	toluene	67 ppm
· PAC-2:		
28182-81-2	Hexamethylene Diisocyanate Homopolymer	86 mg/m³
110-43-0	Methyl n-amyl ketone	670 ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
108-88-3	toluene	560 ppm
· PAC-3:		
28182-81-2	Hexamethylene Diisocyanate Homopolymer	510 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	4000* ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
108-88-3	toluene	3700* ppm
		US

(Contd. on page 5)

#### Trade name: Activator 9100

Safety Data Sheet acc. to OSHA HCS

Reviewed on 12/13/2024

(Contd. of page 4)

### 7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

110-4	43-0 Methyl n-amyl ketone	
PEL	Long-term value: 465 mg/m³, 100 ppm	
REL	Long-term value: 465 mg/m³, 100 ppm	
TLV	Long-term value: 233 mg/m³, 50 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI	
123-8	86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm	
108-8	88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL		
TLV	Long-term value: 75 mg/m³, 20 ppm BEI	
I	(Contd. on p	age

#### Trade name: Activator 9100

Reviewed on 12/13/2024

Safety Data Sheet acc. to OSHA HCS

Inar	(Contd. of page (Contd. of page )
	0-20-7 xylene
	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
108-	88-3 toluene
BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)
Avoi Brea In ca expo	sh hands before breaks and at the end of work. id contact with the eyes and skin. <b>athing equipment:</b> ase of brief exposure or low pollution use respiratory filter device. In case of intensive or long osure use respiratory protective device that is independent of circulating air. t <b>ection of hands:</b>
	Protective gloves
Due prep	glove material has to be impermeable and resistant to the product/ the substance/ the preparation to missing tests no recommendation to the glove material can be given for the product/ to paration/ the chemical mixture.
degr <b>Mate</b>	ection of the glove material on consideration of the penetration times, rates of diffusion and t radation <b>erial of gloves</b>
qual subs be c	selection of the suitable gloves does not only depend on the material, but also on further marks lity and varies from manufacturer to manufacturer. As the product is a preparation of sever stances, the resistance of the glove material can not be calculated in advance and has therefore hecked prior to the application. <b>etration time of glove material</b>
	exact break through time has to be found out by the manufacturer of the protective gloves and h
	e observed.
-	(Contd. on page

(Contd. on page 7) - US -

Safety Data Sheet acc. to OSHA HCS Reviewed on 12/13/2024

Printing date 12/13/2024

## Trade name: Activator 9100

(Contd. of page 6)

## • Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

General Information	
Appearance: Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	139 °C (282.2 °F)
Flash point:	41 °C (105.8 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	480 °C (896 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	5.5 Vol %
Vapor pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
Density at 20 °C (68 °F):	1.15 g/cm³ (9.6 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Miscible
Partition coefficient (n-octanol/water	
Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	20.6 %
VOC content:	20.59 %
	236.8 g/l / 1.98 lb/gal
Solids content:	21.2 % (by weight)
	(Contd. on page

Page 8/12

Safety Data Sheet acc. to OSHA HCS

Printing date 12/13/2024

## Trade name: Activator 9100

Reviewed on 12/13/2024

(Contd. of page 7)

· Other infomation:

No further relevant information available.

## 10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

### · LD/LC50 values that are relevant for classification:

### 28182-81-2 Hexamethylene Diisocyanate Homopolymer

Oral LD50 >5,000 mg/kg (rat)

Inhalative LC50/4 h 0.554 mg/l (rat)

### 110-43-0 Methyl n-amyl ketone

	, , ,	
Oral	LD50	1,670 mg/kg (rat)
Dermal	LD50	12,600 mg/kg (rabbit)

## Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.

### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

## · Carcinogenic categories

•	rnational Agency for Research on Cancer)
1330-20-7	•
108-88-3	toluene
· NTP (Natio	onal Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

 $\cdot$  **Persistence and degradability** No further relevant information available.

(Contd. on page 9)

3 3

US

#### Trade name: Activator 9100

acc. to OSHA HCS Reviewed on 12/13/2024

Safety Data Sheet

(Contd. of page 8)

- <sup>.</sup> Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### 13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint related material	
IMDG, IATA	PAINT RELATED MATERIAL	
Transport hazard class(es)		
DOT		
3		
Class	3 Flammable liquids	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group		
DOT, IMĎG, IATA	11	
Environmental hazards:	Not applicable.	

#### Trade name: Activator 9100

Safety Data Sheet acc. to OSHA HCS

Reviewed on 12/13/2024

	(Contd. of pag
· Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	36
· EMS Number:	F-E,S-E
· Stowage Category	A
· Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
-	On cargo aircraft only: 220 L
·IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
· · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

## 15 Regulatory information

 $^{\cdot}$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $^{\cdot}$  Sara

· Section 35	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	13 (Specific toxic chemical listings):	
1330-20-7	xylene	
108-88-3	toluene	
· TSCA (Tox	xic Substances Control Act):	
All ingredie	ents are listed.	
· Propositio	on 65	
	s known to cause cancer:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
108-88-3 t	oluene	
<sup>.</sup> Carcinoge	enic categories	
· EPA (Envi	ronmental Protection Agency)	
1330-20-7	xylene	1
108-88-3	toluene	I
· TLV (Three	shold Limit Value established by ACGIH)	
1330-20-7	xylene	A
108-88-3	toluene	A
		(Contd. on page 1

### Trade name: Activator 9100

Reviewed on 12/13/2024

(Contd. of page 10) · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Warning · Hazard-determining components of labeling: Methyl n-amyl ketone Hexamethylene Diisocyanate Homopolymer toluene xvlene · Hazard statements Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eve irritation. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

(Contd. on page 12)

JS -

Safety Data Sheet acc. to OSHA HCS

Reviewed on 12/13/2024

Printing date 12/13/2024

Trade name: Activator 9100

Store locked up.

(Contd. of page 11)

Dispose of contents/container in accordance with local/regional/national/international regulations. **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Williams
- · Date of preparation / last revision 12/13/2024 / -

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

us -