



1 Identification

- **Product identifier**
- **Trade name:** FleetSpec Toner Light Aluminum
- **Article number:** T513
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Baril Coatings USA
401 Growth Parkway
Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Naphtha (petroleum), hydrotreated heavy
Solvent naphtha (petroleum), light arom.

· **Hazard statements**

Flammable liquid and vapor.
Causes skin irritation.
May cause genetic defects.
May cause cancer.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = *2
Fire = 3
Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Hazardous substances listed below.

(Contd. on page 3)

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 2)

· Dangerous components:		
1330-20-7	xylene	>25-≤50%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	>2.5-≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-≤2.5%
123-86-4	n-butyl acetate	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 02/07/2025

Reviewed on 02/07/2025

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 3)

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

1330-20-7	xylene	130 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
123-86-4	n-butyl acetate	5 ppm

· PAC-2:

1330-20-7	xylene	920* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
123-86-4	n-butyl acetate	200 ppm

· PAC-3:

1330-20-7	xylene	2500* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
123-86-4	n-butyl acetate	3000* ppm

7 Handling and storage**· Handling:****· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:** No special requirements.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** Keep receptacle tightly sealed.**· Specific end use(s)** No further relevant information available.**8 Exposure controls/personal protection****· Additional information about design of technical systems:** No further data; see item 7.**· Control parameters****· Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1330-20-7 xylenePEL Long-term value: 435 mg/m³, 100 ppmREL Short-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTLV Short-term value: 651 mg/m³, 150 ppmLong-term value: 434 mg/m³, 100 ppm

BEI

(Contd. on page 5)

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 4)

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

Ingredients with biological limit values:**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

US

(Contd. on page 6)

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 5)

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Liquid
Color:	Silver-colored
Odor:	Solvent-like
Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137-143 °C (278.6-289.4 °F)

· **Flash point:** 30 °C (86 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 500 °C (932 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	7 Vol %

· **Vapor pressure at 20 °C (68 °F):** 6.7-8.2 hPa (5-6.2 mm Hg)· **Density at 20 °C (68 °F):** 0.94 g/cm³ (7.84 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**

Water: Miscible

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:**

Organic solvents:	47.7 %
VOC content:	47.68 %
	448.2 g/l / 3.74 lb/gal

· **Solids content:** 52.3 %· **Other information:** No further relevant information available.**10 Stability and reactivity**· **Reactivity** No further relevant information available.

(Contd. on page 7)

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 6)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
Carcinogenic.
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
-----------	--------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Printing date 02/07/2025

Reviewed on 02/07/2025

Trade name: FleetSpec Toner Light Aluminum



(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1263
· DOT, IMDG, IATA	
· UN proper shipping name	Paint
· DOT	PAINT
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.

(Contd. on page 9)

Printing date 02/07/2025

Reviewed on 02/07/2025

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 8)

· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 | xylene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 | xylene

I

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 | xylene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 10)

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 9)

· **GHS label elements***The product is classified and labeled according to the Globally Harmonized System (GHS).*· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:***Naphtha (petroleum), hydrotreated heavy**Solvent naphtha (petroleum), light arom.*· **Hazard statements***Flammable liquid and vapor.**Causes skin irritation.**May cause genetic defects.**May cause cancer.*· **Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Wash thoroughly after handling.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**In case of fire: Use for extinction: CO₂, powder or water spray.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **National regulations:**· **Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.***16 Other information***This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*· **Department issuing SDS:** *Environment protection department.*· **Contact:** *Mr. Williams*

(Contd. on page 11)

Printing date 02/07/2025

Reviewed on 02/07/2025

Trade name: FleetSpec Toner Light Aluminum

(Contd. of page 10)

· **Date of preparation / last revision** 02/07/2025 / -· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

US