

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : DTM-7085 Mid-Temp Reducer
Product code : RED-0062 REV1

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Color By Design, Inc.
407 W. Main
Haven, KS 67543
T 620-465-2600
info@colorbydesigninc.com

1.4. Emergency telephone number

Emergency number : 620-728-4044

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	Highly flammable liquid and vapour
Acute toxicity (inhalation:vapour) Category 3	Toxic if inhaled
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Germ cell mutagenicity Category 1B	May cause genetic defects
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity (single exposure) Category 3	May cause drowsiness or dizziness

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Highly flammable liquid and vapour
Causes serious eye irritation
Toxic if inhaled
May cause drowsiness or dizziness
May cause genetic defects
Suspected of causing cancer

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

If exposed or concerned: Get medical advice/attention.
Call a poison center or doctor
Call a poison center or doctor if you feel unwell
Specific treatment (see supplemental first aid instruction on this label)
If eye irritation persists: Get medical advice/attention.
In case of fire: Use media other than water to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name : DTM-7085 Mid-Temp Reducer

Name	Product identifier	%	GHS US classification
Aromatic Hydrocarbon	(CAS-No.) 64742-95-6	51.0905 4317125 62	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
solvent naphtha (petroleum), light aromatic	(CAS-No.) 64742-95-6	> 25.1510 0404931 2152	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
2-Propanol	(CAS-No.) 67-63-0	21.1804 7158470 71	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1,2,4-Trimethylbenzene	(CAS-No.) 95-63-6	< 8.12961 7470484 736	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
Glycidoxypropyltrimethoxysilane	(CAS-No.) 2530-83-8	0.58098 2662192 955 - 1.51055 4921701 683	Eye Dam. 1, H318
1-butoxy-2-propanol	(CAS-No.) 5131-66-8	0.58098 2662192 955 - 1.16196 5324385 91	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2, H319
cumene	(CAS-No.) 98-82-8	< 0.27945 5600547 913	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a doctor.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Reactivity : Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DTM-7085 Mid-Temp Reducer

ACGIH	ACGIH TWA (ppm)	100 ppm
-------	-----------------	---------

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DTM-7085 Mid-Temp Reducer		
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
solvent naphtha (petroleum), light aromatic (64742-95-6)		
ACGIH	ACGIH TWA (mg/m³)	200 mg/m³
ACGIH	ACGIH TWA (ppm)	200 ppm
OSHA	OSHA PEL (TWA) (ppm)	200
OSHA	OSHA PEL (STEL) (ppm)	500
cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	50 ppm (Cumene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	Lung cancer; liver and lung dam; A2 (Suspected Human Carcinogen: Human data are accepted as adequate in quality but are conflicting or insufficient to classify the agent as a confirmed human carcinogen; OR, the agent is carcinogenic in experimental animals at dose(s), by route(s) of exposure, at site(s), of histologic type(s), or by mechanism(s) considered relevant to worker exposure. The A2 is used primarily when there is limited evidence or carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals with relevance to humans)
OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
1,2,4-Trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Aromatic Hydrocarbon (64742-95-6)		
Not applicable		
2-Propanol (67-63-0)		
ACGIH	ACGIH TWA (ppm)	200 ppm (2-propanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	400 ppm (2-propanol; USA; Short time value; TLV - Adopted Value)
Glycidoxypropyltrimethoxysilane (2530-83-8)		
Not applicable		
1-butoxy-2-propanol (5131-66-8)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): No data available on colour Colourless
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): No data available on odour Irritating/pungent odour Aromatic odour Alcohol odour Stuffy odour Mild odour Ester smell Ether-like odour Characteristic odour Pleasant odour Commercial/unpurified substance: irritating/pungent odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 165 - 340 °F
Flash point	: 57 °F
Relative evaporation rate (butyl acetate=1)	: 1.9
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 33 mm Hg @20 °C
Relative vapor density at 20 °C	: No data available
Relative density	: 0.88
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:vapour: Toxic if inhaled.

DTM-7085 Mid-Temp Reducer	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE US (vapors)	3.000 mg/l/4h

solvent naphtha (petroleum), light aromatic (64742-95-6)	
LD50 oral rat	3492 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	> 6193 ppm/4h
ATE US (oral)	3492.000 mg/kg body weight

cumene (98-82-8)	
LD50 oral rat	> 2000 mg/kg (Rat; Other; Literature study; 4000 mg/kg bodyweight; Rat; Other; Inconclusive, insufficient data)
LD50 dermal rabbit	10578 mg/kg (Rabbit; Literature study; Other)
LC50 inhalation rat (mg/l)	40 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	8000 ppm/4h (Rat; Literature study)
ATE US (dermal)	10578.000 mg/kg body weight
ATE US (gases)	8000.000 ppmV/4h
ATE US (vapors)	40.000 mg/l/4h
ATE US (dust, mist)	40.000 mg/l/4h

1,2,4-Trimethylbenzene (95-63-6)	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	18.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

2-Propanol (67-63-0)	
LD50 dermal rabbit	12870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 16.4; Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
ATE US (dermal)	12870.000 mg/kg body weight
ATE US (vapors)	73.000 mg/l/4h
ATE US (dust, mist)	73.000 mg/l/4h

Glycidoxypropyltrimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value)
LD50 dermal rabbit	4250 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value)
LC50 inhalation rat (mg/l)	> 5.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value)
ATE US (oral)	8025.000 mg/kg body weight
ATE US (dermal)	4250.000 mg/kg body weight

1-butoxy-2-propanol (5131-66-8)	
LD50 oral rat	3300 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value)
LC50 inhalation rat (ppm)	> 651 ppm (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value)
ATE US (oral)	3300.000 mg/kg body weight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : Suspected of causing cancer.

DTM-7085 Mid-Temp Reducer	
IARC group	2B - Possibly carcinogenic to humans, 3 - Not classifiable

cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

2-Propanol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Target organ(s)	liver kidneys central nervous system

cumene (98-82-8)	
Target organ(s)	liver kidneys central nervous system

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

cumene (98-82-8)	
EC50 Daphnia 1	2.14 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

1,2,4-Trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	2.356 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)

2-Propanol (67-63-0)	
LC50 fish 2	9640 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 2	13299 mg/l (EC50; Other; 48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (EC50; UBA; 72 h; Scenedesmus subspicatus)

Glycidoxypolytrimethoxysilane (2530-83-8)	
LC50 fish 1	55 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	473 - 710 mg/l (48 h, Daphnia magna, Literature)
LC50 fish 2	237 mg/l (96 h, Salmo gairdneri, Static system, Literature)
ErC50 (algae)	350 mg/l (72 h, Selenastrum capricornutum, Literature)

1-butoxy-2-propanol (5131-66-8)	
LC50 fish 1	560 - 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value)

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-butoxy-2-propanol (5131-66-8)	
EC50 Daphnia 1	> 1000 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

cumene (98-82-8)	
Persistence and degradability	Inherently biodegradable. Not readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.28 g O ₂ /g substance
Chemical oxygen demand (COD)	2.42 g O ₂ /g substance
ThOD	3.2 g O ₂ /g substance
BOD (% of ThOD)	0.4

1,2,4-Trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance

2-Propanol (67-63-0)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.19 g O ₂ /g substance
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance
ThOD	2.4 g O ₂ /g substance

Glycidoxypyltrimethoxysilane (2530-83-8)	
Persistence and degradability	Not readily biodegradable in water.

1-butoxy-2-propanol (5131-66-8)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6

cumene (98-82-8)	
BCF fish 1	35.5 (BCF)
BCF other aquatic organisms 1	94.69 (BCF; BCFBAF v3.00)
Log Pow	3.66 (Experimental value; 3.55; Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

1,2,4-Trimethylbenzene (95-63-6)	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).

Aromatic Hydrocarbon (64742-95-6)	
Log Pow	2.1 - 6

2-Propanol (67-63-0)	
Log Pow	0.05 (Weight of evidence approach; Other; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Glycidoxypyltrimethoxysilane (2530-83-8)	
Log Pow	-0.92 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

1-butoxy-2-propanol (5131-66-8)	
Log Pow	1.2 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cumene (98-82-8)	
Log Koc	Koc,884; Calculated value; log Koc; 2.946; Calculated value
1,2,4-Trimethylbenzene (95-63-6)	
Surface tension	0.029 N/m
Log Koc	log Koc,3.04; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
2-Propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Glycidoxypropyltrimethoxysilane (2530-83-8)	
Ecology - soil	No (test)data on mobility of the substance available.
1-butoxy-2-propanol (5131-66-8)	
Surface tension	57.6 N/m (20 °C, 100 vol %)
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, III
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG)	: UN 1263 PAINT, 3, III
UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

Air transport

Transport document description (IATA)	: UN 1263 Paint, 3, III
UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
1,2,4-Trimethylbenzene (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aromatic Hydrocarbon (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Propanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

Glycidoxypolytrimethoxysilane (2530-83-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1-butoxy-2-propanol (5131-66-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

cumene (98-82-8)

Listed on the Canadian DSL (Domestic Substances List)

1,2,4-Trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List)

Aromatic Hydrocarbon (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

2-Propanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Glycidoxypolytrimethoxysilane (2530-83-8)

Listed on the Canadian DSL (Domestic Substances List)

1-butoxy-2-propanol (5131-66-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

cumene (98-82-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

cumene (98-82-8)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

1,2,4-Trimethylbenzene (95-63-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

DTM-7085 Mid-Temp Reducer

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Propanol (67-63-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 04/14/2018

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product