



TECHNICAL DATASHEET

DRY GUIDE COAT

ART. NO: #125.001 (black), 125.002 (orange)

Carworx DRY GUIDE COAT is a unique control powder that enhances surface imperfections such as pinholes and scratches, making them visible while sanding. Unlike liquid and aerosol guide coats, DRY GUIDE COAT requires no masking before use and has no dry time after application, making it extremely efficient and easy to use. Additionally, the dry formula contains no added solvents and doesn't clog the sandpaper, increasing body shop productivity while ensuring an easier clean-up.

FEATURES

- ✓ Reveals surface imperfections such as pinholes and scratches
- ✓ Dry consistency requires no masking and no drying time
- ✓ Can be used when wet or dry sanding
- ✓ Does not contain any intentionally added solvents
- ✓ Highlights body lines

COMPATIBLE SURFACES

- ✓ Can be applied over water or solvent based primers and coatings

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

HANDLING

1. Apply one coat of DRY GUIDE COAT on surface with applicator.
2. Sand until guide coat is completely gone.
3. Repeat if required.

PRODUCT DATA

Composition: Powder

Appearance: Black, Orange

Shelf Life: Minimum 2 years in unopened container

Package: 100 g plastic container

FP: Non-flammable

pH: 6.39

Safety Data Sheet (SDS) is available on our website