



TECHNICAL DATASHEET

UNIFLEX SEAM SEALER

*AVAILABLE IN 3 COLORS

ART. NO: #135.691 (Black - 310ml), #135.692 (Clear - 310ml), #135.693 (White - 310ml),

UNIFLEX SEAM SEALER is a high performance, single part sealer that is not only cost effective, but extremely efficient. With excellent adhesion to a variety of surfaces including metal, rubber, glass, wood and concrete, this high solids sealer can be used for both sealing and adhesive applications. Its non-sag formula allows for easy caulking in both vertical and horizontal joints and can be painted within 30 minutes.

FEATURES

- ✓ High elasticity with minimal shrinking
- ✓ Cures fast to a tough rubber consistency
- ✓ Excellent high and low temperature flexibility
- ✓ Fast drying and paintable within 30 minutes
- ✓ Non-staining
- ✓ Non-sagging consistency
- ✓ Water resistant
- ✓ Excellent adhesion
- ✓ Can be applied directly to metal surfaces

APPLICATION

Ideal for general purpose sealing and bedding applications subject to distortions on automobiles, trucks and trailers. Can also be used for channel glazing, tent patching, tile and bathtub caulking and on masonry joints.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

HANDLING

1. Clean the repair area ensuring that the surface is free of grease and oil.
2. Cut cartridge nozzle to desired bead size and begin caulking.
3. Allow to dry for 30 minutes before painting. (Full cure: +24 hours).

PRODUCT DATA

Color: Black, Transparent, White

Consistency: Soft / non-sag

Solids: 75%

Tensile Strength: > 600 psi

Elongation: In excess of 300%

Modulus (100%): 140 psi

Weight/Gallon: 11b

Serviceable temperature: - 20°F to -160°F

Flash Point: 45°F (tag closed cup)

Shelf Life: 12 months in original sealed container

Package: 310 ml

Number per case: 12

Safety Data Sheet (SDS) is available on our website