

GENERAL INFORMATION

90-851 WaterBase Degreaser is a specially developed degreaser for substrates to be coated with MM 900 - 9999 WaterBase 900+ Series. Use wipe on/wipe off method, avoid evaporation of the 90-851 De Beer Waterbase Anti-Static Degreaser to insure all the dirt is removed.

MIXING RATIO



-

GUN SETUP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

APPLICATION



-

FLASH OFF AND DRY TIMES



AIR DRY 20 °C / 68 °F		FORCED DRY 60°C / 140°F	
Flash off	-	Flash off	-
Dust-free	-	Dust-free	-
Dry-to-handle	-	Dry-to-handle	-
Dry-to-tape	-	Dry-to-tape	-
Dry-to-sand	-	Dry-to-sand	-
Dry-to-polish	-	Dry-to-polish	-

SUBSTRATES



-

POTLIFE



-

COMPONENTS



-

ADDITIVES



-

SURFACE PREPARATION



-



NEXT LAYER



-

PHYSICAL DATA

RTS REGULATORY DATA:		A5-IS
		Ready for Use
	lb./gal	g/L
Actual VOC	0.20 Max.	25 Max.
Regulatory VOC (less water and exempt solvents)	-	-
Density	7.5 – 8.5	900 – 1020
	WT. %	VOL. %
Total Solids Content	0.25 – 0.50	0.25 – 0.50
Total Volatile Content	99.50 – 99.75	99.50 – 99.75
Water	95 – 98	95 – 98
Exempt Compound Content	0	0
Coating Category	Pretreatment Coating/Washprimer	

PROTECTION



Use suitable respiratory protection (*we recommend the use of a fresh air supply respirator*).

For more detailed information please visit the following link for the Safety Data Sheet:

<https://sds.de-beer.com>

CLEANUP**STORAGE/SHELF LIFE**

Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).

NOTES

Do not use as Gun Cleaner. INFORMATION: If used as instructed, this product is designed to comply with Volatile Organic Compound (VOC) Standards in low-VOC jurisdictions, for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use.