

# SAFETY DATA SHEET

Revision date 03-Feb-2021

Version 30

Supersedes Date: 26-Sep-2020

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product Code** 9555.L01

**Product Name** 1L MM555 BB 500 Series Transparent Red

### Other means of identification

No information available

### Recommended use of the chemical and restrictions on use

Paint, Coatings

### Details of the supplier of the safety data sheet

See section 16 for more information

Valspar Automotive  
101 W. Prospect Avenue  
Cleveland, OH 44115 USA  
(216) 566-2902

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

### Emergency telephone number

United States of America 800-424-9300

## Section 2: HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

### Label elements



**Signal word**

**DANGER**

### **HAZARD STATEMENTS**

Flammable liquid and vapor

Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing cancer  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
May cause damage to the following organs through prolonged or repeated exposure: Ears

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

##### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

##### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

##### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

#### OTHER HAZARDS

Not applicable.

#### UNKNOWN ACUTE TOXICITY

0% of the mixture consists of ingredient(s) of unknown toxicity.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
n-Butyl acetate	123-86-4	25 - 50
Xylenes	1330-20-7	10 - 25
Propylene glycol monomethyl ether acetate	108-65-6	3 - 5
Ethylbenzene	100-41-4	3 - 5
1-Butanol	71-36-3	1 - 3
Isobutyl alcohol	78-83-1	1 - 3
Butyl methacrylate	97-88-1	0.1 - 0.3
Methyl methacrylate	80-62-6	0.1 - 0.3
Formaldehyde	50-00-0	100 ppm - <0.1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### **Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### Suitable extinguishing media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

### Not to be used for safety reasons:

Strong water jet

### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

### Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

## **Methods and material for containment and cleaning up**

### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

### **Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

## **Section 7: HANDLING AND STORAGE**

### **Precautions for safe handling**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

#### **Incompatible materials**

Strong oxidizing agents.

## **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control parameters**

#### **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

<b>Chemical Name</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>
n-Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
1-Butanol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup>
Isobutyl alcohol 78-83-1	TWA: 50 ppm	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 50 ppm TWA: 150 mg/m <sup>3</sup>
Methyl methacrylate 80-62-6	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	IDLH: 1000 ppm TWA: 100 ppm

			TWA: 410 mg/m <sup>3</sup>
Formaldehyde 50-00-0	Ceiling: 0.3 ppm	TWA: 0.75 ppm STEL: 2 ppm see 29 CFR 1910.1048	IDLH: 20 ppm Ceiling: 0.1 ppm 15 min TWA: 0.016 ppm

### **Appropriate engineering controls**

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### **Individual protection measures, such as personal protective equipment**

#### **Eye/face protection**

Tight sealing safety goggles.

#### **Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### **Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### **Thermal Protection**

No information available

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

### **Information on basic physical and chemical properties**

<b>Physical state</b>	liquid
<b>Appearance</b>	No information available
<b>Odor</b>	Solvent
<b>Color</b>	light red
<b>Odor Threshold</b>	No information available
<b>pH value</b>	No information available
<b>Melting point/freezing point</b>	No information available
<b>Boiling point / boiling range</b>	No information available °C / °F
<b>flash point</b>	25 °C / 77 °F
<b>evaporation rate</b>	No information available
<b>Flammability (solid, gas)</b>	No information available
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>vapor density</b>	No information available
<b>Density (lbs per US gallon)</b>	7.9
<b>specific gravity</b>	.95
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available

### **Other information**

## Section 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	None under normal processing.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Chlorine gas.

## Section 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Eye contact**

Causes serious eye irritation

#### **Skin Contact**

May cause an allergic skin reaction

Causes skin irritation

#### **Ingestion**

May be fatal if swallowed and enters airways

#### **Inhalation**

May cause drowsiness or dizziness

### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Xylenes 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 5000 ppm ( Rat ) 4 h = 29.08 mg/L ( Rat ) 4 h
Propylene glycol monomethyl ether acetate 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	-
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
1-Butanol 71-36-3	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
Isobutyl alcohol 78-83-1	= 2460 mg/kg ( Rat )	= 3400 mg/kg ( Rabbit )	> 6.5 mg/L ( Rat ) 4 h
Butyl methacrylate 97-88-1	= 16 g/kg ( Rat )	= 10181 mg/kg ( Rabbit )	= 4910 ppm ( Rat ) 4 h
Methyl methacrylate 80-62-6	= 7872 mg/kg ( Rat ) 8420 - 10000 mg/kg ( Rat )	> 5 g/kg ( Rabbit ) 5000 - 7500 mg/kg ( Rabbit )	= 7093 ppm ( Rat ) 4 h
Formaldehyde 50-00-0	= 100 mg/kg ( Rat )	= 270 mg/kg ( Rabbit )	= 0.578 mg/L ( Rat ) 4 h

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	29652 Mg/kg
<b>ATEmix (dermal)</b>	7939 Mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	8.7 mg/l
<b>ATEmix (inhalation-vapor)</b>	64 mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-41-4	A3	Group 2B		X
Formaldehyde 50-00-0	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen. A2 - Suspected Human Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans. Group 1 - Carcinogenic to Humans.

NTP (National Toxicology Program)

Known - Known Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

**Skin corrosion/irritation** Causes skin irritation

**Serious eye damage/eye irritation** Causes serious eye irritation

**Skin sensitization** May cause an allergic skin reaction

**Respiratory sensitization** Not applicable

**Germ cell mutagenicity** Not applicable

**Carcinogenicity** Suspected of causing cancer

**Reproductive Toxicity** Not applicable

**Specific target organ toxicity (single exposure)** May cause drowsiness or dizziness

**Specific target organ toxicity (repeated exposure)**

May cause damage to the following organs through prolonged or repeated exposure: Ears

**Aspiration hazard** May be fatal if swallowed and enters airways

## Section 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Environmental precautions Prevent product from entering drains.

### Persistence and degradability

No information available

### Bioaccumulation

No information available

### Mobility

No information available

### Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### **Contaminated packaging**

Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

## Section 14: TRANSPORT INFORMATION

14.1 UN/ID no	<u>DOT</u> UN1263	<u>IMDG</u> UN1263	<u>IATA</u> UN1263
14.2 Proper shipping name	Paint	Paint	Paint
14.3 Hazard Class	3	3	3
14.4 Packing Group	III	III	III

**14.5 Environmental hazard****14.6 Special Provisions**

B1, B52, IB3, T2, TP1, TP29, 367  
**Emergency Response Guide**  
**Number**  
 128

163, 223, 367 955  
**EmS-No**  
 F-E, S-E

A3, A72, A192

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

No information available

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

**International Inventories**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing. (Active List).

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

**US Federal Regulations**

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Xylenes 1330-20-7 10 - 25	1		Present
Ethylbenzene 100-41-4 3 - 5	0.1		Present
1-Butanol 71-36-3 1 - 3	1		
Methyl methacrylate 80-62-6 0.1 - 0.3	1		Present

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			X
Xylenes 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X
Methyl methacrylate 80-62-6	1000 lb			X
Formaldehyde 50-00-0	100 lb			X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
1-Butanol 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Isobutyl alcohol 78-83-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl methacrylate 80-62-6	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Formaldehyde 50-00-0	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations**



**Rule 66 status of product**

Photochemically reactive.

**California Proposition 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**U.S. EPA Label information**

EPA Pesticide registration number Not applicable

**U.S. State Right-to-Know Regulations**

Chemical Name
n-Butyl acetate 123-86-4
Xylenes 1330-20-7
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Propylene glycol monomethyl ether acetate 108-65-6
Ethylbenzene 100-41-4
1-Butanol 71-36-3
Isobutyl alcohol 78-83-1
Formaldehyde 50-00-0

**Section 16: OTHER INFORMATION****HMIS**

Health hazards 3\*

\* = Chronic Health Hazard

Flammability 3

Physical hazards 0

Personal Protection X

Prepared By Product Stewardship

Revision date 03-Feb-2021

Revision Note No information available

**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**