## SAFETY DATA SHEET

Revision date 08-Jul-2020 Version 34 Supersedes Date: 08-Apr-2020

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Code 9987.L01

Product Name 1L MM987 WB 900+ Series Metallic Bright NF

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

Valspar Automotive 101 W. Prospect Avenue Cleveland, OH 44115 USA (216) 566-2902

E-mail address msds@valspar.com

Emergency telephone number

United States of America 800-424-9300

## **Section 2: HAZARDS IDENTIFICATION**

Classification

Serious eye damage/eye irritation Category 2

Label elements



Signal word WARNING

## **HAZARD STATEMENTS**

Causes serious eye irritation

### **PREVENTION**

Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection.

#### **RESPONSE**

Get medical advice/attention if you feel unwell.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin

Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### **STORAGE**

Keep container tightly closed.

#### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

## HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

#### **OTHER HAZARDS**

Not applicable.

#### **UNKNOWN ACUTE TOXICITY**

.0002% of the mixture consists of ingredient(s) of unknown toxicity.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
2-Butoxyethanol	111-76-2	5 - 10
Isopropyl alcohol	67-63-0	3 - 5
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	126-86-3	0.1 - 0.3

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## **Section 4: FIRST AID MEASURES**

## **First Aid Measures**

#### General advice

Get medical advice/attention if you feel unwell.

#### **Eve contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

## Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

#### Section 5: FIRE FIGHTING MEASURES

## Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

#### Not to be used for safety reasons:

Strong water jet

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

#### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

#### Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

#### For emergency responders

Use personal protection recommended in Section 8.

#### Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### Methods and material for containment and cleaning up

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

## **Section 7: HANDLING AND STORAGE**

#### Precautions for safe handling

## Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray.

#### **General Hygiene Considerations**

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

## Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Incompatible materials

Bases. Strong oxidizing agents. Acids.

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m <sup>3</sup>	TWA: 5 ppm
		S*	TWA: 24 mg/m <sup>3</sup>
Isopropyl alcohol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm
			TWA: 980 mg/m <sup>3</sup>
			STEL: 500 ppm
			STEL: 1225 mg/m <sup>3</sup>

#### Appropriate engineering controls

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin and body protection

Wear suitable protective clothing.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### **Thermal Protection**

No information available

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state liquid

Appearance No information available

Odor Water
Color Silver

Odor Threshold
pH value
No information available
No information available
No information available
No information available

Boiling point / boiling range No information available °C / °F

flash point 500 °C / 932 °F
evaporation rate No information available
Flammability (solid, gas)
Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 8.59 specific gravity 1.03

Solubility(ies)

Partition coefficient

Autoignition temperature

Decomposition temperature

Kinematic viscosity

Dynamic viscosity

No information available

**Other information** 

## **Section 10: STABILITY AND REACTIVITY**

**Reactivity** No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

**Hazardous polymerization**None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

**Incompatible materials**Bases. Strong oxidizing agents. Acids.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

## **Section 11: TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact Not applicable Ingestion Not applicable Inhalation Not applicable

### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Isopropyl alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg ( Rabbit )	= 72600 mg/m³ (Rat) 4 h
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl- 126-86-3	> 500 mg/kg(Rat)	> 1000 mg/kg(Rabbit)	> 20 mg/L (Rat)1 h

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5650 Mg/kg
ATEmix (dermal) 11474 Mg/kg
ATEmix (inhalation-dust/mist) 17.2 mg/l
ATEmix (inhalation-vapor) 124 mg/l

**UNKNOWN ACUTE TOXICITY** .0002% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3			
111-76-2				

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen.

Skin corrosion/irritation Not applicable

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitization Not applicable

Respiratory sensitization Not applicable

Germ cell mutagenicity Not applicable

Carcinogenicity Not applicable

Reproductive Toxicity Not applicable

Specific target organ toxicity (single exposure) Not applicable

Specific target organ toxicity (repeated exposure) Not applicable

Aspiration hazard Not applicable

## **Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

**Bioaccumulation** 

No information available

Mobility

No information available

Other adverse effects No information available

## Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

## **Section 14: TRANSPORT INFORMATION**

DOT IMDG IATA

**14.1 UN/ID no** Not regulated Not regulated Not regulated

14.2 Proper shipping name

14.3 Hazard Class

14.4 Packing Group

14.5 Environmental hazard

14.6 Special Provisions

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

#### **Section 15: REGULATORY INFORMATION**

#### **International Inventories**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing. (Active List). All components are listed or exempt from listing

## **US Federal Regulations**

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
2-Butoxyethanol 111-76-2 5 - 10	1		
Aluminum 7429-90-5 5 - 10	1	Aluminum	

## **US State Regulations**

#### Rule 66 status of product

Not photochemically reactive.

#### U.S. EPA Label information

EPA Pesticide registration number Not applicable

#### U.S. State Right-to-Know Regulations

Chemical Name
Water
7732-18-5
Proprietary Non-Hazardous Ingredient - Proprietary CAS
2-Butoxyethanol
111-76-2
Aluminum
7429-90-5
Isopropyl alcohol
67-63-0

## **Section 16: OTHER INFORMATION**

HMIS

Health hazards 2
Flammability 1
Physical hazards 1
Personal Protection X

Prepared By Product Stewardship

Revision date 08-Jul-2020

Revision Note No information available

**Disclaimer** 

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS

should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**