Product Name: Easy Sand 30 ounce

Product identifier: 100421 Revision Date: 09-09-2015

Replaces:



1. Identification

Product Name: Easy Sand 30 ounce

Product identifier: 100421

Relevant identified uses of the substance or mixture and uses

advised against:

Polyester Finishing and Blending Putty Premium Light weight body filler

Chemical Manufacturer / ITW Evercoat

Importer / Distributor: a division of Illinois Tool Works Inc.

6600 Cornell Road Cincinnati, OH 45242

513-489-7600

Emergency telephone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols:





GHS Classification: Respiratory Sensitisation Category 1

Skin Sensitisation Category 1

Reproductive Toxicity Category 1B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Germ Cell Mutagenicity Category 2

Carcinogenicity Category 2 Flammable Liquid Category 3

Hazardous to the aquatic environment - Acute Category 3

Acute Toxicity - Inhalation Dust / Mist Category 4

GHS Signal Word: Danger

GHS Hazard Statements: Flammable liquid and vapour.

Causes skin irritation.

Product Name: Easy Sand 30 ounce

Product identifier: 100421 **Revision Date:** 09-09-2015

Replaces:

May cause an allergic skin reaction.

Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of causing genetic defects.

Suspected of causing cancer.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life.

GHS Precautionary Statements: Safety Precautions:

First Aid Measures:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Product Name: Easy Sand 30 ounce

Product identifier: 100421 **Revision Date:** 09-09-2015

Replaces:

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Take off contaminated clothing and wash before reuse.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction.

Keep container tightly closed. Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise

Reports have associated repeated and prolonged occupational overexposure to classified:

solvents with permanent brain and nervous system damage.

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient	
Styrene	100-42-5	10 - 30	
Titanium dioxide	13463-67-7	1 - 5	
Acid anhydride	85-43-8	1 - 5	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting

> eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. Flush eyes gently with water for at least 15 minutes, lifting upper & lower

eye lids. Seek immediate medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation

> develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing

before reuse.

Inhalation: Remove to fresh air. If breathing is difficult, have a trained

individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and guiet. If the victim has stopped breathing open airway, loosen collar and belt,

Product Name: Easy Sand 30 ounce

Product identifier: 100421 **Revision Date:** 09-09-2015

Replaces:

and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably

on a doctor's advice.

Ingestion: Do not induce vomiting and seek medical attention immediately.

Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended. If vomiting occurs spontaneously, keep head below hips to prevent aspiration

of liquid into lungs.

Immediate medical attention and special treatment needed,: No additional first aid information available

5. Fire-fighting measures

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical

> extinguishing agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical

No data available Unsuitable extinguishing media:

Fire and/or Explosion Hazards: Vapors may be ignited by sparks, flames or other sources of ignition

if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition

Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons,

and flash back.

Hazardous Combustion

Products:

Phthalic anhydride Special protective equipment

and precautions for firefighters:

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme

heat.

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal

protective equipment.

Product Name: Easy Sand 30 ounce

Product identifier: 100421 Revision Date: 09-09-2015

Replaces:

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Methods and material for containment and cleaning up: No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

No special spill clean-up considerations. Collect and discard in regular trash. Shut off ignition sources; including electrical

equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid

breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. All hazard

precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the

reach of children.

Conditions for safe storage: Store in a cool dry ventilated location. Isolate from incompatible

materials and conditions. Keep container(s) closed. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with

incompatible materials.

Materials to Avoid/Chemical

Incompatibility::

Peroxides Strong acids Strong oxidizing agents Polymerization

catalysts

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Styrene	100 ppm	20 ppm	40 ppm STEL; 170 mg/m3 STEL
Titanium dioxide	15 mg/m3	10 mg/m3	

Appropriate engineering controls.:

No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne

Product Name: Easy Sand 30 ounce

Product identifier: 100421 **Revision Date:** 09-09-2015

Replaces:

exposures below exposure limits. Explosion proof exhaust

ventilation should be used.

Eye Protection: Wear chemically resistant safety glasses with side shields when

handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of

product.

Skin Protection: Not normally considered a skin hazard. Where use can result in skin

contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots A barrier cream may

be used for additional skin protection.

Respiratory Protection: Respiratory protection may be required to avoid overexposure

when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use a NIOSH approved respirator designed to remove particulate

i NiOsh approved respirator designed to remove particul

matter and organic solvent vapors.

Other Protective Equipment: Splash proof chemical goggles are recommended to protect against

the splash of product. Protective gloves and proper clothing should

be worn to prevent skin contact. Gloves should be made of

neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots A barrier cream may

be used for additional skin protection.

General Hygiene Conditions: All hazard precautions given in the data sheet must be observed.

Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of

the reach of children.

9. Physical and chemical properties

Appearance (physical state): Paste
Color: White
Odor: Aromatic

Odor threshold: No data available

pH: Neutral

Melting Point/Freezing Point (°C):

No data available

Initial Boiling Point and Boiling Range (°C): 145 Flash Point (°C): 35

Product Name: Easy Sand 30 ounce

Product identifier: 100421 Revision Date: 09-09-2015

Replaces:

Evaporation Rate:No data available **Flammability (solid, gas):**No data available

Upper Flammable/Explosive Limit: 6.1 Lower Flammable/Explosive Limit: 1.1

Vapor Pressure: 5 MMHG@20C/68F

Vapor Density: Heavier than air. Vapors that evolve from this product

will tend to settle and accumulate near the floor.

Relative Density: 1.06

1.02

Solubility(ies): Insoluble Partition coefficient: n-octanol/water: 1.36
Auto-ignition Temperature (°C): 490 °C

Decomposition Temperature::No data available **Viscosity:**27,200 - 32,000

VOC (as packaged-less exempts and water) 1.94

1.56 or 187

VOC (as applied*- 2% by wt hardener- less

exempts and water)

0.26 lbs/gal

0.4 or 31 g/L

48

Percent Solids by weight – as packaged

77.20 82.40

Percent Solids by weight – as applied* - 2%

96.80

by wt hardener

95.50 22.8

VHAP Content by weight – as packaged

20

VHAP Content by weight – as applied* - 2%

3.2

by weight hardener

4.5

10. Stability and reactivity

Reactivity: No data available

Chemical stability: Stable under normal conditions. **Conditions to avoid:** None known. Contamination.

Incompatible materials: Peroxides Strong acids Strong oxidizing agents Polymerization

catalysts

Hazardous decomposition

Carbon dioxide Carbon monoxide Styrene oxide Hydrocarbons

products:

Phthalic anhydride

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):

Ingestion, Skin contact, Eye contact, Absorption

Product Name: Easy Sand 30 ounce

Product identifier: 100421 Revision Date: 09-09-2015

Replaces:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatique, nausea and

headache. Excessive inhalation of vapors may cause nasal and respiratory irritation,

acute nervous system depression, fatigue, weakness, nausea, headache and

dizziness.

Airborne overexposure well above the PEL may result additionally in eye irritation,

headache, chemical bronchitis, asthma-like findings or pulmonary edema.

Inhalation Toxicity: Harmful! Can cause systemic damage (see "Target Organs) **Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption: No absorption hazard in normal industrial use. Causes skin irritation. Contact may

cause irritation and possible dermatitis or sensitization. Symptoms may include

redness, burning, drying and cracking of skin, and skin burns

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue. Contact with liquid or vapor may result in irritation, redness,

tearing, and blurred vision.

Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into

the lungs can cause chemical pneumonitis which can be fatal.

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: Suspected of causing cancer. The International Agency for Research on Cancer

(IARC) has classified styrene as a group 2B carcinogen (possibly carcinogenic to

humans).

Reproductive and

Developmental Toxicity:

May damage fertility or the unborn child.

Mutagenicity: Suspected of causing genetic defects.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory

irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)

Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Skin Absorption: Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50	
No data available				

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen	
Styrene	N	Υ	Υ	
Titanium dioxide	N	Υ	N	

Product Name: Easy Sand 30 ounce

Product identifier: 100421 **Revision Date:** 09-09-2015

Replaces:

12. Ecological information

Ecotoxicity (aquatic andToxic to aquatic life. Styrene is toxic to aquatic organisms and should

terrestrial, where available): not be released

to sewage, draining systems or any body of water exceeding

concentrations of approved limits under applicable regulations and

permits

Persistence and degradability:

Mobility in soil:

No data available No data available No data available

Other adverse effects (such as

hazardous to the ozone layer):

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues: Spent or discarded material is a hazardous waste.

Safe Handling of Waste: This material as supplied, if discarded, would be not be regulated

as a hazardous waste under RCRA (40 CFR 261).

This material as supplied, if discarded, would be regulated as a

hazardous waste under RCRA (40 CFR 261).

Waste treatment methods

(including packaging):

Dispose of by incineration following Federal, State, Local, or

Provincial regulations.

Waste Disposal Code(s): D001

14. Transport information

UN proper shipping name: The DOT Classification for shipping is dependent on quantity,

type of packaging (a kit may include other components), or

method of shipment.

15. Regulatory information

TSCA Status: The intentional ingredients of this product are listed. A

component or components of this product are listed on the

TSCA Inventory of Existing Chemical Substances.

Product Name: Easy Sand 30 ounce

Product identifier: 100421 Revision Date: 09-09-2015

Replaces:

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Styrene	100-42-5	N	N	Υ	N
Titanium dioxide	13463-67-7	N	N	Υ	Υ

16. Other information, including date of preparation or last revision.

Revision Date: 09-09-2015

Revision Number: 10

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances