



GENERAL INFORMATION

KC20 POST SANDING CLEANER removes sanding residue as well as dirt, hand oils, and other light contaminants. KC20 will also reduce static when used on plastic and fiberglass parts. KC20 is designed for use in initial and final surface preparation. However before sanding existing finish KC10 should be used first (National Rule Only). **Refer to instructions for KC10 Wax and Grease Remover.**



USING KC20

KC20 is to be used over sanded surfaces, OEM finishes, sanded primers, cured sealers, fresh base coats, Pin Stripes, Air Brush Art, and other sensitive surfaces.



APPLICATION

- Ready-For-Use
- Wash surface with mild detergent and water
- Rinse and dry surface
- Soak clean cloth with KC20
- Wipe surface with KC20 and wipe dry with clean, dry cloth before product dries.

KC20 should not be allowed to dry on surface. If this occurs, re-apply KC20 using a clean cloth and wipe dry.

NOTE: KC20 is the only cleaner recommended for cleaning Shirin2® base coats prior to top coating.

TECHNICAL DATA

FOR USA (National Rule & Low VOC) / Canada

RTS Regulatory Data	KC20	
	Ready-For-Use	
	LBS/GAL	g/L
Actual VOC	0.2 Max.	25 Max.
Density	7 - 9	840 - 1080
	Weight %	Volume %
Total Solid Content	0	0
Total Volatile Content	100	100
Water	95 - 99	95 - 99
Exempt Compound Content	0	0
Category	Surface Cleaner	

Note: US/Canadian regulations allow for the use of exempt compounds for VOC Calculations.

FOR REST-OF-WORLD

RTS Regulatory Data	KC20	
	Ready-For-Use	
	LBS/GAL	g/L
VOC	8.0 Max.	960 Max.
Density	6 - 8	720 - 960
	Weight %	Volume %
Total Solid Content	0	0
Total Volatile Content	100	100
Water	0	0
Category	Surface Cleaner	

Note: ROW considered areas outside US/Canada.



HEALTH AND SAFETY

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

IMPORTANT The contents of this package have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

If used as instructed, this product is designed to comply with VOC standards in low-VOC jurisdictions. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

valspar

WWW.HOUSEOFKOLOR.COM