

# SAFETY DATA SHEET

KK25

## Section 1. Identification

**Product name** : KANDY KONCENTRATES  
BLACK

**Product code** : KK25

**Other means of identification** : Not available.

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

Paint or paint related material.

**Manufacturer** : Valspar Automotive  
101 W. Prospect Ave.,  
Cleveland, OH 44115  
USA

**Emergency telephone number of the company** : US / Canada: (216) 566-2917  
Mexico: 55-4160-8800 / 55-4160-8819 Monday to Friday from 8:30 a.m. to 5:30 p.m.

**Product Information Telephone Number** : US / Canada: 1-800-844-3691 Option 3  
Mexico: 55-5333-1500

**Transportation Emergency Telephone Number** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 3.8% (oral), 33.2% (dermal), 39% (inhalation)

### GHS label elements

**Hazard pictograms**



**Signal word** : Danger

## Section 2. Hazards identification

**Hazard statements** : Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.

### Precautionary statements

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash thoroughly after handling.

**Response** : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR PROFESSIONAL USE ONLY.

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

**Other means of identification** : Not available.

### CAS number/other identifiers

Ingredient name	% by weight	Identifiers
p-Chlorobenzotrifluoride	≥25 - ≤50	98-56-6
Acetone	≥10 - ≤25	67-64-1
n-Butyl Acetate	≥10 - ≤25	123-86-4
Methyl n-Propyl Ketone	≤10	107-87-9
2-methoxy-1-methylethyl acetate	≤10	108-65-6
Carbon Black	≤3	1333-86-4
2-Butoxyethanol	≤3	111-76-2
Xylene, mixed isomers	≤0.3	1330-20-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

**Date of issue/Date of revision** : 5/3/2025

**Date of previous issue** : 1/26/2025

**Version** : 3

2/21

KK25 KANDY KONCENTRATES  
BLACK

SHW-85-NA-GHS-US

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

## Section 4. First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
halogenated compounds  
carbonyl halides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Remark** : Flammable liquid.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Date of issue/Date of revision** : 5/3/2025

**Date of previous issue** : 1/26/2025

**Version** : 3

4/21

KK25  
KANDY KONCENTRATES  
BLACK

SHW-85-NA-GHS-US

## Section 6. Accidental release measures

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
p-Chlorobenzotrifluoride Acetone	98-56-6 67-64-1	None. <b>ACGIH TLV (United States, 1/2024) A4.</b> TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm. <b>NIOSH REL (United States, 10/2020)</b> TWA 10 hours: 250 ppm. TWA 10 hours: 590 mg/m <sup>3</sup> . <b>OSHA PEL (United States, 5/2018)</b> TWA 8 hours: 1000 ppm.

## Section 8. Exposure controls/personal protection

n-Butyl Acetate	123-86-4	<p>TWA 8 hours: 2400 mg/m<sup>3</sup>.  <b>ACGIH TLV (United States, 1/2024) [Butyl acetates]</b>            STEL 15 minutes: 150 ppm.            TWA 8 hours: 50 ppm.  <b>NIOSH REL (United States, 10/2020)</b>            TWA 10 hours: 150 ppm.            TWA 10 hours: 710 mg/m<sup>3</sup>.            STEL 15 minutes: 200 ppm.            STEL 15 minutes: 950 mg/m<sup>3</sup>.  <b>OSHA PEL (United States, 5/2018)</b>            TWA 8 hours: 150 ppm.            TWA 8 hours: 710 mg/m<sup>3</sup>.</p>
Methyl n-Propyl Ketone	107-87-9	<p><b>ACGIH TLV (United States, 1/2024)</b>            STEL 15 minutes: 150 ppm.  <b>NIOSH REL (United States, 10/2020)</b>            TWA 10 hours: 150 ppm.            TWA 10 hours: 530 mg/m<sup>3</sup>.  <b>OSHA PEL (United States, 5/2018)</b>            TWA 8 hours: 200 ppm.            TWA 8 hours: 700 mg/m<sup>3</sup>.</p>
2-methoxy-1-methylethyl acetate	108-65-6	<p><b>OARS WEEL (United States, 6/2024)</b>            TWA 8 hours: 50 ppm.</p>
Carbon Black	1333-86-4	<p><b>ACGIH TLV (United States, 1/2024) A3.</b>            TWA 8 hours: 3 mg/m<sup>3</sup>. Form: Inhalable fraction.  <b>NIOSH REL (United States, 10/2020) NIA.</b>            TWA 10 hours: 3.5 mg/m<sup>3</sup>.            TWA 10 hours: 0.1 mg/m<sup>3</sup> (as cyclohexane-extractable fraction).  <b>OSHA PEL (United States, 5/2018)</b>            TWA 8 hours: 3.5 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	111-76-2	<p><b>ACGIH TLV (United States, 1/2024) A3.</b>            TWA 8 hours: 20 ppm.  <b>NIOSH REL (United States, 10/2020)</b>            Absorbed through skin.            TWA 10 hours: 5 ppm.            TWA 10 hours: 24 mg/m<sup>3</sup>.  <b>OSHA PEL (United States, 5/2018)</b>            Absorbed through skin.            TWA 8 hours: 50 ppm.            TWA 8 hours: 240 mg/m<sup>3</sup>.</p>
Xylene, mixed isomers	1330-20-7	<p><b>ACGIH TLV (United States, 1/2024) [p-xylene and mixtures containing p-xylene] A4.</b> Ototoxicant.            TWA 8 hours: 20 ppm.  <b>OSHA PEL (United States, 5/2018) [Xylenes]</b>            TWA 8 hours: 100 ppm.            TWA 8 hours: 435 mg/m<sup>3</sup>.</p>

[Occupational exposure limits \(Canada\)](#)

## Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits
acetone	67-64-1	<b>CA Saskatchewan Provincial (Canada, 4/2021)</b> STEL 15 minutes: 750 ppm. TWA 8 hours: 500 ppm. <b>CA British Columbia Provincial (Canada, 4/2024)</b> TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm. <b>CA Ontario Provincial (Canada, 6/2019)</b> TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm. <b>CA Quebec Provincial (Canada, 2/2024)</b> TWAEV 8 hours: 250 ppm. STEV 15 minutes: 500 ppm. <b>CA Alberta Provincial (Canada, 3/2023)</b> OEL 8 hours: 1200 mg/m <sup>3</sup> . OEL 15 minutes: 1800 mg/m <sup>3</sup> . OEL 8 hours: 500 ppm. OEL 15 minutes: 750 ppm.
n-butyl acetate	123-86-4	<b>CA Saskatchewan Provincial (Canada, 4/2021)</b> STEL 15 minutes: 200 ppm. TWA 8 hours: 150 ppm. <b>CA British Columbia Provincial (Canada, 4/2024) [butyl acetate, all isomers]</b> STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm. <b>CA Ontario Provincial (Canada, 6/2019) [butyl acetates, all isomers]</b> STEL 15 minutes: 150 ppm. TWA 8 hours: 50 ppm. <b>CA Quebec Provincial (Canada, 2/2024) [butyl acetates]</b> STEV 15 minutes: 150 ppm. TWAEV 8 hours: 50 ppm. <b>CA Alberta Provincial (Canada, 3/2023)</b> OEL 15 minutes: 200 ppm. OEL 15 minutes: 950 mg/m <sup>3</sup> . OEL 8 hours: 150 ppm. OEL 8 hours: 713 mg/m <sup>3</sup> .
Methyl propyl ketone	107-87-9	<b>CA Saskatchewan Provincial (Canada, 4/2021)</b> STEL 15 minutes: 250 ppm. TWA 8 hours: 200 ppm. <b>CA British Columbia Provincial (Canada, 4/2024)</b> TWA 8 hours: 150 ppm. STEL 15 minutes: 250 ppm. <b>CA Ontario Provincial (Canada, 6/2019)</b> STEL 15 minutes: 150 ppm. <b>CA Quebec Provincial (Canada, 2/2024)</b> STEV 15 minutes: 150 ppm. <b>CA Alberta Provincial (Canada, 3/2023)</b> OEL 8 hours: 200 ppm. OEL 15 minutes: 250 ppm.



## Section 8. Exposure controls/personal protection

Carbon black	1333-86-4	<p>OEL 8 hours: 705 mg/m<sup>3</sup>. OEL 15 minutes: 881 mg/m<sup>3</sup>. <b>CA Saskatchewan Provincial (Canada, 4/2021)</b> STEL 15 minutes: 7 mg/m<sup>3</sup>. TWA 8 hours: 3.5 mg/m<sup>3</sup>. <b>CA British Columbia Provincial (Canada, 4/2024) Carc 2B.</b> TWA 8 hours: 3 mg/m<sup>3</sup>. Form: Inhalable. <b>CA Ontario Provincial (Canada, 6/2019)</b> TWA 8 hours: 3 mg/m<sup>3</sup>. Form: Inhalable particulate matter.. <b>CA Quebec Provincial (Canada, 2/2024) C3.</b> TWA EV 8 hours: 3 mg/m<sup>3</sup>. Form: inhalable aerosol fraction. <b>CA Alberta Provincial (Canada, 3/2023)</b> OEL 8 hours: 3.5 mg/m<sup>3</sup>.</p>
2-Butoxyethanol	111-76-2	<p><b>CA Saskatchewan Provincial (Canada, 4/2021)</b> STEL 15 minutes: 30 ppm. TWA 8 hours: 20 ppm. <b>CA British Columbia Provincial (Canada, 4/2024)</b> TWA 8 hours: 20 ppm. <b>CA Ontario Provincial (Canada, 6/2019)</b> TWA 8 hours: 20 ppm. <b>CA Quebec Provincial (Canada, 2/2024) C3.</b> TWA EV 8 hours: 20 ppm. <b>CA Alberta Provincial (Canada, 3/2023)</b> OEL 8 hours: 97 mg/m<sup>3</sup>. OEL 8 hours: 20 ppm.</p>
Xylene	1330-20-7	<p><b>CA Saskatchewan Provincial (Canada, 4/2021) [Xylene]</b> STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. <b>CA British Columbia Provincial (Canada, 4/2024) [xylene (o, m &amp; p isomers)]</b> TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm. <b>CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)]</b> STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm. <b>CA Quebec Provincial (Canada, 2/2024) [Xylene]</b> TWA EV 8 hours: 100 ppm. TWA EV 8 hours: 434 mg/m<sup>3</sup>. STEV 15 minutes: 150 ppm. STEV 15 minutes: 651 mg/m<sup>3</sup>. <b>CA Alberta Provincial (Canada, 3/2023) [Dimethylbenzene]</b> OEL 8 hours: 100 ppm. OEL 15 minutes: 651 mg/m<sup>3</sup>. OEL 15 minutes: 150 ppm. OEL 8 hours: 434 mg/m<sup>3</sup>.</p>



## Section 8. Exposure controls/personal protection

### Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
Acetone	67-64-1	<b>NOM-010-STPS-2014 (Mexico, 4/2016) A4.</b> TWA 8 hours: 500 ppm. STEL 15 minutes: 750 ppm.
n-Butyl Acetate	123-86-4	<b>NOM-010-STPS-2014 (Mexico, 4/2016)</b> TWA 8 hours: 150 ppm. STEL 15 minutes: 200 ppm.
Methyl n-Propyl Ketone	107-87-9	<b>NOM-010-STPS-2014 (Mexico, 4/2016)</b> STEL 15 minutes: 150 ppm.
2-Butoxyethanol	111-76-2	<b>NOM-010-STPS-2014 (Mexico, 4/2016) A3.</b> TWA 8 hours: 20 ppm.

### Biological exposure indices (United States)

Ingredient name	Exposure indices
Acetone	<b>ACGIH BEI (United States, 1/2024)</b> BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.
2-Butoxyethanol	<b>ACGIH BEI (United States, 1/2024)</b> BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: end of shift.
Xylene, mixed isomers	<b>ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)]</b> BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.

### Biological exposure indices (Canada)

No exposure indices known.

### Biological exposure indices (Mexico)

Ingredient name	Exposure indices
Acetone	<b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b> BEI: 50 mg/L [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the work shift.
2-Butoxyethanol	<b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b> BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: exposure sample at the end of the work shift.

## Section 8. Exposure controls/personal protection

<b>Appropriate engineering controls</b>	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
<b>Environmental exposure controls</b>	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<b><u>Individual protection measures</u></b>	
<b>Hygiene measures</b>	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
<b>Eye/face protection</b>	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
<b><u>Skin protection</u></b>	
<b>Hand protection</b>	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
<b>Body protection</b>	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
<b>Other skin protection</b>	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

<b>Physical state</b>	: Liquid.
<b>Color</b>	: Black.
<b>Odor</b>	: Not available.
<b>Odor threshold</b>	: Not available.
<b>pH</b>	: Not applicable.
<b>Melting point/freezing point</b>	: Not available.
<b>Boiling point or initial boiling point and boiling range</b>	: 55°C (131°F)

<b>Date of issue/Date of revision</b>	: 5/3/2025	<b>Date of previous issue</b>	: 1/26/2025	<b>Version</b>	: 3	10/21
KK25	KANDY KONCENTRATES BLACK			SHW-85-NA-GHS-US		

## Section 9. Physical and chemical properties

Flash point	: Closed cup: -4°C (24.8°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 89 (butyl acetate = 1)
Flammability	: Flammable liquid.
Lower and upper explosion limit/flammability limit	: Lower: 0.9% Upper: 13.1%
Vapor pressure	: 24 kPa (180 mm Hg)
Relative vapor density	: 2 [Air = 1]
Relative density	: 1.04
Density	: 1.03 g/cm <sup>3</sup>
Solubility(ies)	:

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): <20.5 mm <sup>2</sup> /s (<20.5 cSt)
Molecular weight	: Not applicable.
<u>Particle characteristics</u>	
Median particle size	: Not applicable.
Heat of combustion	: 25.055 kJ/g

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

##### Product/ingredient name

##### Result

p-Chlorobenzotrifluoride

**Rat - Oral - LD50**

13 g/kg

Acetone

**Rat - Oral - LD50**

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor

n-Butyl Acetate

**Rat - Oral - LD50**

10768 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes

**Rabbit - Dermal - LD50**

>17600 mg/kg

Methyl n-Propyl Ketone

**Rat - Oral - LD50**

1600 mg/kg

**Rabbit - Dermal - LD50**

6500 mg/kg

2-methoxy-1-methylethyl acetate

**Rat - Oral - LD50**

8532 mg/kg

**Rabbit - Dermal - LD50**

>5 g/kg

Carbon Black

**Rat - Oral - LD50**

>15400 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity)

2-Butoxyethanol

**Guinea pig - Dermal - LD50**

>2000 mg/kg

**Rat - Oral - LD50**

1300 mg/kg

**Guinea pig - Inhalation - LCLo Vapor**

>3.1 mg/l [1 hours]

Xylene, mixed isomers

**Rat - Oral - LD50**

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

**Rat - Inhalation - LC50 Gas.**

6700 ppm [4 hours]

Toxic effects: Behavioral - Somnolence (general depressed activity)

**Conclusion/Summary [Product]** : Not available.

#### Skin corrosion/irritation

##### Product/ingredient name

##### Result

Acetone

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Rabbit - Skin - Mild irritant**

Amount/concentration applied: 395 mg

n-Butyl Acetate

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

## Section 11. Toxicological information

Methyl n-Propyl Ketone

Amount/concentration applied: 500 mg

**Rabbit - Skin - Mild irritant**

2-Butoxyethanol

Amount/concentration applied: 405 mg

**Rabbit - Skin - Mild irritant**

Xylene, mixed isomers

Amount/concentration applied: 500 mg

**Rat - Skin - Mild irritant**

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Rabbit - Skin - Moderate irritant**

Amount/concentration applied: 100 %

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### Product/ingredient name

#### Result

Acetone

**Human - Eyes - Mild irritant**

Amount/concentration applied: 186300 ppm

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 10 uL

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 20 mg

**Rabbit - Eyes - Moderate irritant**

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 100 mg

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 87 mg

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

n-Butyl Acetate

2-Butoxyethanol

Xylene, mixed isomers

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### Skin

**Conclusion/Summary [Product]** : Not available.

Date of issue/Date of revision : 5/3/2025

Date of previous issue : 1/26/2025

Version : 3

13/21

KK25 KANDY KONCENTRATES  
BLACK

SHW-85-NA-GHS-US

## Section 11. Toxicological information

### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
p-Chlorobenzotrifluoride	-	2B	-
Carbon Black	-	2B	-
2-Butoxyethanol	-	3	-
Xylene, mixed isomers	-	3	-

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### Product/ingredient name

#### Result

p-Chlorobenzotrifluoride

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Acetone

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

n-Butyl Acetate

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

2-methoxy-1-methylethyl acetate

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

2-Butoxyethanol

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Xylene, mixed isomers

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

### Specific target organ toxicity (repeated exposure)

#### Product/ingredient name

#### Result

Xylene, mixed isomers

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

### Aspiration hazard

## Section 11. Toxicological information

### Product/ingredient name

Xylene, mixed isomers

### Result

ASPIRATION HAZARD - Category 1

### Information on the likely routes of exposure

Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.



## Section 11. Toxicological information

**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
KANDY KONCENTRATES	19211.7	N/A	N/A	168.1	N/A
p-Chlorobenzotrifluoride	13000	N/A	N/A	N/A	N/A
Acetone	5800	N/A	N/A	N/A	N/A
n-Butyl Acetate	10768	N/A	N/A	N/A	N/A
Methyl n-Propyl Ketone	1600	6500	N/A	N/A	N/A
2-methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
2-Butoxyethanol	1200	N/A	N/A	3	N/A
Xylene, mixed isomers	4300	2500	N/A	N/A	N/A

## Section 12. Ecological information

### Toxicity

#### Product/ingredient name

Acetone

#### Result

##### Acute - EC50 - Fresh water

Algae - Green algae - *Selenastrum* sp.  
7200 mg/l [96 hours]

Effect: Population

##### Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*  
4.95 mg/l [96 hours]

Effect: Reproduction

##### Chronic - NOEC - Fresh water

Crustaceans - Daphnia - *Daphniidae*  
0.016 ml/l [21 days]

Effect: Population

##### Chronic - NOEC - Marine water

Fish - Threespine stickleback - *Gasterosteus aculeatus* - Larvae  
Age: 7 days

5 µg/l [42 days]

Effect: Population

##### Acute - LC50 - Marine water

ISO

Crustaceans - Calanoid copepod - *Acartia tonsa* - Copepodid  
4.42589 ml/l [48 hours]

Effect: Mortality

##### Acute - LC50 - Fresh water

Fish - Guppy - *Poecilia reticulata*

Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g  
5600 ppm [96 hours]

Effect: Mortality

n-Butyl Acetate

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 31 to 32 days; Size: 21.6 mm; Weight: 0.175 g  
18 mg/l [96 hours]

Effect: Mortality

##### Acute - LC50 - Marine water

Date of issue/Date of revision : 5/3/2025

Date of previous issue : 1/26/2025

Version : 3

16/21

KK25 KANDY KONCENTRATES  
BLACK

SHW-85-NA-GHS-US

## Section 12. Ecological information

Methyl n-Propyl Ketone

Crustaceans - Brine shrimp - *Artemia salina*

32 mg/l [48 hours]

Effect: Mortality

**Acute - LC50 - Fresh water**

Fish - Fathead minnow - *Pimephales promelas*

Age: 32 days; Size: 18.4 mm; Weight: 0.095 g

1240 mg/l [96 hours]

Effect: Mortality

2-Butoxyethanol

**Acute - LC50 - Marine water**

Crustaceans - Common shrimp, sand shrimp - *Crangon crangon*

800 mg/l [48 hours]

Effect: Mortality

**Acute - LC50 - Marine water**

Fish - Inland silverside - *Menidia beryllina*

1250 ppm [96 hours]

Effect: Mortality

Xylene, mixed isomers

**Acute - LC50 - Marine water**

Crustaceans - Daggerblade grass shrimp - *Palaemon pugio*

8500 µg/l [48 hours]

Effect: Mortality

**Acute - LC50 - Fresh water**

Fish - Fathead minnow - *Pimephales promelas*

Age: 31 days; Size: 18.4 mm; Weight: 0.077 g

13.4 mg/l [96 hours]

Effect: Mortality

**Conclusion/Summary [Product]** : Not available.

### Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetone	-	-	Readily
n-Butyl Acetate	-	-	Readily
2-Butoxyethanol	-	-	Readily
Xylene, mixed isomers	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Xylene, mixed isomers	-	8.1 to 25.9	Low

### Mobility in soil

**Soil/Water partition coefficient** : Not available.

### Other adverse effects







No known significant effects or critical hazards.

## Section 13. Disposal considerations

### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT. Marine pollutant (p-Chlorobenzotrifluoride)
Transport hazard class(es)	3 	3 	3 	3 	3  
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	Yes. The environmentally hazardous substance mark is not required.	Yes.
Additional information	-  <u>ERG No.</u> 128	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).  <u>ERG No.</u> 128	-  <u>ERG No.</u> 128	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency schedules</u> F-E, S-E

## Section 14. Transport information

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to IMO instruments** : Not available.

**Proper shipping name** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** :

### SARA 313

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production. Reporting of chemicals in this section does not necessarily indicate their presence in the final formulated product.

<b>Ingredient name</b>	<b>% by weight</b>	<b>CAS number</b>
Mercury (as Hg)	0.0000002	111-76-2
2-Butoxyethanol	1	
Glycol Ethers (SARA)	1	
Lead (as Pb)	0.000005	

### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### **International lists**

: **Australia inventory (AIIIC)**: Not determined.  
**China inventory (IECSC)**: Not determined.  
**Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**Korea inventory (KECI)**: Not determined.  
**New Zealand Inventory of Chemicals (NZIoC)**: Not determined.  
**Philippines inventory (PICCS)**: Not determined.  
**Taiwan Chemical Substances Inventory (TCSI)**: Not determined.  
**Thailand inventory**: Not determined.  
**Turkey inventory**: Not determined.  
**Vietnam inventory**: Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method

### History

**Date of printing** : 5/3/2025

**Date of issue/Date of revision** : 5/3/2025

**Date of previous issue** : 1/26/2025

**Version** : 3

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is

<b>Date of issue/Date of revision</b> : 5/3/2025	<b>Date of previous issue</b> : 1/26/2025	<b>Version</b> : 3	20/21
KK25 KANDY KONCENTRATES BLACK		SHW-85-NA-GHS-US	

Section 16. Other information

responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.