

# **SAFETY DATA SHEET**

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** HOT ROD BLACK 2.8 VOC Urethane Topcoat

**PRODUCT CODES:** UA-70388 Satin Finish, UA-70389 Matte Finish

**MANUFACTURER:**

COVENTRY COATINGS CORP.  
 dba Kirker Automotive Finishes  
 89 Taft Ave.  
 Newburgh, NY 12550  
 USA: 1-800-307-7951 or (845) 562-5666

**EMERGENCY CONTACT FOR  
 SPILL, FIRE, EXPLOSION:  
 CHEM-TREC 1-800-424-9300**

## **SECTION 2: HAZARD IDENTIFICATION**

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<b>Classification:</b>	FLAMMABLE LIQUIDS:	Category 2
	ACUTE TOXICITY Inhalation:	Category 4
	ACUTE TOXICITY Oral:	Category 4
	ACUTE TOXICITY Dermal:	Category 4
	ASPIRATION HAZARD:	Category 1
	CARCINOGENICITY:	Category 2
	SKIN IRRITATION:	Category 2
	EYE IRRITATION:	Category 2A
	SPECIFIC TARGET ORGAN TOXICITY:	
	SINGLE EXPOSURE:	Category 3 (Respiratory, Central Nervous System)
	REPEATED EXPOSURE:	Category 2 (Liver, Kidney, Central Nervous System)

**GHS Label Elements:**      **PICTOGRAMS**



**SIGNAL WORD:**                      **Danger**

**Hazard Statements:**      Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin, causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

**Precautionary Statements:**

**Prevention:**      Read all warning statements on all labels for this and any other products to be mixed with it prior to use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing and eye protection/face protection. Wear an appropriate, properly fitted fresh-air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated in Section 8.

**Response:**      IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. Call a POISON CENTER, doctor or physician if you feel unwell.

If medical advice is needed, have product container/label and Safety Data Sheet at hand.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish, do not use water, see Section 5.

**Storage:**      Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**Disposal:**      Dispose of contents, unused amounts and empty container with an approved waste disposal facility only, in accordance with all local, regional and national regulations. Avoid release to environment. If spilled, contain material with inert absorbent, in compliance with local, regional and national regulations.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredient Name	CAS Number	% by Weight	
		UA-70388	UA-70389
		<u>Satin</u>	<u>Matte</u>
DIMETHYL CARBONATE	616-38-6	20.6	10.6
PARACHLOROBENZOTRIFLUORIDE	98-56-6	14.6	15.9
XYLENE	1330-20-7	4.4	13.0
HIGH FLASH NAPHTHA	64742-95-6	11.9	-
TERTIARY BUTYL ACETATE	540-88-5	7.0	7.7
ACETONE	67-64-1	-	8.7
GLYCOL ETHER EB ACETATE	112-07-2	2.9	1.6

**SECTION 4: FIRST AID MEASURES**

<b>Eyes:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, check for and remove contact lenses. Seek immediate medical attention.
<b>Skin:</b>	Remove contaminated clothing. Immediately flush exposed area with large amounts of water. If symptoms persist, seek medical attention. Wash clothing separately and clean shoes before reuse.
<b>Ingestion:</b>	Seek immediate medical attention, contact physician or poison control center. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
<b>Inhalation:</b>	Seek immediate medical attention. Remove from exposure to fresh air. If not breathing or if breathing is irregular, provide artificial respiration or oxygen by trained personnel; rescuers should put on appropriate protective gear. To prevent aspiration, keep head below knees.
<b>Notes to Physician:</b>	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Symptoms of poisoning may appear several hours after exposure.

**SECTION 5: FIRE FIGHTING MEASURES****Suitable Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Alcohol-resistant Foam. Do not use water, material will float and may ignite on surface of water.

**Fire Fighting Procedures:**

Fight as volatile liquid fire. Wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Eliminate all sources of ignition. Evacuate unnecessary personnel. Use water spray to cool containers with caution, avoid spreading burning liquid. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

**Unusual Fire and Explosion Hazard:**

Highly flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Vapors/dust may cause flash fire or explosion. This material may be ignited by heat, sparks, flame or static electricity. Closed containers may explode when exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Environmental Precautions:**

Avoid runoff and contact with soil, drains, sewers and waterways. Contact appropriate authority if spill is in excess of reportable quantity.

**Personal Precautions:**

Eliminate all ignition sources. No smoking, do not use flares. Contact emergency personnel. Evacuate the spill area and keep unnecessary, unprotected personnel away. Do not breathe vapors, use suitable personal protective equipment. Do not touch or walk through spilled material. Prevent additional discharge of material if able to do so safely. Ventilate spill area.

**Method of Cleaning Up:**

For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material, or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal using non-sparking tools.

Dispose of spilled material and contaminated absorbent material in compliance with local and national regulations, use a licensed waste disposal contractor, and refer to Section 13.

**SECTION 7: HANDLING AND STORAGE****Precautions for Safe Handling:**

Use only in a well ventilated area, with appropriate personal protective equipment, (see section 8). Do not eat, drink or smoke when handling this material. Wash hands and face before eating, drinking or smoking. Do not breathe vapor, fumes or mist. Do not get in eyes, or on skin, or clothing.

Always open containers slowly to allow any excess pressure to vent. Containers should be grounded when pouring. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-proof tools and explosion proof equipment.

This material is part of a multiple component system, read the Safety Data Sheet(s) for all components before mixing, as the mixture will have the hazards of all of its parts. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Conditions for Safe Storage, Including Incompatibilities:**

Store in accordance with local regulations. Store locked up. Keep container closed when not in use. Isolate from heat, flame, sparks, pilot lights, smoking materials and other sources of ignition. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated, explosion proof area. Protect from direct sunlight. KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Ingredient Name	CAS	Exposure Limits
ACETONE	67-64-1	ACGIH TWA 500 ppm OSHA PEL TWA 1,000 ppm
DIMETHYL CARBONATE	616-38-6	Data not available
GLYCOL ETHER EB ACETATE	112-07-2	ACGIH TWA 20 ppm NIOSH REL TWA 5 ppm
HIGH FLASH NAPHTHA	64742-95-6	Data not available
PARACHLOROBENZOTRIFLUORIDE	98-56-6	Data not available
TERTIARY BUTYL ACETATE	540-88-5	ACGIH TWA 200 ppm OSHA PEL TWA 200 ppm
XYLENE	1330-20-7	ACGIH TWA 100 ppm OSHA PEL TWA 100 ppm

**Engineering Controls:** Provide explosion proof exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

**Personal Protective Equipment**

**Eyes and Face:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

**Skin:** Wear impervious gloves to prevent contact with the skin. Where contact is likely, wear chemical resistant gloves, a chemical suit, long sleeves, rubber boots, and chemical safety goggles plus a face shield.

**Respiratory:** Wear an appropriate, properly fitted fresh-air supplied respirator, (NIOSH-approved TC-19C or equivalent), during and after application, until all organic vapors and spray mists are exhausted or any time airborne contaminate levels exceed exposure limits. Follow respirator manufacturer's directions and observe OSHA regulations for respirator use (29 cfr 1910.134).

**Work Hygienic Practices:**

Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State:	Liquid
Color:	Black liquid
Odor:	Typical
Odor Threshold:	Not available
pH:	Not available
Melting Point:	Not applicable
Boiling Point:	90°C
Evaporation Rate:	Not available
Flammability(Solid/Gas):	Not applicable
Vapor Pressure:	Not available
Vapor Density:	Heavier Than Air
% Solubility in Water:	Not available
Octanol/Water Partition Coefficient:	Not available
Auto-Ignition Temperature:	Not available
Decomposition Temperature:	Not available
Viscosity:	54 – 56 Krebs Units

	<u>UA-70388</u>	<u>UA-70389</u>
Flash Point (TCC)	40°F	-4°F
Flammable Limits:	.9 - 16	.9 - 16
Density:	9.07 lb/gl	8.788 lb/gl
Specific Gravity:	1.089	1.055

VOC INFORMATION: Coating Category: Low-VOC Automotive Topcoat  
 UA-70388 (Satin):  
 Actual VOC (as supplied): 156.42 g/L (1.31 lbs/gallon)  
 Regulatory VOC (as supplied): 269.91 g/L (2.25 lbs/gallon)  
 When mixed as directed, RTS VOC will not exceed 2.8 lbs/gallon.

UA-70389 (Matte)  
 Actual VOC (as supplied): 155.96 g/L (1.3 lbs/gallon)  
 Regulatory VOC (as supplied): 268.56 g/L (2.24 lbs/gallon)  
 When mixed as directed, RTS VOC will not exceed 2.8 lbs/gallon.

**SECTION 10: STABILITY AND REACTIVITY****Hazardous Polymerization:**

Under normal conditions of storage and use, hazardous polymerization will not occur.

**Conditions to Avoid:**

Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke, extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, tools, appliances and any other possible sources of ignition prior to spray application, during use and until all vapors are exhausted from the area.

**Chemical Stability:**

The product is stable. Avoid heat, open flame, sparks, static electricity, freezing.

**Hazardous Decomposition Products:**

Carbon monoxide, carbon dioxide, and possible oxides of nitrogen.

**Incompatible Materials:**

Alkaline materials, strong acids and oxidizing materials.

**Possibility of Hazardous Reactions:**

Under normal conditions of use and storage, hazardous reactions will not occur.

**SECTION 11: TOXICOLOGICAL INFORMATION**

Available ingredient data is listed below:

**ACETONE (67-64-1)**

Acute Dermal Toxicity	LD50: >7,426 mg/kg (guinea)	
Acute Inhalation Toxicity	LC50: 32,000 ppm 4hrs (rat)	
Acute Oral Toxicity	LD50: 5,800 mg/kg (rat)	
Target Organ, Single Exposure	Category 3: Respiratory, Central Nervous System	May cause respiratory irritation, drowsiness or dizziness.
Eye Irritation	Category 2: Causes eye irritation.	

**DIMETHYL CARBONATE (616-38-6)**

Acute Dermal Toxicity	LD50: >5,000 mg/kg (rabbit)
Acute Inhalation Toxicity	LC50:>140 mg/l 4hrs (rat)
Acute Oral Toxicity	LD50: 13,000 mg/kg (rat)

**HIGH FLASH NAPHTHA (64742-95-6)**

Acute Dermal Toxicity	LD50: >3,160 mg/kg (rabbit)	
Acute Inhalation Toxicity	LC50: >6,193 mg/m <sup>3</sup> 4hrs (rat)	
Acute Oral Toxicity	LD50: >3,492 mg/kg (rat)	
Aspiration Toxicity	Category 1	May be fatal if swallowed and enters airways.
Target Organ, Single Exposure	Category 3: Respiratory, Central Nervous System	May cause respiratory irritation, drowsiness or dizziness.
Carcinogenicity Classification	IARC Group 2B	Contains Cumene,(CAS No. 98-82-8), which is classified as possibly carcinogenic to humans.

**GLYCOL ETHER EB ACETATE (112-07-2)**

Acute Dermal Toxicity	LD50: >2,000 mg/kg (guinea pig)	
Acute Inhalation Toxicity	LC50: 3.91 mg/l (rat)	
Acute Oral Toxicity	LD50: 1,880 mg/kg (rat)	Category 4 Harmful if swallowed.

**PARACHLOROBENZOTRIFLUORIDE (98-56-6)**

Acute Dermal Toxicity	LD50: >3,300 mg/kg (rabbit)	
Acute Inhalation Toxicity	LC50: 33 mg/l 4hrs (rat)	
Acute Oral Toxicity	LD50: 13,000 mg/kg (rat)	
Skin Sensitization	Category 1	May cause an allergic skin reaction.
Target Organ, Single Exposure	Respiratory System	Category 3 May cause respiratory irritation.
Eye Irritation	Category 2A	Causes serious eye irritation.
Skin Irritation	Category 2	Causes skin irritation.

**TERTIARY BUTYL ACETATE (540-88-5)**

Acute Dermal Toxicity	LD50: >2,000 mg/kg	
Acute Inhalation Toxicity	LC50: 12.52 mg/l 4hrs	Category 4 Harmful if inhaled.
Acute Oral Toxicity	LD50: 4,500 mg/kg	
Target Organ, Single Exposure	Category 3: Respiratory, Central Nervous System	May cause respiratory irritation, drowsiness or dizziness.

**XYLENE (1330-20-7)**

Acute Dermal Toxicity	LD50: >4,200 mg/kg (rabbit)	Category 4 Harmful in contact with skin.
Acute Inhalation Toxicity	LC50: >20 mg/l 4hrs (rat)	Category 4 Harmful if inhaled.
Acute Oral Toxicity	LD50: 3,523 mg/kg (rat)	
Aspiration Toxicity	Category 1:	May be fatal if swallowed and enters airways.
Target Organ, Single Exposure	Category 3: Respiratory,	May cause respiratory irritation.
Target Organ, Repeated Exposure	Category 2: Liver, Kidney, Central Nervous System,	May cause damage to organs through prolonged or repeated exposure.
Eye Irritation	Category 2A:	Causes serious eye irritation.
Skin Irritation	Category 2:	Causes skin irritation.
Carcinogenicity Classification	Contains Ethyl Benzene: IARC Group 2B	Suspected of causing cancer.

**SECTION 12: ECOLOGICAL INFORMATION**

Available ingredient data is listed below:

**ACETONE (67-64-1)**

Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 5,540 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 12,700 mg/l 48hrs
Toxicity to algae	Chlorella pyrenoidosa (algae)	EC50: 3,020 mg/l 14 days
Persistence and degradability	Biodegradability	Readily

**GLYCOL ETHER EB ACETATE (112-07-2)**

Toxicity to fish	Pimephales promelas (fathead minnow)	LC50: 22 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	LC50: 37 mg/l 48hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EC50: 1,570 mg/l 72hrs
Toxicity to bacteria	Activated sludge	EC20: >1,000 mg/l 3hrs

Persistence and degradability	Biodegradability	Readily
Bioaccumulative potential	Bioaccumulation	Low potential for bioaccumulation
<b><u>HIGH FLASH NAPHTHA (64742-95-6)</u></b>		
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LL50: 9.2 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EL50: 3.2 mg/l 48hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	ErL50: 2.9 mg/l 72hrs
Persistence and degradability	Biodegradability	Readily
<b><u>PARACHLOROBENZOTRIFLUORIDE (98-56-6)</u></b>		
Toxicity to fish	Danio rerio (zebra fish)	LC50: 3 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	IC50: 2 mg/l 48hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EC50: >0.41 mg/l 72hrs
Persistence and degradability	Biodegradability	Not readily biodegradable
Bioaccumulative potential	Partition coefficient: n-octanol/water	Pow: 5,030 (25 C) log Pow: 3.7 (25 C)
<b><u>TERTIARY BUTYL ACETATE (540-88-5)</u></b>		
Acute aquatic toxicity	Harmful to aquatic life.	
Toxicity to fish	Low acute toxicity to fish.	
Toxicity to daphnia and other aquatic invertebrate	Low acute toxicity to aquatic invertebrates.	
Toxicity to algae	Harmful to algae. Can inhibit growth of aquatic algae	EC50: 16 ml/l 72hrs
	Pseudokirchneriella subcapitata (green algae)	EC50: 64 mg/l 96hrs
Toxicity to bacteria	High concentrations may be harmful to sewage treatment plant microbes	1.5 mg/l
Persistence and degradability	Biodegradability	Inherently biodegradable
Bioaccumulative potential	Bioaccumulation	Not expected to bioaccumulate
<b><u>XYLENE (1330-20-7)</u></b>		
Acute aquatic toxicity	Expected to be toxic to aquatic organisms.	
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 2.6 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 1 mg/l 24hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	ErC50: 4.36 mg/l 73hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulative potential	Partition coefficient: n-octanol/water	Log Kow: 3.12 - 3.16

### **SECTION 13: DISPOSAL CONSIDERATIONS**

**Recommendations:** The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection, waste disposal legislation and any regional local authority requirements. Empty containers should be disposed of through an approved waste management facility. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, ensure conformity to all applicable hazardous waste regulations, and consult your local or regional authorities.

### **SECTION 14: TRANSPORT INFORMATION**

UN NUMBER: UN1263

UN PROPER SHIPPING NAME: PAINT

TRANSPORT HAZARD CLASS: 3

PACKING GROUP: II

**SPECIAL PRECAUTIONS:** The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the shipper and the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Local Government regulations and rules should prevail.

### **SECTION 15: REGULATORY INFORMATION**

#### **United States Federal Regulations:**

**OSHA:** OSHA Hazard Communication Standard 29 CFR 1910.1200  
A component(s) of this product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### **EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA RQ - 40 CFR302.4(a):** List of Hazardous Substances and Reportable Quantities (RQ)

ACETONE	67-64-1	5,000 lbs.
GLYCOL ETHER EB ACETATE	112-07-2	Glycol Ethers N230
TERTIARY BUTYL ACETATE	540-88-5	5,000 lbs.
XYLENE	1330-20-7	100 lbs
Xylene Component: ETHYL BENZENE	100-41-4	1,000 lbs.

#### **SARA Section 311/312 Hazard Category - 40 CFR 370.2**

This product is considered, under applicable definitions, to meet the following categories:  
Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**SARA 313 Components - 40 CFR 372.65**

This product contains the following substances subject to the reporting requirements of Section 313 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and 40 CFR 372:

GLYCOL ETHER EB ACETATE	112-07-2 N230
HIGH FLASH NAPHTHA	64742-95-6
Contains: 1,2,4-Trimethylbenzene	95-63-6
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

**STATE REGULATIONS:**

**California Proposition 65:** WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

ACETONE	67-64-1
GLYCOL ETHER EB ACETATE	112-07-2
HIGH FLASH NAPHTHA	64742-95-6
Contains: 1,2,4-Trimethylbenzene	95-63-6
Cumene	98-82-8
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

**New Jersey, Pennsylvania, Massachusetts**

ACETONE	67-64-1
DIMETHYL CARBONATE	616-38-6
GLYCOL ETHER EB ACETATE	112-07-2
HIGH FLASH NAPHTHA	64742-95-6
Contains: 1,2,4-Trimethylbenzene	95-63-6
Cumene	98-82-8
PARACHLOROBENZOTRIFLUORIDE	98-56-6
TERTIARY BUTYL ACETATE	540-88-5
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

**SECTION 16: OTHER INFORMATION****HMIS RATING**

<b>Health:</b>	<b>3</b>
<b>Flammability:</b>	<b>3</b>
<b>Personal Hazard:</b>	<b>1</b>
<b>Personal Protection:</b>	<b>J</b>

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

DISCLAIMER: The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date. Coventry Coatings Corp. makes no representation, warranty or guarantee as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

DATE ISSUED: 5/29/2017  
Version No.: 2017HRB-2