

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 1 of 11

Printed: 07/29/2024

Revision: 07/29/2024


Supersedes Revision: 01/20/2021

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Naked Gun Spray Paint Remover  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Web site address:** www.wmbarr.com  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Intended Use:** Removes both solvent and waterborne paints from hard to reach areas  
**Product Code:** ENGC11131, ENGC11131CN, ENGC11

### 2. HAZARDS IDENTIFICATION

Flammable Aerosols, Category 1  
Gas Under Pressure, Liquefied gas  
Acute Toxicity: Oral, Category 4  
Acute Toxicity: Skin, Category 4  
Acute Toxicity: Inhalation, Category 4  
Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Germ Cell Mutagenicity, Category 1A  
Carcinogenicity, Category 1B  
Specific Target Organ Toxicity (single exposure), Category 1  
Aspiration Toxicity, Category 1  
Simple Asphyxiant



**GHS Signal Word:** **Danger**

**GHS Hazard Phrases:** H223: Flammable aerosol.  
H280: Containers gas under pressure; may explode if heated.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H340: May cause genetic defects.  
H350: May cause cancer.  
H370: Causes damage to organ.

**GHS Precautionary Phrases:** P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211: Do not spray on an open flame or any other ignition source.  
P251: Pressurized container: Do not pierce or burn, even after use.  
P260: Do not breathe gas/mist/vapors/spray.  
P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 2 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

<b>GHS Response Phrases:</b>	P281: Use personal protective equipment as required.
	P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P312: Call a POISON CENTER or doctor/physician if you feel unwell.
	P302+352: IF ON SKIN: Wash with plenty of soap and water.
	P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P307+311: IF exposed: Call a POISON CENTER or doctor/physician.
	P308+313: IF exposed or concerned: Get medical attention/advice.
	P321: Specific treatment see label.
	P322: Specific measures label.
	P330: Rinse mouth.
	P331: Do NOT induce vomiting.
	P332+313: If skin irritation occurs, get medical advice/attention.
	P337+313: If eye irritation persists, get medical advice/attention.
	P362: Take off contaminated clothing and wash before re-use.
	P363: Wash contaminated clothing before reuse.
<b>GHS Storage and Disposal Phrases:</b>	P405: Store locked up.
	P410+403: Protect from sunlight and store in well-ventilated place.
	P412: Do not expose to temperatures exceeding 50 °C/122 °F.
	P501: Dispose of contents/container according to local, state and federal regulations.
<b>Potential Health Effects (Acute and Chronic):</b>	Listed above.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #	Molecular Formula
67-64-1	Acetone {2-Propanone}	30.0 -60.0 %	AL3150000	C3H6O
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	10.0 -30.0 %	NA	NA
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	7.0 -13.0 %	PC1400000	CH3OH
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	3.0 -7.0 %	ZE2100000	C6H4(CH3)2
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	1.0 -5.0 %	KJ8575000	CH3(CH2)3OCH2CH2OH
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	1.0 -5.0 %	AI8925000	C6H12O3
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	1.0 -5.0 %	EL6475000	C4H8O
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	1.0 -5.0 %	DA0700000	CH3CH2C6H5
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	0.5 -1.5 %	DC3325000	C9H12
64742-95-6	Petroleum Hydrocarbons	1.0 -5.0 %	WF3400000	?
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	0.1 -1.0 %	GR8575000	C9H12

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

**SAFETY DATA SHEET**  
**Naked Gun Spray Paint Remover**

Page: 3 of 11  
Printed: 07/29/2024  
Revision: 07/29/2024  
Supersedes Revision: 01/20/2021

## 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:**

**Skin:**  
Remove contaminated clothing. Immediately wash skin thoroughly with large amounts of water and mild soap, if available. Seek medical attention if irritation develops or persists.

**Eyes:**  
Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

**Inhalation:**  
Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**Ingestion:**  
If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**Signs and Symptoms Of Exposure:**

Refer to Section 2.

## 5. FIRE FIGHTING MEASURES

**Flammability Classification:** Level 3 Aerosol

**Flash Point:** No data.

**Explosive Limits:** LEL: 1.8 % UEL: 12.8 %

**Autoignition Pt:** N.D.

**Suitable Extinguishing Media:** Dry chemical, CO2, alcohol-resistant foam or water spray.

**Unsuitable Extinguishing Media:** None known.

**Fire Fighting Instructions:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.  
Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas.

Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up.

Stay away from heads of containers that have been exposed to intense heat or flame. Containers can build up pressure if exposed to heat (fire).

**Flammable Properties and Hazards:**

EXTREMELY FLAMMABLE.

Flashpoint of liquid concentrate: ~10 F (SCC)

Flashpoint of propellant: -142.5 F (closed cup)

**Hazardous Combustion Products:**

Decomposition may produce carbon monoxide and carbon dioxide.

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 4 of 11  
Printed: 07/29/2024  
Revision: 07/29/2024  
Supersedes Revision: 01/20/2021

### 6. ACCIDENTAL RELEASE MEASURES

<b>Steps To Be Taken In Case Material Is Released Or Spilled:</b>	Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut of ignition sources; keep flares, smoking or flames out of hazard area.  Small Spills: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.  Large Spills: dike far ahead of spill for later disposal.
---	--

### 7. HANDLING AND STORAGE

<b>Precautions To Be Taken in Handling:</b>	Danger! Contents under pressure. Do not puncture or incinerate. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.  Keep away from sources of ignition. Ground and bond containers when transferring material.
<b>Precautions To Be Taken in Storing:</b>	Keep container closed when not in use. Do not store in direct sunlight. Store in a tightly closed container. Store in cool, dry area.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
67-64-1	Acetone {2-Propanone}	ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
		OSHA PELs	PEL: 1000 ppm	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
		OSHA PELs	PEL: 200 ppm	
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	ACGIH TLV	TLV: 100 ppm STEL: 150 ppm	
		OSHA PELs	PEL: 100 ppm	
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	ACGIH TLV	TLV: 20 ppm	
		OSHA PELs	PEL: 50 ppm	
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	ACGIH TLV	TLV: 200 ppm STEL: 300 ppm	
		OSHA PELs	PEL: 200 ppm	
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	ACGIH TLV	TLV: 100 ppm STEL: 125 ppm	
		OSHA PELs	PEL: 100 ppm	
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	ACGIH TLV	TLV: 50 ppm	

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 5 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	OSHA PELs	PEL: 50 ppm	
(continued)				
<b>Personal Protective Equipment Symbols:</b>				
<b>Respiratory Equipment (Specify Type):</b>		A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.		
<b>Eye Protection:</b>		If the work area is not properly ventilated to keep airborne levels below their exposure limits, you must use a properly fitted and maintained NIOSH approved respirator for organic vapors. A dust mask does not provide protection against vapors.		
<b>Protective Gloves:</b>		Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Chemical goggles or face shields are recommended when splashing or spraying of chemical is possible. A faceshield provides more protection to help reduce chemical contact to the face and eyes.		
<b>Other Protective Clothing:</b>		Wear gloves with as much resistance to the chemical ingredients as possible. Laminate film gloves offer the best protection. Other glove materials such as nitrile may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.		
<b>Engineering Controls (Ventilation etc.):</b>		Various application methods can dictate the use of additional protective safety equipment, such as impermeable aprons to minimize exposure.		
<b>Work/Hygienic/Maintenance Practices:</b>		Use only with adequate ventilation to prevent the buildup of vapors. Do not use in areas where vapors can accumulate and concentrate. Whenever possible, use outdoors in an open air area. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area away from the individual. If strong odor is noticed or you experience slight dizziness, headache, nausea, or other signs of inhalation exposure, STOP. The ventilation is inadequate. Leave the area immediately.		
		Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.		
		A source of clean water should be available in the work area when handling this product. Wash hands thoroughly after use and before eating, drinking, or smoking. Do not eat, drink, or smoke in the work area. Discard any clothing or other protective equipment that cannot be decontaminated.		

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ X ] Gas    [ X ] Liquid    [   ] Solid
<b>Appearance and Odor:</b>	Liquid, mobile, free and clear.
<b>pH:</b>	Not applicable
<b>Melting Point:</b>	N.D.
<b>Boiling Point:</b>	N.D.
<b>Flash Point:</b>	No data.
<b>Evaporation Rate:</b>	> 1
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: 1.8 %    UEL: 12.8 %

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 6 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

<b>Vapor Pressure:</b>	29.45 MM HG at 68.0 F (20.0 C)
	No data.
<b>Vapor Density (vs. Air=1):</b>	> 1
<b>Specific Gravity (Water=1):</b>	0.808
<b>Density:</b>	6.755 LB/GL
<b>Bulk density:</b>	ND
<b>Solubility in Water:</b>	partially
<b>Saturated Vapor Concentration:</b>	N.D.
<b>Octanol/Water Partition Coefficient:</b>	No data.
<b>Percent Volatile:</b>	100.0 %
<b>VOC / Volume:</b>	< 50.0000 % WT
<b>Autoignition Pt:</b>	N.D.
<b>Decomposition Temperature:</b>	N.D.
<b>Viscosity:</b>	N.D.
<b>Particle Size:</b>	ND
<b>Heat Value:</b>	ND
<b>a_fld_hdr[9]:</b>	N.D. = Not Determined NP = Not Applicable

### 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Unstable [ ]    Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	No data available.
<b>Incompatibility - Materials To Avoid:</b>	Chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide, and thioglycol. Strong oxidizers and acids. Nitric acid, sulfuric acid. Avoid contact with reactive metals, such as aluminum and magnesium.
<b>Hazardous Decomposition or Byproducts:</b>	Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ]    Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	No data available.

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 7 of 11  
Printed: 07/29/2024  
Revision: 07/29/2024  
Supersedes Revision: 01/20/2021

### 11. TOXICOLOGICAL INFORMATION

#### Toxicological Information:

Product has not been tested as a whole. Refer to section 2 for acute and chronic effects.  
CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 1330-20-7:

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.

Result:

Behavioral: Muscle contraction or spasticity.

Lungs, Thorax, or Respiration: Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxilogickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 111-76-2:

Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.

Result:

Behavioral: Ataxia.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.

Result:

Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Musculoskeletal system.

- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.

Result:

Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.

Result:



# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 8 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

Effects on Newborn: Apgar score (human only).  
Effects on Newborn: Other neonatal measures or effects.  
Effects on Newborn: Drug dependency.  
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 78-93-3:  
Standard Draize Test, Eyes, Human, 350.0 PPM.  
Result:  
Behavioral: Anticonvulsant.  
- Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943

CAS# 100-41-4:  
Tumorigenic Effects:, TCLO, Inhalation, Rat, 750.0 ppm.  
Result:  
Tumorigenic: Carcinogenic by RTECS criteria.  
Kidney, Ureter, Bladder: Tumors.  
  
Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.  
Result:  
Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).  
Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).  
Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).  
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 64742-95-6:  
Acute toxicity, LD50, Oral, Rat, 8400. MG/KG.  
Result:  
Behavioral: Somnolence (general depressed activity).  
Behavioral: Tremor.  
Lungs, Thorax, or Respiration:Other changes.  
- National Technical Information Service, Vol/p/yr: OTS0534799,

Standard Draize Test, Eyes, Species: Rabbit, 100.0 UL, 24 H, Mild.  
Result:  
Brain and Coverings: Changes in surface EEG.  
Blood:Changes in serum composition (e.g.  
Related to Chronic Data - changes in testicular weight.  
- National Technical Information Service, Vol/p/yr: OTS0534779,

### Carcinogenicity/Other Information:

IARC 3: Not Classifiable as to Carcinogenicity in Humans.  
IARC 2B - Possibly Carcinogenic to Humans  
ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans  
ACGIH A4 - Not Classifiable as a Human Carcinogen.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.



# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 9 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	n.a.	n.a.	n.a.	n.a.
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	n.a.	n.a.	n.a.	n.a.
64742-95-6	Petroleum Hydrocarbons	n.a.	n.a.	n.a.	n.a.
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	Possible	2B	n.a.	n.a.

## 12. ECOLOGICAL INFORMATION

**General Ecological Information:** Product has not been tested as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with all applicable local, state, and federal regulations.

## 14. TRANSPORT INFORMATION

### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Aerosols, flammable  
**DOT Hazard Class:** 2.1 FLAMMABLE GAS  
**UN/NA Number:** UN1950



**Additional Transport Information:** The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. REGULATORY INFORMATION

### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone {2-Propanone}	No	Yes NA	No
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	No	No	No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes NA	Yes (13%)
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes NA	Yes (7%)
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230 (5%)
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	No	No	Yes-Cat (5%)
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	No	Yes NA	No

# SAFETY DATA SHEET

## Naked Gun Spray Paint Remover

Page: 10 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes NA	Yes (5%)
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	No	No	Yes (1.5%)
64742-95-6	Petroleum Hydrocarbons	No	No	No
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	No	Yes NA	Yes (1%)

### EPA SARA Title III Section 313 Toxic Release Inventory.

This product contains a toxic chemical or chemicals subject to the reporting requirements of EPCRA Section 313 (40 CFR Section 372).

### California Proposition 65



#### WARNING

This product can expose you to chemicals including Ethylbenzene and Cumene, which are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	TSCA: Inventory
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	TSCA: Inventory
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP: VHAP TSCA: Inventory CA PROP.65: Yes: RDTox.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: HAP - Cat. TSCA: Inventory
108-65-6	Propylene glycol methyl ether acetate (PMA glycol ether acetate)	CAA HAP,ODC: HAP - Cat. TSCA: Inventory, 8A PAIR, 8D TERM
78-93-3	Methyl ethyl ketone {MEK; 2-Butanone}	TSCA: Inventory
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory CA PROP.65: Yes: Canc.
95-63-6	1,2,4-Trimethylbenzene {Pseudocumene}	TSCA: Inventory, 4 ECA
64742-95-6	Petroleum Hydrocarbons	TSCA: Inventory
98-82-8	Cumene {Benzene, 1-Methylethyl-; Isopropylbenzene}	CAA HAP,ODC: HAP: VHAP TSCA: Inventory CA PROP.65: Yes: Canc.

### Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

**SAFETY DATA SHEET**  
**Naked Gun Spray Paint Remover**

Page: 11 of 11

Printed: 07/29/2024

Revision: 07/29/2024

Supersedes Revision: 01/20/2021

**16. OTHER INFORMATION**

**Revision Date:** 07/29/2024 **Previous revision:** 01/20/2021

**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:** No data available.

**Company Policy or**

**Disclaimer:**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.