

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 1 of 8

Revision: 07/12/2021
Supersedes Revision: 06/30/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Aircraft Ultra Paint Remover
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Web site address: www.wmbarr.com
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Intended Use: Paint remover
Product Code: GAR4000, QAR4000

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2
Acute Toxicity: Inhalation, Category 4
Acute Toxicity: Oral, Category 4
Skin Corrosion/Irritation, Category 1B
Serious Eye Damage/Eye Irritation, Category 1
Carcinogenicity, Category 2
Specific Target Organ Toxicity (single exposure), Category 1
Specific Target Organ Toxicity (repeated exposure), Category 1



GHS Signal Word: Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.
Harmful if swallowed or if inhaled.
Causes severe skin burns and eye damage.
Causes serious eye damage.
Harmful if inhaled.
Suspected of causing cancer .
Causes damage to organs
Causes damage to organs - Eyes: through prolonged or repeated exposure.

GHS Precautionary Phrases: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/.../ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 2 of 8

Revision: 07/12/2021

Supersedes Revision: 06/30/2021

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed: Call a POISON CENTER or doctor/physician.
IF exposed or concerned: Get medical attention/advice.
Immediately call a POISON CENTER or doctor/physician.
Get medical attention/advice if you feel unwell.
Specific treatment see label.
Rinse mouth.
Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases:

Store in cool/well-ventilated place.
Store locked up.
Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Other Hazards:

Toxic to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	60.0 -80.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	3.0 -7.0 %
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	1.0 -5.0 %
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	1.0 -5.0 %
68439-46-3	Proprietary Ingredient	0.1 -1.5 %
9004-65-3	Hydroxypropyl methyl cellulose	0.1 -1.5 %
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	0.1 -1.5 %

Additional Chemical Information

Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

In Case of Inhalation: If inhaled, remove to fresh air.
In Case of Skin Contact: Immediately flush skin with plenty of water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing before reuse.
In Case of Eye Contact: Immediately flush eyes with water for at least 15 minutes while holding eyelids open. Get medical attention.
In Case of Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel.

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 3 of 8

Revision: 07/12/2021
Supersedes Revision: 06/30/2021

5. FIRE FIGHTING MEASURES

Flammability Classification:	Flammability Classification 1B
Flash Pt:	6.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: N.D. UEL: N.D.
Autoignition Pt:	N.D.
Suitable Extinguishing Media:	Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
Fire Fighting Instructions:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.
Flammable Properties and Hazards:	Vapor may travel considerable distance to source of ignition and flash back.
Hazardous Combustion Products:	Carbon oxides, nitrogen oxides.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.
---	--

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. A source of clean water should be kept in the immediate work area for flushing of the eyes and skin.
Precautions To Be Taken in Storing:	Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	ACGIH TLV	TLV: 50 ppm	
		OSHA PELs	STEL: 100 ppm	
			PEL: 200 ppm	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	ACGIH TLV	TLV: 200 ppm	
		OSHA PELs	STEL: 250 ppm	
			PEL: 200 ppm	
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	ACGIH TLV	TLV: 25 ppm	
		OSHA PELs	STEL: 35 ppm	
			PEL: 50 ppm	
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	ACGIH TLV	TLV: 100 ppm	
		OSHA PELs	STEL: 150 ppm	
			PEL: 100 ppm	
68439-46-3	Proprietary Ingredient	ACGIH TLV	TLV: 200 mg/m3	
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	ACGIH TLV	TLV: 20 ppm	
		OSHA PELs	STEL: 125 ppm	
			PEL: 100 ppm	

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 4 of 8

Revision: 07/12/2021

Supersedes Revision: 06/30/2021

Respiratory Equipment (Specify Type):	When used by the consumer following directions for use and with adequate ventilation, respiratory protection should not be needed.
Eye Protection:	Eye protection recommended.
Protective Gloves:	Wear appropriate gloves to prevent skin exposure.
Other Protective Clothing:	Wear appropriate protective clothing to prevent skin exposure.
Engineering Controls (Ventilation etc.):	A single prolonged skin exposure is not likely to result in the material being absorbed in harmful amounts.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Yellow opaque viscous liquid. Ammonia odor. Odor threshold not determined.
pH:	11.5 - 12.5
Melting Point:	N.D.
Boiling Point:	N.D.
Flash Pt:	6.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Evaporation Rate:	N.D.
Flammability (solid, gas):	EXTREMELY FLAMMABLE.
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or mm Hg):	N.D.
Vapor Density (vs. Air = 1):	> 1 Air = 1N.D.
Specific Gravity (Water = 1):	0.8842
Density:	7.357 LB/GL
Bulk density:	N.D.
Solubility in Water:	Appreciable
Octanol/Water Partition Coefficient:	N.D.
Percent Volatile:	95.9 % by weight.
VOC / Volume:	80.4700 % WT
Autoignition Pt:	N.D.
Decomposition Temperature:	N.D.
Viscosity:	N.D.
Particle Size:	N.D.
Heat Value:	N.D.
Corrosion Rate:	N.D.
Additional Physical Information	ND = Not Determined.

10. STABILITY AND REACTIVITY

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	**None known.
Incompatibility - Materials To Avoid:	**None known.
Hazardous Decomposition or Byproducts:	No data available.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid -	**None known.

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 5 of 8

Revision: 07/12/2021

Supersedes Revision: 06/30/2021

Hazardous Reactions:

11. TOXICOLOGICAL INFORMATION

Toxicological Information:

This product has not been tested as a whole. Information below will be for individual ingredients. Refer to section 2 for acute and chronic health effects.

CAS# 109-99-9:

Other Studies:, TDLo, Oral, Rat, 26280. mg/kg.

Result:

Liver: Tumors.

Kidney, Ureter, Bladder: Kidney tumors.

- Toxicologist., Soc. of Toxicology, Inc., 475 Wolf Ledge Parkway, Akron, OH 44311, Vol/p/yr: 60,286, 2001

CAS# 1330-20-7:

Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.

Result:

Behavioral: Muscle contraction or spasticity.

Lungs, Thorax, or Respiration: Other changes.

- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.

Result:

Behavioral: General anesthetic.

Behavioral: Somnolence (general depressed activity).

Behavioral: Irritability.

- "Sbornik Vysledku Toxikologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 68439-46-3:

Acute toxicity, LD50, Oral, Rat, 1378. MG/KG.

Result:

Behavioral: Somnolence (general depressed activity).

Behavioral: Ataxia.

Gastrointestinal: Hypermotility, diarrhea.

- Journal of the American College of Toxicology., Mary Ann Liebert, Inc., New York, NY, Vol/p/yr: 10(4),427, 1991

CAS# 100-41-4:

Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm.

Result:

Tumorigenic: Carcinogenic by RTECS criteria.

Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

Result:

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 6 of 8

Revision: 07/12/2021

Supersedes Revision: 06/30/2021

Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).
Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave.,
Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Carcinogenicity/Other Information:

ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans. ACGIH A4 - Not Classifiable as a Human Carcinogen. IARC 2B - Possibly Carcinogenic to Humans. IARC 3: Not Classifiable as to Carcinogenicity in Humans.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	n.a.	n.a.	n.a.	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	n.a.	n.a.	n.a.	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
68439-46-3	Proprietary Ingredient	n.a.	n.a.	n.a.	n.a.
9004-65-3	Hydroxypropyl methyl cellulose	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information:

This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint related material, flammable, corrosive.
DOT Hazard Class: 3 (8) FLAMMABLE LIQUID, CORROSIVE
UN/NA Number: UN3469 **Packing Group:** II



LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Paint related material, flammable, corrosive.
UN Number: 3469 **Packing Group:** II
Hazard Class: 3 (8) - FLAMMABLE LIQUID, **TDG Classification:** CORROSIVE

Additional Transport Information:

The shipper / supplier may be able to apply one of the following exceptions if allowed under 49 CFR Regulations: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49 CFR Hazmat Regulations. Please consult 49 CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 7 of 8

Revision: 07/12/2021
Supersedes Revision: 06/30/2021

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	No	Yes NA	No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes NA	Yes
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	Yes 500 LB	Yes NA	Yes
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	No	Yes NA	Yes
68439-46-3	Proprietary Ingredient	No	No	No
9004-65-3	Hydroxypropyl methyl cellulose	No	No	No
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	No	Yes NA	Yes

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	TSCA: Inventory, 8A PAIR
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP: VHAP TSCA: Inventory CA PROP.65: Yes: RDTox.
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	CWA NPDES TSCA: Inventory, 8A CAIR
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory
68439-46-3	Proprietary Ingredient	TSCA: Inventory
9004-65-3	Hydroxypropyl methyl cellulose	TSCA: Inventory
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	CAA HAP,ODC: HAP: VHAP CWA NPDES TSCA: Inventory CA PROP.65: Yes: Canc.

Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

SAFETY DATA SHEET

Aircraft Ultra Paint Remover

Page: 8 of 8

Revision: 07/12/2021

Supersedes Revision: 06/30/2021

16. OTHER INFORMATION

Revision Date: 07/12/2021 **Previous revision:** 06/30/2021

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: N.D.: Not determined.

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.