

MX-57

BASECOAT ACTIVATOR



Technical Data Sheet

Painters Hotline 800.735.0303

DESCRIPTION

MX-57 Basecoat Activator may be used in Matrix MPB/MSB basecoat when two toning or striping. It will enhance performance, improve repairability and strengthen the overall paint film. MX-57 may also be used as a replacement product for specific paint systems.

MIXING RATIO

<u>Option 1:</u>	<u>MPB</u> 1 Part	<u>MR-REDUCER</u> 1 Part	<u>MX-57</u> 1.5 oz per RTS qt.
<u>Option 2:</u>	<u>MPB</u> 1 Part	<u>MR-REDUCER</u> 1 Part	<u>MX-57</u> 5% (by volume)
<u>Option 3:</u>	Add 10% by volume to unreduced MPB basecoat. Then reduce MPB as normal.		
<u>Option 4:</u>	Add 42.5 grams to 32 oz. of RTS basecoat.		
<u>Option 5:</u>	<u>MSB</u> 1 Part	<u>MR-REDUCER</u> 1:1 1/2 Parts	<u>MX-57</u> 1.5 oz per RTS qt.
<u>Option 6:</u>	<u>MSB</u> 1 Part	<u>MR-REDUCER</u> 1:1 1/2 Parts	<u>MX-57</u> 5% (by volume)

POT LIFE

The pot life of MPB/MSB with MX-57 added is 1-2 hours at 70° F.

Note: Mixed product must be discarded if MX-57 has been used.

EQUIPMENT CLEAN-UP

Clean equipment immediately after use with MX-110 Gun Wash reducer a high quality lacquer thinner or urethane reducer.

FOR INDUSTRY USE ONLY

Read MSDS Before Use

The contents of the package must be blended with other components before the product can be used. Any mixture of components will have hazards of all components. Before opening the packages, read all warning labels. Follow all precautions.

The material is designed for application only by professionally trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public.

SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.

NOTE: Matrix Systems products are not recommended for use in temperatures below 65°F. Use below these temperatures will effect dry times and performance.

Put it to the test!

www.matrixsystem.com