

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 4/19/2023 Revision date: 5/16/2023 Supersedes: 4/20/2023 Version: 1.2

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : PROXL OEM PANEL COLOUR AEROSOL GREY 400ML  
Product code : 908288-US

#### 1.2. Recommended use and restrictions on use

Recommended use : Industrial spraying, Non industrial spraying  
Restrictions on use : All other uses not recommended above

#### 1.3. Supplier

Capella Inc  
370 W. Pleasantview Ave, Suite 2-281V  
Hackensack, New Jersey 07601  
United States  
T (800) 451-0917  
[sds@capellasolutionsinc.com](mailto:sds@capellasolutionsinc.com)

#### 1.4. Emergency telephone number

Emergency number : For Hazardous Materials or Dangerous Goods Incident Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night: 1-800-424-9300 (Toll Free, USA) / 703-527-3887 (Virginia, USA)  
CCN 1014359

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable aerosol Category 1	Extremely flammable aerosol
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity – Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness
Full text of H statements : see section 16	

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :  
Extremely flammable aerosol  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Suspected of causing cancer

Precautionary statements (GHS US) :  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Avoid breathing gas, mist, spray, vapors.  
Wash hands, forearms and face thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear eye protection, protective clothing.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
If exposed or concerned: Get medical advice/attention.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

44.01% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
48.83% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	CAS-No.: 67-64-1	20 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Dimethyl ether	CAS-No.: 115-10-6	15 – 20	Flam. Gas 1, H220 Press. Gas (Comp.), H280
n-Butyl acetate	CAS-No.: 123-86-4	10 – 15	Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Acute 3, H402
Propane	CAS-No.: 74-98-6	5 – 10	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Butane (containing < 0,1 % butadiene)	CAS-No.: 106-97-8	5 – 10	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Isobutane (containing < 0,1 % butadiene)	CAS-No.: 75-28-5	5 – 10	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Titanium dioxide	CAS-No.: 13463-67-7	2 – 5	Carc. 2, H351

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Butan-1-ol	CAS-No.: 71-36-3	1 – 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Take off contaminated clothing and wash it before reuse. Wash skin with plenty of water. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: May cause moderate irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause severe irritation. Redness, pain.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Ingestion may cause nausea and vomiting.
Most Important Symptoms/Effects	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Causes serious eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Contains gas under pressure; may explode if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Proper grounding procedures to avoid static electricity should be followed. Use non-sparking tools. Avoid all personal contact including breathing in the spray, mist, gas, vapors. Do not take actions involving personal risks.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate the danger area. If outdoors, move to an area upwind of the danger area. If possible without taking personal risks, remove ignition sources, ventilate area. Prevent other non-emergency personnel from entering the danger area.

##### 6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Evacuate personnel to a safe area. Remove all sources of ignition. Ventilate spillage area.

#### 6.2. Environmental precautions

Avoid release to the environment. Do NOT wash away into sewer. Do not let the product reach soil, drains, sewers, or surface and ground water.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain with non-combustible inert absorbent.  
Methods for cleaning up : Take up in non-combustible inert absorbent and place into container for disposal. Contaminated absorbent material may pose the same hazard as the spilt product. Decontaminate surfaces and equipment with water and detergent. Until a sufficient level of dilution is achieved, the decontamination water may pose the same hazards as the product. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing spray, mist, vapors, gas. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof equipment in any process generating vapors, gas air mixtures above the Lower Explosive Limit (refer to Section 9). Pressurized container: Do not pierce or burn, even after use.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect from sunlight. Store locked up. Store in a well-ventilated place.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PROXL OEM PANEL COLOUR AEROSOL GREY 400ML	
No additional information available	
Dimethyl ether (115-10-6)	
No additional information available	
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone
ACGIH OEL TWA	250 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2023
USA - ACGIH - Biological Exposure Indices	
Local name	ACETONE
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL TWA	2400 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
n-Butyl acetate (123-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Butyl acetate
ACGIH OEL TWA	50 ppm
ACGIH OEL STEL	150 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	n-Butyl-acetate
OSHA PEL TWA	710 mg/m³
	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Propane (74-98-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Propane
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane (74-98-6)	
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Propane
OSHA PEL TWA	1800 mg/m <sup>3</sup>
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Butane (containing < 0,1 % butadiene) (106-97-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Butane
ACGIH OEL STEL	1000 ppm (EX - Explosion hazard)
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2023
Titanium dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	0.2 mg/m <sup>3</sup> (Nanoscale particles. R - Repirable particulate matter)
	2.5 mg/m <sup>3</sup> (Finescale particles. R - Repirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Isobutane (containing < 0,1 % butadiene) (75-28-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Isobutane
ACGIH OEL STEL	1000 ppm (EX - Explosion hazard)
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2023
Butan-1-ol (71-36-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Butanol
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2023

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Butan-1-ol (71-36-3)

#### USA - OSHA - Occupational Exposure Limits

Local name	n-Butyl alcohol
OSHA PEL TWA	300 mg/m <sup>3</sup>
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Use general ventilation, local exhaust ventilation or process enclosure to keep the airborne concentrations below the permissible exposure limits.
Environmental exposure controls	: Avoid release to the environment. Take measures to reduce or limit air emissions and releases to soil and the aquatic environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Personal protective equipment should be chosen according to national standards and in discussion with the supplier of the protective equipment.

#### Hand protection:

Butyl rubber protective gloves with a permeation time of > 480 minutes minutes for each ingredient of this mixture.

#### Eye protection:

Chemical goggles or face shield

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Color	: Gray
Odor	: Solvent-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: 400 kPa (20°C/68°F)

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.8 g/cm <sup>3</sup> (20°C/68°F)
Solubility	: Material insoluble in water. Water: Not miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 240 °C (464°F)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: Lower explosion limit: 1.2 vol % Upper explosion limit: 26.2 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

Additional information	: Maximum Incremental Reactivity (MIR): 0.71 This product has been based on the Californian regulation for consumer products using the most recent values. Capella Solutions Inc have classified this product as a flat coating.
------------------------	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Oxidizing agents. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

### PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

Unknown acute toxicity (GHS US)	44.01% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 48.83% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
---------------------------------	--



# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Dimethyl ether</b>	
LC50 Inhalation - Rat [ppm]	164000 ppm
<b>Acetone</b>	
LD50 oral rat	5800 mg/kg body weight
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h
<b>n-Butyl acetate</b>	
LD50 oral rat	10800 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat	21 mg/l
<b>Butane (containing &lt; 0,1 % butadiene)</b>	
LC50 Inhalation - Rat	658 mg/l/4h
<b>Titanium dioxide</b>	
LD50 oral rat	> 5000 mg/kg body weight
<b>Butan-1-ol</b>	
LD50 oral rat	2290 mg/kg
LD50 dermal rabbit	3430 mg/kg
Skin corrosion/irritation	: Not classified
<b>n-Butyl acetate</b>	
pH	6.2 (5,3 g/L   20°C/68°F)
Serious eye damage/irritation	: Causes serious eye irritation.
<b>n-Butyl acetate</b>	
pH	6.2 (5,3 g/L   20°C/68°F)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
<b>Titanium dioxide</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
<b>Acetone</b>	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight
NOAEL (animal/male, F0/P)	900 mg/kg body weight
STOT-single exposure	: May cause drowsiness or dizziness.
<b>Acetone</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>n-Butyl acetate</b>	
STOT-single exposure	May cause drowsiness or dizziness.

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Butan-1-ol	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified
n-Butyl acetate	
LOAEL (oral,rat,90 days)	500 mg/kg body weight
NOAEL (oral,rat,90 days)	125 mg/kg body weight
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
n-Butyl acetate	
Viscosity, kinematic	0.83 mm <sup>2</sup> /s (20°C/ 68°F)
Butan-1-ol	
Viscosity, kinematic	3.641 mm <sup>2</sup> /s
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: May cause moderate irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause severe irritation. Redness, pain.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Ingestion may cause nausea and vomiting.
Most Important Symptoms/Effects	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Dimethyl ether	
LC50 - Fish [1]	> 4.1 g/l
EC50 - Crustacea [1]	> 4.4 g/l
EC50 96h - Algae [1]	154917 mg/l
ErC50 algae	155 mg/l
Acetone	
LC50 - Fish [1]	8300 mg/l
EC50 - Crustacea [1]	8450 mg/l
ErC50 algae	7200 mg/l
LOEC (chronic)	> 79 mg/l
NOEC (chronic)	≥ 79 mg/l
NOEC chronic crustacea	2212 mg/l
n-Butyl acetate	
LC50 - Fish [1]	18 mg/l
EC50 - Crustacea [1]	44 mg/l
EC50 72h - Algae [1]	397 mg/l

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Butyl acetate	
EC50 72h - Algae [2]	246 mg/l
LOEC (chronic)	47.6 mg/l
NOEC (chronic)	23.2 mg/l
Titanium dioxide	
EC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l
LOEC (chronic)	5 mg/l
Butan-1-ol	
LC50 - Fish [1]	1376 mg/l
EC50 - Crustacea [1]	1328 mg/l
EC50 96h - Algae [1]	225 mg/l
ErC50 algae	225 mg/l
NOEC (chronic)	4.1 mg/l
NOEC chronic crustacea	4.1 mg/l

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. This material and its container must be disposed of as hazardous waste.
Ecological information	: Avoid release to the environment.

## SECTION 14: Transport information




In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
1950	1950	1950

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	IMDG	IATA
<b>14.2. Proper Shipping Name</b>		
Aerosols	AEROSOLS	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT)	: UN1950
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### IMDG

Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
ERG code (IATA)	: 10L

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Butan-1-ol	CAS-No. 71-36-3	1 – 3%
Propan-2-ol	CAS-No. 67-63-0	≤ 1%

#### Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

#### n-Butyl acetate (123-86-4)

CERCLA RQ	5000 lb
-----------	---------

#### Butan-1-ol (71-36-3)

CERCLA RQ	5000 lb
-----------	---------

### 15.2. International regulations

#### CANADA

##### Dimethyl ether (115-10-6)

Listed on the Canadian DSL (Domestic Substances List)

##### Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

##### n-Butyl acetate (123-86-4)

Listed on the Canadian DSL (Domestic Substances List)

##### Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

##### Butane (containing < 0,1 % butadiene) (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Titanium dioxide

Listed on the Canadian DSL (Domestic Substances List)

### Isobutane (containing < 0,1 % butadiene) (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

### Butan-1-ol (71-36-3)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

#### Dimethyl ether (115-10-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Acetone (67-64-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### n-Butyl acetate (123-86-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Propane (74-98-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Butane (containing < 0,1 % butadiene) (106-97-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Titanium dioxide

Listed on IARC (International Agency for Research on Cancer)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Isobutane (containing < 0,1 % butadiene) (75-28-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Butan-1-ol (71-36-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# PROXL OEM PANEL COLOUR AEROSOL GREY 400ML

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations



#### WARNING:

This product can expose you to Titanium dioxide (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 5/16/2023

Full text of H-phrases	
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.