1 Identification

- · Product identifier
- · Trade name: 39063 Gloss Trim Black Aerosol
- · Article number: 39063
- $\cdot \textit{Relevant identified uses of the substance or \textit{mixture and uses advised against}}$

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Muta. 1A	H340	May cause genetic defects.
Carc. 2	H351	Suspected of causing cancer.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2)

USA



Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 1)

· Hazard pictograms









GHS04

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Petroleum gases, liquefied, sweetened

toluene

acetone

ethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H340 May cause genetic defects. H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. H373

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P301+P310 If swallowed: Immediately call a poison center/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)



Trade name: 39063 Gloss Trim Black Aerosol

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:		
67-64-1	acetone	30 - 40%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
108-88-3	toluene	13 - 30%
141-78-6	ethyl acetate	7 - 10%
78-93-3	butanone	5 - 7%
108-65-6	2-methoxy-1-methylethyl acetate	1.5 - 5%
	NJ TSRN: 8009285004 Polyester Plasticizer	1.5 - 5%
1333-86-4	Carbon black	≤1%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot \textit{Special hazards arising from the substance or \textit{mixture}} \ \textit{No further relevant information available}.$
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that	t require monitoring at the workplace:
67-64-1 acetone	

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

BEI

(Contd. on page 5)



Trade name: 39063 Gloss Trim Black Aerosol

<i>108-8</i>	8-3 toluene
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 75 mg/m³, 20 ppm BEI
141-7	8-6 ethyl acetate
PEL	Long-term value: 1400 mg/m³, 400 ppm
REL	Long-term value: 1400 mg/m³, 400 ppm
TLV	Long-term value: 1440 mg/m³, 400 ppm
	-3 butanone
PEL	Long-term value: 590 mg/m³, 200 ppm
REL	Short-term value: 885 mg/m³, 300 ppm
KLL	Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m³, 300 ppm
12,	Long-term value: 590 mg/m³, 200 ppm
	BEI
108-6	5-6 2-methoxy-1-methylethyl acetate
WEEI	L Long-term value: 50 ppm
Inore	dients with biological limit values:
_	-1 acetone
	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)
108-8	8-3 toluene
BEI (0.02 mg/L
1	Medium: blood
	Time: prior to last shift of workweek
1	Parameter: Toluene
/	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
0	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)
	-3 butanone
	2 mg/L
1	Medium: urine
	Time: end of shift

Safety Data Sheet acc. to OSHA HCS



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 5)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Color: According to product specification

Odor: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55 °C

(Contd. on page 7)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39063 Gloss Trim Black Aerosol

	(Contd. of page
Flash point:	< -17 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	460 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
Vapor pressure at 20 °C:	233 hPa
Density at 20 °C:	0.78448 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	92.8 %
VOC content:	62.8 %
	701.7 g/l / 5.86 lb/gl
Solids content:	7.8 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- $\cdot \textbf{Incompatible materials:} \ No \ further \ relevant \ information \ available.$
- · Hazardous decomposition products:

Nitrogen oxides

Hydrocarbons

Carbon monoxide and carbon dioxide

TICA

acc. to OSHA HCS

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 7)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
108-88-3	toluene	3	
1333-86-4	Carbon black	2B	
111-76-2	2-butoxyethanol	3	
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			

12 Ecological information

None of the ingredients is listed.

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 9)



Trade name: 39063 Gloss Trim Black Aerosol

· Other adverse effects No further relevant information available.

(Contd. of page 8)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN1950
Aerosols, flammable
1950 Aerosols
AEROSOLS
AEROSOLS, flammable
2.1
2.1
2 5F Gases
2.1
2.1
2.1 2.1
2.1
Void

USA

Safety Data Sheet acc. to OSHA HCS

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39063 Gloss Trim Black Aerosol

	(Contd. of page
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number:	Warning: Gases F-D,S-U
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations · Remarks	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg ORM-D 49CFR-173-150,156, 306
· ADR · Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN1950, Aerosols, 2.1

15 Regulatory information

111-76-2 2-butoxyethanol

9038-95-3 OXIRANE, ME, POLYMER

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

	· Sara		
	· Section 355 (extremely hazardous substances):		
	None of the ingredient is listed.		
Ī	· Section 313 (Specific toxic chemical listings):		
Ī	108-88-3 to	luene	
Ī	78-93-3 bi	utanone	
	111-76-2 2-	-butoxyethanol	
Ī	TSCA (Toxic Substances Control Act):		
Ī	67-64-1	acetone	
	68476-86-8	Petroleum gases, liquefied, sweetened	
	108-88-3	toluene	
	141-78-6	ethyl acetate	
	763-69-9	ethyl 3-ethoxypropionate	
	<i>78-93-3</i>	butanone	
	108-65-6	2-methoxy-1-methylethyl acetate	
	1333-86-4	Carbon black	

(Contd. on page 11)

acc. to OSHA HCS

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 10)

	known to cause cancer:
1333-86-4	Carbon black

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Proposition 65

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Cancerogenity categories

· EPA (Environmental Protection Agency)		
67-64-1	acetone	I
108-88-3	toluene	II
78-93-3	butanone	I
111-76-2	2-butoxyethanol	NL

· TLV (Threshold Limit Value established by ACGIH)			
67-64-1	acetone	A4	
108-88-3	toluene	A4	
1333-86-4	Carbon black	A4	
111-76-2	2-butoxyethanol	<i>A3</i>	

· NIOSH-Ca (National Institute for Occupational Safety and Health) 1333-86-4 Carbon black

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS04 GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Petroleum gases, liquefied, sweetened

toluene

acetone

ethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H340 May cause genetic defects.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- May cause damage to organs through prolonged or repeated exposure. H373
- May be fatal if swallowed and enters airways. H304

(Contd. on page 12)

Safety Data Sheet acc. to OSHA HCS



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39063 Gloss Trim Black Aerosol

(Contd. of page 11)

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P301+P310 If swallowed: Immediately call a poison center/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/01/2015 / 4
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Muta. 1A: Germ cell mutagenicity, Hazard Category 1A

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

* Data compared to the previous version altered.

USA