

1 Identification

- **Product identifier**
- **Trade name:** 39133 Flexible Primer Surfacer
- **Article number:** 39133
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Carc. 1A	H350	May cause cancer.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT SE 2	H371-H336	May cause damage to organs. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

- **Signal word** *Danger*



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
toluene
acetone
titanium dioxide

· **Hazard statements**

H222-H229 *Extremely flammable aerosol. Pressurized container: May burst if heated.*
H315 *Causes skin irritation.*
H319 *Causes serious eye irritation.*
H350 *May cause cancer.*
H361 *Suspected of damaging fertility or the unborn child.*
H371-H336 *May cause damage to organs. May cause drowsiness or dizziness.*
H373 *May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
P251 *Pressurized container: Do not pierce or burn, even after use.*
P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
P211 *Do not spray on an open flame or other ignition source.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P321 *Specific treatment (see on this label).*
P405 *Store locked up.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
------------	---------------------------------------	----------

(Contd. on page 3)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 2)

67-64-1	acetone	13 - 30%
14808-60-7	Quartz (SiO ₂)	13 - 30%
1330-20-7	xylene	10 - 13%
110-19-0	isobutyl acetate	7 - 10%
108-88-3	toluene	1.5 - 5%
123-86-4	n-butyl acetate	1.5 - 5%
13463-67-7	titanium dioxide	1.5 - 5%
78-93-3	butanone	1.5 - 5%
14807-96-6	Talc	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

USA

(Contd. on page 4)



Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 3)

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm

Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

BEI

14808-60-7 Quartz (SiO₂)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³
*as respirable fraction

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 5)

USA



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 4)

REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
110-19-0 isobutyl acetate	
PEL	Long-term value: 700 mg/m ³ , 150 ppm
REL	Long-term value: 700 mg/m ³ , 150 ppm
TLV	Long-term value: 713 mg/m ³ , 150 ppm
108-88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI
123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm
78-93-3 butanone	
PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI
· Ingredients with biological limit values:	
67-64-1 acetone	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
1330-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

(Contd. on page 6)

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 5)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: MEK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· Flash point: -103 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 405 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:	1.1 Vol %
Upper:	13.0 Vol %

· Vapor pressure at 20 °C: 233 hPa

· Density at 20 °C: 0.91876 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents: 77.4 %

(Contd. on page 8)

USA



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39133 Flexible Primer Surfacer

(Contd. of page 7)

VOC content:	57.4 % 687.2 g/l / 5.73 lb/gl
Solids content:	22.6 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO ₂)	1
1330-20-7	xylene	3
108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
14807-96-6	Talc	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3

(Contd. on page 9)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 8)

100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration)		
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1950
· UN proper shipping name	
· DOT	Aerosols, flammable
· ADR	1950 Aerosols
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable

(Contd. on page 10)

USA

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class**

2.1

· **Label**

2.1

· **ADR**



· **Class**

2 5F Gases

· **Label**

2.1

· **IMDG, IATA**



· **Class**

2.1

· **Label**

2.1

· **Packing group**

· **DOT, ADR, IMDG, IATA**

Void

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Gases

· **EMS Number:**

F-D,S-U

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

(Contd. on page 11)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39133 Flexible Primer Surfacers

(Contd. of page 10)

· **UN "Model Regulation":** UN1950, Aerosols, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
	ACRYLIC RESIN
108-88-3	toluene
78-93-3	butanone
14807-96-6	Talc
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
67-56-1	methanol

· **TSCA (Toxic Substances Control Act):**

68476-86-8	Petroleum gases, liquefied, sweetened
67-64-1	acetone
14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
110-19-0	isobutyl acetate
108-88-3	toluene
123-86-4	n-butyl acetate
13463-67-7	titanium dioxide
78-93-3	butanone
14807-96-6	Talc
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
16883-83-3	benzyl 3-isobutyloxy-1-isopropyl-2-2-dimethylpropyl phthalate
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
51274-00-1	YELLOW IRON OXIDE

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
13463-67-7	titanium dioxide
1333-86-4	Carbon black
100-41-4	ethylbenzene

(Contd. on page 12)

Trade name: 39133 Flexible Primer Surfacer

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

67-56-1	methanol
---------	----------

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
---------	---------	---

1330-20-7	xylene	I
-----------	--------	---

108-88-3	toluene	II
----------	---------	----

78-93-3	butanone	I
---------	----------	---

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

100-41-4	ethylbenzene	D
----------	--------------	---

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
---------	---------	----

14808-60-7	Quartz (SiO ₂)	A2
------------	----------------------------	----

1330-20-7	xylene	A4
-----------	--------	----

108-88-3	toluene	A4
----------	---------	----

13463-67-7	titanium dioxide	A4
------------	------------------	----

14807-96-6	Talc	A4
------------	------	----

1333-86-4	Carbon black	A4
-----------	--------------	----

111-76-2	2-butoxyethanol	A3
----------	-----------------	----

100-41-4	ethylbenzene	A3
----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

13463-67-7	titanium dioxide
------------	------------------

1333-86-4	Carbon black
-----------	--------------

67-56-1	methanol
---------	----------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO₂)

toluene

acetone

titanium dioxide

(Contd. on page 13)



Trade name: 39133 Flexible Primer Surfacer

(Contd. of page 12)

· **Hazard statements**

H222-H229 *Extremely flammable aerosol. Pressurized container: May burst if heated.*

H315 *Causes skin irritation.*

H319 *Causes serious eye irritation.*

H350 *May cause cancer.*

H361 *Suspected of damaging fertility or the unborn child.*

H371-H336 *May cause damage to organs. May cause drowsiness or dizziness.*

H373 *May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

P251 *Pressurized container: Do not pierce or burn, even after use.*

P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*

P211 *Do not spray on an open flame or other ignition source.*

P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P321 *Specific treatment (see on this label).*

P405 *Store locked up.*

P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 04/01/2015 / 4

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 1A: Carcinogenicity, Hazard Category 1A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

· *** Data compared to the previous version altered.**