

1 Identification

- **Product identifier**
- **Trade name:** 39131;39134 Flexible Primer Surface
- **Article number:** 39131, 39134
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371-H336 May cause damage to organs. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

USA

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
toluene
titanium dioxide
n-butyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H371-H336 May cause damage to organs. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P280 Wear protective gloves / eye protection / face protection.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.
Weight percentages

(Contd. on page 3)


Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 2)

· Dangerous components:		
14808-60-7	Quartz (SiO ₂)	30 - 40%
1330-20-7	xylene	13 - 30%
108-88-3	toluene	10 - 13%
123-86-4	n-butyl acetate	7 - 10%
78-93-3	butanone	1.5 - 5%
13463-67-7	titanium dioxide	1.5 - 5%
67-64-1	acetone	1.5 - 5%
14807-96-6	Talc	1-1.5%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)


Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 3)

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

14808-60-7 Quartz (SiO₂)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³
*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³
*as respirable fraction

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

(Contd. on page 5)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 4)

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm
BEI

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm
BEI

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

108-88-3 toluene

(Contd. on page 6)


Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 5)

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

67-64-1 acetone

BEI 50 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 6)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	110 °C

· **Flash point:** 7 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	7.0 Vol %

· **Vapor pressure at 20 °C:** 29 hPa

· **Density at 20 °C:** 1.50929 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:** 574.3 g/l / 4.79 lb/gal

(Contd. on page 8)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 7)

· Organic solvents:	51.1 %
· VOC content:	48.1 %
	769.4 g/l / 6.42 lb/gl
· Solids content:	48.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO ₂)	1
1330-20-7	xylene	3
108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
14807-96-6	Talc	2B
7631-86-9	silicon dioxide, chemically prepared	3

(Contd. on page 9)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 8)

1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration)		
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|------------------------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · ADR | 1263 Paint, special provision 640D |
| · IMDG, IATA | PAINT |

(Contd. on page 10)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3

· **ADR, IMDG, IATA**



· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**

· **DOT, ADR, IMDG, IATA**

II

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Flammable liquids

· **EMS Number:**

F-E,S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **Remarks**

ORM-D 49CFR 173-150,156,306

· **ADR**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN1263, Paint, special provision 640D, 3, II

USA

(Contd. on page 11)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 10)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
	ACRYLIC RESIN
108-88-3	toluene
78-93-3	butanone
14807-96-6	Talc
111-76-2	2-butoxyethanol
100-41-4	ethylbenzene
67-56-1	methanol

· TSCA (Toxic Substances Control Act):

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
108-88-3	toluene
123-86-4	n-butyl acetate
78-93-3	butanone
13463-67-7	titanium dioxide
67-64-1	acetone
14807-96-6	Talc
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
51274-00-1	YELLOW IRON OXIDE
1333-86-4	Carbon black
111-76-2	2-butoxyethanol

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
13463-67-7	titanium dioxide
1333-86-4	Carbon black
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

108-88-3	toluene
----------	---------

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 12)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 11)

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
67-56-1	methanol

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
108-88-3	toluene	II
78-93-3	butanone	I
67-64-1	acetone	I
111-76-2	2-butoxyethanol	NL
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

14808-60-7	Quartz (SiO ₂)	A2
1330-20-7	xylene	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
67-64-1	acetone	A4
14807-96-6	Talc	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide
1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
toluene
titanium dioxide
n-butyl acetate

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.

(Contd. on page 13)

Trade name: 39131;39134 Flexible Primer Surface

(Contd. of page 12)

- H361 Suspected of damaging fertility or the unborn child.
H371-H336 May cause damage to organs. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
 - P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 - P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 - P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 - P280 Wear protective gloves / eye protection / face protection.
 - P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P321 Specific treatment (see on this label).
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 - **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Steve Gaver (sgaver@semproducts.com)
- **Date of preparation / last revision** 04/01/2015 / 3
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - Flam. Liq. 2: Flammable liquids, Hazard Category 2
 - Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 - Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 - Carc. 1A: Carcinogenicity, Hazard Category 1A
 - Repr. 2: Reproductive toxicity, Hazard Category 2
 - STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2
 - STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- *** Data compared to the previous version altered.**