

DESCRIPTION

Rust Preventer is a semi-transparent black internal panel compound to restore OEM corrosion protection on inner body panels.

FEATURES

- Non-hardening
- Sprayable in 360° pattern
- Superior adhesion
- Fast drying
- Excellent corrosion protection

SUITABLE SUBSTRATES

- Inner body panels, cavities, and channels

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39573	Rust Preventer	Transparent Black	Aerosol
39574	Rust Preventer	Transparent Black	Quart

	39573	39574
Regulatory VOC:	N/A	3.58 #/gal (430 g/L)
Actual VOC:	N/A	3.53 #/gal (424 g/L)
MIR:	Category ABT .812	N/A
Paintable:	No	No

HANDLING AND APPLICATION

PREPARATION:

Clean surface with **SEM Solve, Zero VOC Surface Cleaner** or compliant cleaner.

APPLICATION:

RUST PREVENTER AEROSOL

Shake can for 1 minute prior to use. Remove cap, attach straw or **Rust Preventer Aero Wand**.

RUST PREVENTER AEROSOL + AERO WAND

Apply 1-2 coats. Change the angle of the **Aero Wand**, and vary the depth of the wand inside the panel to ensure



Check local VOC regulations to ensure compliance of all products in your area.

complete coverage. Clean **Aero Wand** by attaching the tip and wand to **XXX Gun Cleaner** or solvent compliant with VOC regulations in your area.

Note:

With the **Rust Preventer Aero Wand** attached, the spray pattern is 360°, do not spray product without tip being inserted into inner panel access point.

RUST PREVENTER QUART + PREMIUM UNDERCOAT GUN AND WAND

Shake bottle for 1 minute prior to use, remove cap. Attach **Rust Preventer** to **Premium Undercoat Gun & Wand**.

Note:

With the **Premium Undercoat Gun & Wand** attached, the spray pattern is 360°, do not spray product without tip being inserted into inner panel access point.

Using 35-40 psi, apply 1-2 coats changing the angle of the gun, and varying the depth of the tip inside the panel to ensure complete coverage. Clean wand with **XXX Gun Cleaner** or solvent compliant with VOC regulations in your area.

STORAGE:

Rust Preventer should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Rust Preventer** is 3 years when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:
38371	SEM Solve	Gallon
38373	SEM Solve	Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
40401	Zero VOC Surface Cleaner	Gallon
40404	Zero VOC Surface Cleaner	Quart
71120	Rust Preventer Aero Wand	Each
71110	Premium Undercoat Gun & Wand	Each
77743	XXX Gun Cleaner	Aerosol



Check local VOC regulations to ensure compliance of all products in your area.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.