Printing date 04/01/2015 Reviewed on 04/01/2015

1 Identification

- · Product identifier
- · Trade name: 39804 Clear Chip Guard
- · Article number: 39804
- $\cdot \textit{Relevant identified uses of the substance or mixture and uses advised against}$

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 1)

· Hazard-determining components of labeling:

toluene butanone acetone

Cellulose Acetate Butyrate

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Specific treatment (see on this label). P321

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2Fire = 3REACTIVITY $\boxed{0}$ Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:

108-88-3 toluene

40 - 60%

(Contd. on page 3)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

		(Contd. of page 2)
78-93-3	butanone	10 -13%
67-64-1	acetone	7 - 10%
2807-30-9	2-(propyloxy)ethanol	5 - 7%
9004-36-8	Cellulose Acetate Butyrate	1.5 - 5%
	NJ TSRN: 8009285004 Polyester Plasticizer	1.5 - 5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

USA

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 $\cdot \textit{Specific end use}(s) \textit{ No further relevant information available}.$

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift
REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm

BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

BEI

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

BEI

(Contd. on page 5)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 4)

· Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 5)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

α	•		•		
- U - P	averea	ana	\cdot μ ρ m_{1}	cal nra	morring
	IAMIIATII		714371144		perties

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

Odor: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55 °C

· Flash point: -18 °C

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 230 °C

• Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 11.5 Vol %

· Vapor pressure at 20 °C: 105 hPa

• Density at 20 °C: 0.9 g/cm³
• Relative density Not determ

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 7)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	77.2 %	
VOC content:	67.6 %	
	683.0 g/l / 5.70 lb/gl	
Solids content:	22.8 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:			
108-88-3 t	oluene			
Oral	LD50	5000 mg/kg (rat)		
Dermal	<i>LD50</i>	12124 mg/kg (rabbit)		
Inhalative	LC50/4 h	5320 mg/l (mouse)		

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
108-88-3 toluene	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)

- USA

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

 \cdot **DOT** Paint

· ADR 1263 Paint, special provision 640D

· IMDG, IATA PAINT

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

(Contd. on page 9)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

	(Contd. of pa
Label	3
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number:	F-E,S-E
Transport in bulk according to Annex	· · · · · · · · · · · · · · · · · · ·
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	11
•	
DOT Quantity limitations	On passenger aircraft/rail: 5 L
Quantity annuations	On cargo aircraft only: 60 L
Remarks	ORM-D 49CFR 173-150,156,306
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1263, Paint, special provision 640D, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

	· Section 355	(extremely	hazardous	substances):
--	---------------	------------	-----------	------------	----

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

ACRYLIC RESIN

78-93-3 butanone

(Contd. on page 10)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 9) · TSCA (Toxic Substances Control Act): 108-88-3 toluene 78-93-3 butanone 67-64-1 acetone 2807-30-9 2-(propyloxy)ethanol 9004-36-8 Cellulose Acetate Butyrate · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: 108-88-3 toluene · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene

· Cancerogenity categories

· EPA (Environmental Protection Agency)			
108-88-3	toluene	II	
78-93-3	butanone	Ι	
67-64-1	acetone	Ι	

· TLV (Threshold Limit Value established by ACGIH)

127 (17	restrond than 4 white estate tished by 110 0111)	
108-88-3	toluene	A4
67-64-1	acetone	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS07

7 GHSC

- · Signal word Danger
- · Hazard-determining components of labeling:

toluene

butanone

acetone

Cellulose Acetate Butyrate

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 11)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39804 Clear Chip Guard

(Contd. of page 10)

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/01/2015 / 3
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

* Data compared to the previous version altered.

USA