### 1 Identification

- · Product identifier
- · Trade name: 39897 Patch Panel Adhesive
- · Article number: 39897
- $\cdot \textit{Relevant identified uses of the substance or mixture and uses advised against}$

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)



Trade name: 39897 Patch Panel Adhesive

(Contd. of page 1)

### · Hazard-determining components of labeling:

methyl methacrylate

2-hydroxyethyl methacrylate

ACRYLONITRILE/BUTADIENE RESIN

NEPHELINE SYENITE

#### · Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

*P280* Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Classification system:

#### · NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

(Contd. on page 3)



Trade name: 39897 Patch Panel Adhesive

		(Contd. of page 2)	
· Dangerous	· Dangerous components:		
80-62-6	methyl methacrylate	40 - 60%	
9003-56-9	ACRYLONITRILE/BUTADIENE RESIN	13 - 30%	
37244-96-5	NEPHELINE SYENITE	13 - 30%	
	2-hydroxyethyl methacrylate	5 - 7%	
614-45-9	tert-butyl perbenzoate	1-1.5%	
79-41-4	methacrylic acid	1-1.5%	
128-37-0	2,6-di-tert-butyl-p-cresol	1-1.5%	
56-23-5	carbon tetrachloride	≤1%	
123-31-9	1,4-dihydroxybenzene	≤1%	

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

HISA



Trade name: 39897 Patch Panel Adhesive

(Contd. of page 3)

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 $\cdot$  *Specific end use*(s) *No further relevant information available.* 

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	· Components with limit values that require monitoring at the workplace:		
80-62	2-6 methyl methacrylate		
PEL	Long-term value: 410 mg/m³, 100 ppm		
REL	Long-term value: 410 mg/m³, 100 ppm		
TLV	Short-term value: 410 mg/m³, 100 ppm		
	Long-term value: 205 mg/m³, 50 ppm		
	(SEN) NIC-DSEN		
<b>79-4</b> .	41-4 methacrylic acid		
REL	Long-term value: 70 mg/m³, 20 ppm		
	Skin		

Skin

TLV Long-term value: 70 mg/m³, 20 ppm

# 128-37-0 2,6-di-tert-butyl-p-cresol

REL	Long-term value: 10 mg/m³
TLV	Long-term value: 2* mg/m³
	*as inhalable fraction and vapor

(Contd. on page 5)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39897 Patch Panel Adhesive

(Contd. of page 4)

### 56-23-5 carbon tetrachloride

PEL Long-term value: 10 ppm

Ceiling limit value: 25; 200\* ppm

\*5-min peak in any 3 hrs

REL Short-term value: 12.6\* mg/m³, 2\* ppm

\*60-min;See Pocket Guide App. A

TLV Short-term value: 63 mg/m³, 10 ppm Long-term value: 31 mg/m³, 5 ppm

Skin

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

(Contd. on page 6)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39897 Patch Panel Adhesive

	(Contd. of pag
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	101 °C
Flash point:	10 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapor pressure at 20 °C:	47 hPa
Density at 20 °C:	$1.06 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.1 %
VOC content:	0.1 %
Solids content:	100.0 %
Other information	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39897 Patch Panel Adhesive

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
	56-23-5 carbon tetrachloride		
Oral	LD50	2350 mg/kg (rat)	
Dermal	<i>LD50</i>	5070 mg/kg (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
80-62-6	methyl methacrylate	3	
128-37-0	2,6-di-tert-butyl-p-cresol	3	
56-23-5	carbon tetrachloride	2B	
123-31-9	1,4-dihydroxybenzene	3	
· NTP (National Toxicology Program)			
56-23-5 carbon tetrachloride R			
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- $\cdot$  *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

IISΔ

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39897 Patch Panel Adhesive

(Contd. of page 7)

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

 $\cdot DOT$ 

· Quantity limitations

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1133
UN proper shipping name	
DOT	Adhesives
ADR	1133 Adhesives, special provision 640D
IMDG, IATA	ADHESIVES
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number:	F-E,S-D
Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.

On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

(Contd. on page 9)

SEM

Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39897 Patch Panel Adhesive

	(Contd. of pag
· Remarks	ORM-D 49CFR 173.150,156,306
$\cdot ADR$	
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN1133, Adhesives, special provision 640D, 3, II

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Sara

· Suru
· Section 355 (extremely hazardous substances):

123-31-9 1,4-dihydroxybenzene

### · Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

56-23-5 carbon tetrachloride

123-31-9 1,4-dihydroxybenzene

### · TSCA (Toxic Substances Control Act):

80-62-6 methyl methacrylate

9003-56-9 ACRYLONITRILE/BUTADIENE RESIN

868-77-9 2-hydroxyethyl methacrylate

614-45-9 tert-butyl perbenzoate

79-41-4 methacrylic acid

128-37-0 2,6-di-tert-butyl-p-cresol

56-23-5 carbon tetrachloride

123-31-9 1,4-dihydroxybenzene

· Proposition 65

### · Chemicals known to cause cancer:

9003-56-9 ACRYLONITRILE/BUTADIENE RESIN

56-23-5 carbon tetrachloride

### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)



Trade name: 39897 Patch Panel Adhesive

(Contd. of page 9)

# Cancerogenity categories

· Cancerogenity categories			
· EPA (Environmental Protection Agency)			
80-62-6 methyl methacrylate	E, NL		
56-23-5 carbon tetrachloride	L		
· TLV (Threshold Limit Value established by ACGIH)	· TLV (Threshold Limit Value established by ACGIH)		
80-62-6 methyl methacrylate	A4		
128-37-0 2,6-di-tert-butyl-p-cresol	A4		
56-23-5 carbon tetrachloride	A2		
123-31-9 1,4-dihydroxybenzene	A3		
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
56-23-5 carbon tetrachloride			

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

methyl methacrylate

2-hydroxyethyl methacrylate

ACRYLONITRILE/BUTADIENE RESIN

NEPHELINE SYENITE

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

### · Precautionary statements

P101 *If medical advice is needed, have product container or label at hand.* 

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Use explosion-proof electrical/ventilating/lighting/equipment.* P241

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

P321 P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 11)



Printing date 04/01/2015 Reviewed on 04/01/2015

Trade name: 39897 Patch Panel Adhesive

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/01/2015 / 3
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

\* \* Data compared to the previous version altered.

USA