Printing date 04/01/2015



Reviewed on 04/01/2015

1 Identification

- · Product identifier
- · Trade name: 40502, 40507 QUICK SET 50 Adhesive
- · Article number: 40502, 40507
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives

· Details of the supplier of the safety data sheet · Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

GHS08 Health hazard

Resp. Sens. 1 H334	4 May cause allergy	or asthma symptoms of	r breathing difficulties if inhaled.
--------------------	---------------------	-----------------------	--------------------------------------

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: 4,4'-methylenediphenyl diisocyanate

(Contd. on page 2)

USA

Printing date 04/01/2015

Reviewed on 04/01/2015

S

Trade name: 40502, 40507 QUICK SET 50 Adhesive

	(Contd. of page 1)
methylenediphe	nyl diisocyanate
Polyurethane p	repolymer/ Proprietary
	rol / proprietary
• Hazard stateme	<i>nts</i>
H332 Harmful i	
H315 Causes sk	xin irritation.
H319 Causes se	prious eye irritation.
	e allergy or asthma symptoms or breathing difficulties if inhaled.
	e an allergic skin reaction.
	l of causing cancer.
	e respiratory irritation.
	e damage to organs through prolonged or repeated exposure.
• Precautionary s	
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P284	Wear respiratory protection.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification s	ystem:
· NFPA ratings ((scale 0 - 4)
h h	Iealth = 2
	ire = 1 $eactivity = 0$
	-
· HMIS-ratings ((scale 0 - 4)
	Health = *1 $Fire = 1$

Fire = I**REACTIVITY** O *Reactivity* = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components. Weight percentages

· Dangerous components:

101-68-8 4,4'-methylenediphenyl diisocyanate Polyurethane prepolymer/ Proprietary

30 - 40% (Contd. on page 3)

USA

*

Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

	(Co	ntd. of page 2)
	Alkylated glycerol / proprietary	13 - 30%
	Polyurethane prepolymer / Proprietary	7 - 10%
	Hydroxy terminated poly(oxyalkylated)polyol / proprietary	1.5 - 5%
26447-40-5	methylenediphenyl diisocyanate	1.5 - 5%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • *Special hazards arising from the substance or mixture No further relevant information available.*

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 4)





Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 3)

7 Handling and storage

- · Handling:
- Precautions for safe handling No special measures required. Thorough dedusting.
 Ensure good ventilation/exhaustion at the workplace. Prevent formation of dust.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

- REL Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min
- TLV Long-term value: 0.051 mg/m³, 0.005 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.


Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance:	7 · · · 1
Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	208 °C
Flash point:	94 °C
Flammability (solid, gaseous):	Not determined.
Ignition temperature:	520 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	0.4 Vol %
Upper:	Not determined.
Vapor pressure:	Not applicable.
Density at 20 °C:	1.117 g/cm ³
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Insoluble.

USA



Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

		(Contd. of page
· Partition coefficient (n-octand	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through inhalation.
- Sensitization possible through skin contact.

• Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

101-68-8 4,4'-methylenediphenyl diisocyanate

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

3



SEM

Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- *Persistence and degradability* No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- \cdot **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name	17.1	
· DOT, ADR, ADN, IMDG, IATA	Void	
• Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Void	
· Packing group		
· DOT, ADR, IMDG, IATA	Void	
· Environmental hazards:		
· Marine pollutant:	No	
· Special precautions for user	Not applicable.	



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

(Contd. of page 7)

Page 8/10

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN ''Model Regulation'':

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

_

 \cdot Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

26447-40-5 methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

101-68-8 4,4'-methylenediphenyl diisocyanate

26447-40-5 methylenediphenyl diisocyanate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling:* 4,4'-methylenediphenyl diisocyanate

(Contd. on page 9)

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

	(Contd. of page 8)
methylenedipher	nyl diisocyanate
Polyurethane pr	epolymer/ Proprietary
Alkylated glycer	
• Hazard stateme	nts
H332 Harmful ij	f inhaled.
H315 Causes sk	in irritation.
H319 Causes se	rious eye irritation.
H334 May cause	e allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause	e an allergic skin reaction.
H351 Suspected	of causing cancer.
H335 May cause	e respiratory irritation.
H373 May cause	e damage to organs through prolonged or repeated exposure.
• Precautionary s	tatements
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P284	Wear respiratory protection.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety	assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/01/2015 / 3
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Carc. 2: Carcinogenicity, Hazard Category 2

(Contd. on page 10)

USA



Page 10/10

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 40502, 40507 QUICK SET 50 Adhesive

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 • * Data compared to the previous version altered. (Contd. of page 9)

USA –