



Reviewed on 04/02/2015

1 Identification

- · Product identifier
- · Trade name: 61993 Custom Fill Aerosol
- Article number: 61993
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- Application of the substance / the mixture Coating

Details of the supplier of the safety data sheet
Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

GHS07 Eye Irrit. 2A H319

Causes serious eye irritation. May cause drowsiness or dizziness.

STOT SE 3 H336 M

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: acetone butanone
Hazard statements H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

^{5€ 2)} — USA



Page 2/10

Reviewed on 04/02/2015

Printing date 04/02/2015

Trade name: 61993 Custom Fill Aerosol

	(Contd. of page 1)
P251	Pressurized container: Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear eye protection / face protection.
P305+P	351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P410+P	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classific	ation system:
	tings (scale 0 - 4)
· HMIS-r	Health = 1 Fire = 4 Reactivity = 3 atings (scale 0 - 4)
HEALTH FIRE REACTIV	1 $Health = 1$ 4 $Fire = 4$ Reactivity = 3
• Other ho	uzards
· Results	of PBT and vPvB assessment
• PBT: No	t applicable.
• vPvB: N	ot applicable.
3 Compo	sition/information on ingredients
· Chemico · Descript	l characterization: Mixtures
-	consisting of the following components.
	ercentages
	us components:
67-64-1	
	propane 13 - 30%
	butanone 7 - 10%
/0-75-5	7 - 1070

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

USA

Printing date 04/02/2015

Reviewed on 04/02/2015

(Contd. of page 2)

Trade name: 61993 Custom Fill Aerosol

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures* Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot Methods and material for containment and cleaning up:
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· Handling:

- *Precautions for safe handling* No special measures required. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- · Information about protection against explosions and fires:
 - Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
 Observe official regulations on storing packagings with pressurized containers.
 Information about storage in one common storage facility: Not required.
 Further information about storage conditions: Keep receptacle tightly sealed.
 Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

(Contd. on page 4)

USA

SEM

Printing date 04/02/2015

Trade name: 61993 Custom Fill Aerosol

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

Components with	limit values that	require monitorin	g at the workplace:
1		1	3 1

- **67-64-1 acetone** PEL Long-term value: 2400 mg/m³, 1000 ppm
- REL Long-term value: 590 mg/m³, 250 ppm
- TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV refer to Appendix F

78-93-3 butanone

PELLong-term value: 590 mg/m³, 200 ppmRELShort-term value: 885 mg/m³, 300 ppm

Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm BEI

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)



Reviewed on 04/02/2015

(Contd. of page 3)

Printing date 04/02/2015

Reviewed on 04/02/2015

Trade name: 61993 Custom Fill Aerosol

(Contd. of page 4)

• Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol Color: According to product specification · Odor: *Characteristic* • Odour threshold: Not determined. · pH-value: Not determined. · Change in condition *Melting point/Melting range:* Undetermined. **Boiling point/Boiling range:** -44 °C -97 °C · Flash point: · Flammability (solid, gaseous): Not applicable. 465 °C · Ignition temperature: Not determined. · Decomposition temperature: · Auto igniting: Product is not selfigniting. · Danger of explosion: In use, may form flammable/explosive vapour-air mixture. · Explosion limits: Lower: 1.7 Vol % 13.0 Vol % Upper: • Vapor pressure at 20 °C: 8300 hPa · Density at 20 °C: 0.69578 g/cm3

(Contd. on page 6)

USA

Printing date 04/02/2015

Reviewed on 04/02/2015

Trade name: 61993 Custom Fill Aerosol

		(Contd. of page
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol	/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	35.0 %	
	569.6 g/l / 4.75 lb/gl	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: No irritant effect.

• on the eye: Irritating effect.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant


· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 7)

USA



Reviewed on 04/02/2015

Trade name: 61993 Custom Fill Aerosol

(Contd. of page 6)

- · NTP (National Toxicology Program)
- None of the ingredients is listed.
- · OSHA-Ca (Occupational Safety & Health Administration)
- None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- Danger to drinking water if even extremely small quantities leak into the ground.
- Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1950	
· UN proper shipping name		
$\cdot DOT$	Aerosols, flammable	
· ADR	1950 Aerosols	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	



Printing date 04/02/2015

Reviewed on 04/02/2015

Trade name: 61993 Custom Fill Aerosol

	(Conta. of page
· Transport hazard class(es)	
·DOT	
2	
· Class	2.1
· Label	2.1
· ADR	
· Class	2 5F Gases
· Label	2.1
· IMDG, IATA	
· Class · Label	2.1 2.1
· Packing group	2.1
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
 Special precautions for user EMS Number: 	Warning: Gases
	F-D,S-U
• Transport in bulk according to Annex . MARPOL73/78 and the IBC Code	<i>II of</i> Not applicable.
· Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: 75 kg
· Remarks	On cargo aircraft only: 150 kg ORM-D 49CFR 173-150,156,306
	OMM D 7701 K 175-130,130,300
· ADR · Excepted quantities (EQ)	Code: E0
~~	Not permitted as Excepted Quantity
·IMDG	
· Limited quantities (LQ)	IL Code: F0
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity

(Contd. of page 7)



Printing date 04/02/2015

Reviewed on 04/02/2015

Trade name: 61993 Custom Fill Aerosol

· UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3 butanone

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1 acetone

78-93-3 butanone

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

 Hazard-determining components of labeling: acetone butanone Hazard statements H2220 1220 Extended for the provided fo

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.H319 Causes serious eye irritation.

(Contd. on page 10)

Ι

Ι

A4

(Contd. of page 8)

Printing date 04/02/2015

EN Reviewed on 04/02/2015

Trade name: 61993 Custom Fill Aerosol

	(Conta. of page 9)
H336	May cause drowsiness or dizziness.
Precaution	ary statements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P251	Pressurized container: Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear eye protection / face protection.
P305+P35	1+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P410+P41	<i>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.</i>
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical s	afety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Steve Gaver (sgaver@semproducts.com)

· Date of preparation / last revision 04/02/2015 / 4

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 • * Data compared to the previous version altered.

Page 10/10

(Contd. of maga 0)

USA