

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 6/19/2017

Revision date: 6/10/2022 update 01/13/2023

Supersedes: 9/21/2020

Version: 3.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 2K Epoxy Primer Black
Product code : 3680034 / REZ1225

1.2. Recommended use and restrictions on use

Recommended use : Automotive refinish

1.3. Supplier

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831 - Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
40 University Avenue, Suite 904
Toronto, ON M5J 1T1

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Skin Irrit. 2
Eye Irrit. 2A
Skin Sens. 1
Carc. 2
Repr. 2
STOT SE 3
STOT RE 2
Simple Asphy

2.2. GHS Label elements, including precautionary statements

GHS labeling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|--------------------------------|--|
| Precautionary statements (GHS) | <p>Causes skin irritation May cause an allergic skin reaction Causes serious eye irritation May cause drowsiness or dizziness Suspected of causing cancer Suspected of damaging fertility or the unborn child May cause damage to organs through prolonged or repeated exposure May displace oxygen and cause rapid suffocation</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p> |
|--------------------------------|--|

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Chemical name / Synonyms | Product identifier | % |
|----------------|--|--------------------|---------|
| Dimethyl ether | Dimethyl ether Methane, oxybis- / Methyl ether / Wood ether / Methoxymethane / Methane, 1,1'-oxybis- / DIMETHYL ETHER / Oxybismethane / Dimethyl oxide / Butylene | CAS-No.: 115-10-6 | 30 - 60 |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Name | Chemical name / Synonyms | Product identifier | % |
|-------------------------------------|--|---------------------|---------|
| Acetone | Acetone Dimethyl ketone / 2-Propanone / ACETONE / Propan-2-one / Propanone | CAS-No.: 67-64-1 | 10 - 30 |
| Bisphenol A-epichlorohydrin polymer | Bisphenol A-epichlorohydrin polymer 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane / 4,4'-(1-Methylethylidene)bisphenol polymer with (chloromethyl)oxirane / Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane / Epichlorohydrin-4,4'-isopropylidenediphenol resin / Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane / Epichlorohydrin-bisphenol A resin / 4,4'-Isopropylidenediphenol-epichlorohydrin polymer / Diphenylolpropane-epichlorohydrin resin / Polymer of 4,4'-isopropylidenediphenol and 1-chloro-2,3-epoxypropane / 2,2-Bis(4-hydroxyphenyl)propane-epichlorohydrin copolymer / UP 5-207 / Epoxy adhesive UP 5-207 / Poly(bisphenol A/epichlorohydrin) / Bisphenol A-epichlorohydrin, reaction product / 4,4'-ISOPROPYLIDENEDIPHENOL/EPICHLOROHYDRIN COPOLYMER / Reaction product: bisphenol A, epichlorohydrin epoxy resin / Bisphenol-A-(epichlorohydrin) epoxy resin (reaction product) / Reaction product: bisphenol-A-(epichlorohydrin) and epoxy resin / (Chloromethyl)oxirane, 4,4'-(1-methylethylidene)bisphenol copolymer / Poly[2-(chloromethyl)oxirane-alt-4,4'-(propane-2,2-diyl)diphenol] / Reaction product: bisphenol-A-(epichlorohydrin); epoxy resin (number average molecular weight ≤ 700) / Epichlorohydrin/bisphenol A copolymer / Polymer mainly composed of epichlorohydrin/bisphenol A / Reaction product: bisphenol-A-(epichlorohydrin), epoxy resin | CAS-No.: 25068-38-6 | 5 - 10 |
| Talc | Talc Talc / Magnesium silicate / Talc (containing no asbestos fibers) / Talc (containing no asbestos) / Talc not containing asbestiform fibres / Talc, not containing asbestos / Talc, containing no asbestos fibres / Talc (nonasbestos form) / Talc (non-asbestos form) / Talc, non-fibrous type / Talc, non fibrous / Talc (containing no asbestos fibres) / Non-asbestiform talc / Talc (not containing asbestos) / C.I. 77718 / TALC / Trimagnesium tetrasilicon undecaoxide hydrate / Talc, non-asbestiform / Talc, non-fibrous / Pigment White 26 / Magnesium silicate, hydrous / Talc, not containing mineral fibers (including asbestos) / Asbestiform talc / Talc powder | CAS-No.: 14807-96-6 | 1 – 5 |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Name | Chemical name / Synonyms | Product identifier | % |
|--|---|---------------------|-----------|
| Xylenes (o-, m-, p- isomers) | Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene | CAS-No.: 1330-20-7 | 1 – 5 |
| 1-Butanol | 1-Butanol n-Butyl alcohol / n-Butanol / Butanol, 1- / 1-Butyl alcohol / Butyl alcohol, n- / 1-Hydroxybutane / Butan-1-ol / Butanol, n- / N-BUTYL ALCOHOL / Normal butyl alcohol / Butyl alcohol / Butanol | CAS-No.: 71-36-3 | 1 - 5 |
| Methyl isoamyl ketone | Methyl isoamyl ketone Hexan-2-one, 5-methyl- / 2-Hexanone, 5-methyl- / Isoamyl methyl ketone / Isopentyl methyl ketone / 5-Methyl-2-hexanone / 5-Methylhexan-2-one / Methyl-2-hexanone, 5- | CAS-No.: 110-12-3 | 1 - 5 |
| Solvent naphtha, petroleum, heavy aromatic | Solvent naphtha, petroleum, heavy aromatic Naphtha (petroleum), heavy aromatic / Heavy aromatic naphtha / Solvent naphtha (petroleum), heavy aromatic / Heavy aromatic solvent naphtha / Aromatic 150 / Solvent naphtha (petroleum) heavy aromatic / Heavy aromatic solvent naphtha (petroleum) / Solvent naphtha, petroleum, heavy aromatic (A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 165-290°C.) / Solvent naphtha / Hydrocarbons, C10-13, aromatics, >1% naphthalene / Solvent naphtha (petroleum), heavy aromatic; Kerosine - unspecified [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165°C to 290°C (330°F to 554°F).] | CAS-No.: 64742-94-5 | 1 – 5 |
| Ethylbenzene | Ethylbenzene Benzene, ethyl- / Phenylethane / ETHYLBENZENE | CAS-No.: 100-41-4 | 0.5 - 1.5 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|---------------------------------------|--|
| First-aid measures after skin contact | : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. |

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|--|
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Chronic symptoms | : Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. |

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Water spray. Dry powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | : Do not use water jet. |

5.2. Specific hazards arising from the chemical

| | |
|------------------|---|
| Fire hazard | : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. |
| Explosion hazard | : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. vapors may form explosive mixture with air. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|---|
| Firefighting instructions | : DO NOT fight fire when fire reaches explosives. Evacuate area. |
| Protection during firefighting | : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|---|
| General measures | : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges. |
|------------------|---|

6.1.1. For non-emergency personnel

No additional information available

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store locked up. Store in a well-ventilated place. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| 2K Epoxy Primer Black | |
|--|--|
| No additional information available | |
| Dimethyl ether (115-10-6) | |
| No additional information available | |
| Acetone (67-64-1) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 250 ppm |
| ACGIH OEL STEL [ppm] | 500 ppm |
| ACGIH chemical category | Not Classifiable as a Human Carcinogen |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Acetone (67-64-1) | |
|---|---|
| USA - ACGIH - Biological Exposure Indices | |
| BEI (BLV) | 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific) |
| USA - IDLH - Occupational Exposure Limits | |
| IDLH [ppm] | 2500 ppm (10% LEL) |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 590 mg/m ³ |
| NIOSH REL TWA [ppm] | 250 ppm |
| Bisphenol A-epichlorohydrin polymer (25068-38-6) | |
| No additional information available | |
| 1-Butanol (71-36-3) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 20 ppm |
| USA - IDLH - Occupational Exposure Limits | |
| IDLH [ppm] | 1400 ppm (10% LEL) |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (Ceiling) | 150 mg/m ³ |
| NIOSH REL C [ppm] | 50 ppm |
| US-NIOSH chemical category | Potential for dermal absorption |
| Methyl isoamyl ketone (110-12-3) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 20 ppm |
| ACGIH OEL STEL [ppm] | 50 ppm |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 240 mg/m ³ |
| NIOSH REL TWA [ppm] | 50 ppm |
| Ethylbenzene (100-41-4) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH chemical category | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| USA - ACGIH - Biological Exposure Indices | |
| BEI (BLV) | 0.15 g/g Kreatinin Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific) |
| USA - IDLH - Occupational Exposure Limits | |
| IDLH [ppm] | 800 ppm (10% LEL) |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 435 mg/m ³ |
| NIOSH REL TWA [ppm] | 100 ppm |
| NIOSH REL (STEL) | 545 mg/m ³ |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Ethylbenzene (100-41-4) | |
|--|---|
| NIOSH REL STEL [ppm] | 125 ppm |
| Talc (14807-96-6) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) |
| ACGIH chemical category | Not Classifiable as a Human Carcinogen containing no asbestos fibers |
| USA - IDLH - Occupational Exposure Limits | |
| IDLH | 1000 mg/m ³ (containing no asbestos and <1% quartz) |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust) |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 100 ppm |
| ACGIH OEL STEL [ppm] | 150 ppm |
| ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA - ACGIH - Biological Exposure Indices | |
| BEI (BLV) | 1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift |
| Solvent naphtha, petroleum, heavy aromatic (64742-94-5) | |
| No additional information available | |

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

| |
|--|
| Hand protection: |
| Wear suitable gloves resistant to chemical penetration |
| Eye protection: |
| Wear eye/face protection |
| Skin and body protection: |
| Wear suitable protective clothing |
| Respiratory protection: |
| In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------------|
| Physical state | : Liquid |
| Appearance | : Aerosol. |
| Color | : Black |
| Odor | : Characteristic |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : Not applicable |
| Flash point | : < -18 °C (-0.4 °F) |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability | : Extremely flammable aerosol. |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 0.955 |
| Solubility | : No data available |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

| | |
|------------------|---------------------|
| Gas group | : Press. Gas (Liq.) |
| Flame projection | : >75 cm < 100 cm |
| Flackback | : Possible |

: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| Dimethyl ether (115-10-6) | |
|---|---|
| LC50 inhalation rat | 164000 ppm/4h |
| ATE CA (Gases (except aerosol dispensers and lighters)) | 164000 ppmV/4h |
| Acetone (67-64-1) | |
| LD50 oral rat | 5800 mg/kg body weight Animal: rat, Animal sex: female |
| LD50 dermal rabbit | > 15700 mg/kg |
| LC50 inhalation rat | 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4 |
| ATE CA (oral) | 5800 mg/kg body weight |
| Bisphenol A-epichlorohydrin polymer (25068-38-6) | |
| LD50 oral rat | 11400 mg/kg |
| LD50 dermal rat | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)) |
| LD50 dermal rabbit | 20 ml/kg (Toxnet) |
| ATE CA (oral) | 11400 mg/kg body weight |
| ATE CA (Dermal) | 23200 mg/kg body weight |
| 1-Butanol (71-36-3) | |
| LD50 oral rat | 700 mg/kg |
| LD50 dermal rabbit | 3402 mg/kg |
| LC50 inhalation rat | > 8000 ppm/4h |
| ATE CA (oral) | 700 mg/kg body weight |
| ATE CA (Dermal) | 3400 mg/kg body weight |
| Methyl isoamyl ketone (110-12-3) | |
| LD50 oral rat | > 3200 mg/kg |
| LD50 dermal rabbit | 10 ml/kg |
| LC50 inhalation rat | 17.8 mg/l (Exposure time: 6 h) |
| ATE CA (Dermal) | 10000 mg/kg body weight |
| ATE CA (Gases (except aerosol dispensers and lighters)) | 4500 ppmV/4h |
| ATE CA (vapors) | 17.8 mg/l/4h |
| ATE CA (dust,mist) | 1.5 mg/l/4h |
| Ethylbenzene (100-41-4) | |
| LD50 oral rat | 3500 mg/kg |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Ethylbenzene (100-41-4) | |
|--|--|
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat | 17.4 mg/l/4h |
| ATE CA (oral) | 3500 mg/kg body weight |
| ATE CA (Dermal) | 15400 mg/kg body weight |
| ATE CA (Gases (except aerosol dispensers and lighters)) | 4500 ppmV/4h |
| ATE CA (vapors) | 17.4 mg/l/4h |
| ATE CA (dust,mist) | 1.5 mg/l/4h |
| Talc (14807-96-6) | |
| LD50 oral rat | > 5000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method) |
| LD50 dermal rat | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 inhalation rat | > 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity) |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rat | 1100 mg/kg |
| ATE CA (oral) | 3500 mg/kg body weight |
| ATE CA (Dermal) | 1100 mg/kg body weight |
| ATE CA (Gases (except aerosol dispensers and lighters)) | 4500 ppmV/4h |
| ATE CA (vapors) | 11 mg/l/4h |
| ATE CA (dust,mist) | 1.5 mg/l/4h |
| Solvent naphtha, petroleum, heavy aromatic (64742-94-5) | |
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rat | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: other:EPA Fed Reg Vol 50, No. 188 1985 and as amended in Fed Reg Vol 52, No. 97, 1987 |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | > 590 mg/m ³ (Exposure time: 4 h) |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Suspected of causing cancer. |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Bisphenol A-epichlorohydrin polymer (25068-38-6) | |
|--|--|
| NOAEL (chronic,oral,animal/male,2 years) | 15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information) |
| NOAEL (chronic,oral,animal/female,2 years) | 100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information) |
| Ethylbenzene (100-41-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |
| Talc (14807-96-6) | |
| IARC group | 3 - Not classifiable |
| National Toxicology Program (NTP) Status | Evidence of Carcinogenicity |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| IARC group | 3 - Not classifiable |
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| Acetone (67-64-1) | |
| LOAEL (animal/female, F0/P) | 11298 mg/kg body weight Animal: mouse, Animal sex: female |
| NOAEL (animal/male, F0/P) | 900 mg/kg body weight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information) |
| Solvent naphtha, petroleum, heavy aromatic (64742-94-5) | |
| NOAEL (animal/male, F0/P) | 35 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test |
| NOAEL (animal/female, F0/P) | 125 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test |
| STOT-single exposure | : May cause drowsiness or dizziness. |
| Acetone (67-64-1) | |
| STOT-single exposure | May cause drowsiness or dizziness. |
| 1-Butanol (71-36-3) | |
| STOT-single exposure | May cause drowsiness or dizziness. May cause respiratory irritation. |
| Methyl isoamyl ketone (110-12-3) | |
| STOT-single exposure | May cause drowsiness or dizziness. |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

: May cause damage to organs through prolonged or repeated exposure.

STOT-repeated exposure

| 1-Butanol (71-36-3) | |
|----------------------------|-----------------------------------|
| LOAEL (oral, rat, 90 days) | 500 mg/kg body weight Animal: rat |
| NOAEL (oral, rat, 90 days) | 125 mg/kg body weight Animal: rat |

| Ethylbenzene (100-41-4) | |
|--------------------------------|---|
| NOAEL (oral, rat, 90 days) | 75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

| Talc (14807-96-6) | |
|----------------------------|---|
| NOAEL (oral, rat, 90 days) | 100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies) |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|--|
| LOAEL (oral, rat, 90 days) | 150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |

| Solvent naphtha, petroleum, heavy aromatic (64742-94-5) | |
|--|---|
| LOAEL (oral, rat, 90 days) | 1250 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| LOAEC (inhalation, rat, vapor, 90 days) | 4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study) |
| NOAEL (oral, rat, 90 days) | 625 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| NOAEL (dermal, rat/rabbit, 90 days) | 2000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| NOAEC (inhalation, rat, vapor, 90 days) | 2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study) |

Aspiration hazard : Not classified

| 2K Epoxy Primer Black | |
|------------------------------|---------|
| Vaporizer | Aerosol |

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

| Dimethyl ether (115-10-6) | |
|---|---|
| LC50 - Fish [1] | > 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static]) |
| EC50 - Crustacea [1] | > 4.4 g/l Test organisms (species): Daphnia magna |
| Acetone (67-64-1) | |
| LC50 - Fish [1] | 4.74 – 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 - Crustacea [1] | 10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 - Fish [2] | 6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 - Crustacea [2] | 12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LOEC (chronic) | > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | ≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| Bisphenol A-epichlorohydrin polymer (25068-38-6) | |
| LC50 - Fish [1] | 1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | ≈ 2 mg/l Test organisms (species): Daphnia magna |
| LOEC (chronic) | 1 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| 1-Butanol (71-36-3) | |
| LC50 - Fish [1] | 1730 – 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 - Crustacea [1] | 1983 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 - Fish [2] | 1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 - Crustacea [2] | 1897 – 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| NOEC (chronic) | 4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic crustacea | 4.1 mg/l |
| Methyl isoamyl ketone (110-12-3) | |
| LC50 - Fish [1] | 159 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| Ethylbenzene (100-41-4) | |
| LC50 - Fish [1] | 11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 - Crustacea [1] | 1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 - Fish [2] | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
| LOEC (chronic) | 1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d' |
| NOEC (chronic) | 0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d' |
| NOEC chronic crustacea | 0.956 mg/l |
| Talc (14807-96-6) | |
| LC50 - Fish [1] | > 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static]) |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Talc (14807-96-6) | |
|--|--|
| LC50 - Fish [2] | 110000 mg/l Test organisms (species): other: |
| NOEC (chronic) | 1459798 mg/l Test organisms (species): other: Duration: '30 d' |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| LC50 - Fish [1] | 2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| LC50 - Fish [2] | 2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 - Crustacea [2] | 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris) |
| LOEC (chronic) | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |
| Solvent naphtha, petroleum, heavy aromatic (64742-94-5) | |
| LC50 - Fish [1] | 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 - Crustacea [1] | 0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 - Fish [2] | 2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 - Crustacea [2] | 0.76 mg/l Test organisms (species): Daphnia magna |
| 12.2. Persistence and degradability | |
| 2K Epoxy Primer Black | |
| Persistence and degradability | Not established. |
| 12.3. Bioaccumulative potential | |
| 2K Epoxy Primer Black | |
| Bioaccumulative potential | Not established. |
| Dimethyl ether (115-10-6) | |
| Partition coefficient n-octanol/water | -0.18 |
| Acetone (67-64-1) | |
| BCF - Fish [1] | 0.69 |
| Partition coefficient n-octanol/water | -0.24 |
| 1-Butanol (71-36-3) | |
| BCF - Fish [1] | 0.64 |
| Partition coefficient n-octanol/water | 0.785 (at 25 °C) |
| Methyl isoamyl ketone (110-12-3) | |
| Partition coefficient n-octanol/water | 1.88 |
| Ethylbenzene (100-41-4) | |
| BCF - Fish [1] | 15 |
| Partition coefficient n-octanol/water | 3.2 |

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Talc (14807-96-6) | |
|---|----------------------------|
| BCF - Fish [1] | (no known bioaccumulation) |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| BCF - Fish [1] | 0.6 – 15 |
| Partition coefficient n-octanol/water | 2.77 – 3.15 |
| Solvent naphtha, petroleum, heavy aromatic (64742-94-5) | |
| BCF - Fish [1] | 61 – 159 |
| Partition coefficient n-octanol/water | 2.9 – 6.1 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1950

UN-No. (TDG) : UN1950

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : LTD QTY

Hazard labels (DOT) : LTD QTY




2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

TDG

Transport hazard class(es) (TDG) : 2.1
Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

UN-No.(DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L
Emergency Response Guide (ERG) Number : 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date : 06/19/2017
Revision date : 06/10/2022
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



| Full text of H-phrases | |
|------------------------|--|
| Carc. 2 | Carcinogenicity Category 2 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Aerosol 1 | Flammable aerosol Category 1 |
| Press. Gas (Liq.) | Gases under pressure Liquefied gas |
| Repr. 2 | Reproductive toxicity Category 2 |
| Simple Asphy | Simple Asphyxiant |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| Skin Sens. 1 | Skin sensitization, Category 1 |
| STOT RE 2 | Specific target organ toxicity (repeated exposure) Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |

| |
|--------------------------------|
| Indication of changes: |
| SDS Update. GHS classification |

SDS HazCom 2012 - WHMIS 2015 (NexReg)

2K Epoxy Primer Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.