

# Technical Data Sheet



The United States of America:  
by Peter Kwasny Inc.  
62-64 Enter Lane  
Islandia, NY 11749

Distributed in

Canada:  
Peter Kwasny Spraypaint Canada Inc.  
40 University Avenue, Suite 904  
Toronto, ON. M5J 1T1

Toll free North America  
Phone: 1-844-426-6330 / Fax: 1-866-226-6434  
order@kwasny.us / service@kwasny.us  
www.spraymax.com

## **SprayMax®** **1K Gun Cleaner** **299 g NET WT. 10.6 oz** **Art. Nr. 3680095**



### **Product**

#### **Description / Purpose**

Rich in active cleaning solvents for the thorough cleaning of the variator nozzle of conventional spray guns. Universal for 1K solvent and 1K water-based paints, as well as for non cured 2K paints can be used. The short and long lancet allow residue-free cleaning the spray gun without disassembling it to have to.

#### **Properties**

- Cleans spray guns that are soiled with both solvent-based or water-based paints
- Fast cleaning completely free of residues thanks to the solvent power
- Optionally with a short or long nozzle
- Spray gun can be cleaned overhead without being dismantled
- Cleans the Variator nozzle
- Improved cleaning effect thanks to spray can pressure
- Dosed distribution

#### **Material base**

Special solvent combination

#### **Colour**

Transparent

<b>EPA Coating Category</b>	n.a.
<b>CARB Aerosol Rule Coating Category</b> (01/2017)	n.a.


## Processing

### Protection measures




Wear personal protection equipment.  
(respiratory mask / gloves / goggles)  
For more information, see safety data sheet.

### Spraying distance



6 - 8 inches / 15 - 20 cm

### Processing conditions



1. After you finished your paint job spray your spraying gun thoroughly empty
2. Remove the paint cup and nozzle head.
3. Not later than 2 h after you have finalized your paint work rinse the inner part of your spray gun as well as the nozzle head using the lancet on the spray head of the aerosol.
4. Drain the spray gun
5. Reassemble your spray gun and dry it with compressed air.


## Additional Information

### Important Information



Avoid bumps, friction and impact.

### Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 60° F - 77° F / 15 - 25° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

For professional use only.  
Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.