Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Issue date: 10/9/2019 Revision date: 3/22/2022 update 01/13/2023 Supersedes: 3/26/2021 Version: 2.1

SECTION 1: Identification	
1.1. Identification	
Product form Product name Product code	: Mixture : Surface Control Spray : 3680225 / REZ1134
1.2. Recommended use and restrictio	ns on use
Use of the substance/mixture	: Automotive refinish
1.3. Supplier	
Manufacturer Peter Kwasny GmbH 96 Heibronner Str. Gundelsheim, 74831 - Germany T 49(0) 6269-95-20	Distributor Peter Kwasny Inc. 62-64 Enter Lane Islandia, NY 11749 T 1-844-726-6330 (tollfree North America) Distributor Peter Kwasny Spraypaint Canada Inc 40 University Avenue, Suite 904 Toronto, ON M5J 1T1
1.4. Emergency telephone number	
Emergency number	: 352-323-3500 (24h / 7 days a week)
SECTION 2: Hazard(s) identification 2.1. Classification of the substance of GHS classification Flam. Aerosol 1 Press. Gas (Liq.) Skin Irrit. 2 STOT SE 3 Asp. Tox. 1 2.2. GHS Label elements, including pro-	' mixture
GHS labelling	ecautional y statements
Hazard pictograms (GHS)	
Signal word (GHS)	: Danger
Hazard statements (GHS)	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.
Precautionary statements (GHS)	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Do not spray on an open flame or other ignition source.
03/22/2022	EN (English) Page 1

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Hydrocarbons, C9-10, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 1174921-73-3	45 - 70
n-Butane	n-Butane Butane / BUTANE	CAS-No.: 106-97-8	10 – 30
C8-9 Isoparaffin	C8-9 Isoparaffin Alkanes, iso-, C8-9 / C8-9 ISOPARAFFIN / Hydrocarbons, C8-9, isoalkanes	CAS-No.: 246538-71-6	10 - 30
Propane	Propane Normal propane / PROPANE / n-Propane / R290	CAS-No.: 74-98-6	7 - 13

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29	1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Not expected to be a primary route of exposure. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects	(acute and delayed)
Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	 May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguish	ing media
Suitable extinguishing media Unsuitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. : Do not use water jet.
5.2. Specific hazards arising from the ch	emical
Fire hazard Explosion hazard	 Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. irritating vapours. Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket.
5.3. Special protective equipment and pr	recautions for fire-fighters
Firefighting instructions	In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
Other information	 Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back.

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equi	pment and emergency procedures	
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges. Isolate from fire, if possible, without unnecessary risk.	
6.1.1. For non-emergency personnel		

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.2. For emergency responders No additional information available		
6.2. Environmental precautions		
Prevent entry to sewers and public waters.		
6.3. Methods and material for containment and cleaning up		
For containment	: Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.	
Methods for cleaning up	: Provide ventilation. Sweep or shovel spills into appropriate container for disposal.	
6.4. Reference to other sections		

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling	 Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only non-sparking tools. Take precautionary measures against static discharge. Do not spray on an open flame or other ignition source.
Hygiene measures	: Take off contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.
7.2. Conditions for safe storage, includin	g any incompatibilities
Technical measures Storage conditions	 Proper grounding procedures to avoid static electricity should be followed. Store locked up. Keep out of the reach of children. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Protect from sunlight. Protect containers from physical damage. Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection		
8.1. Control parameters		
Surface Control Spray		
No additional information available		
n-Butane (106-97-8)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers)	
USA - IDLH - Occupational Exposure Limits		
IDLH [ppm]	1600 ppm (>10% LEL)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	1900 mg/m ³	
NIOSH REL TWA [ppm]	800 ppm	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Propane (74-98-6)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Propane	
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant	
ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content	
Regulatory reference	ACGIH 2020	
USA - OSHA - Occupational Exposure Limits		
Local name	Propane	
OSHA PEL TWA [1]	1800 mg/m³	
OSHA PEL TWA [2]	1000 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
USA - IDLH - Occupational Exposure Limits		
IDLH [ppm]	2100 ppm (10% LEL)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	1800 mg/m³	
NIOSH REL TWA [ppm]	1000 ppm	
Hydrocarbons, C9-10, n-alkanes, isoalkanes,	cyclics, aromatics (2-25%) (1174921-73-3)	
No additional information available		
C8-9 Isoparaffin (246538-71-6)		
No additional information available		
8.2. Appropriate engineering controls		
	Provide readily accessible eye wash stations and safety showers. Ensure good ventilation of the	
	work station.	
Environmental exposure controls :	Avoid release to the environment.	
8.3. Individual protection measures/Personal	protective equipment	
Hand protection:		
Wear suitable gloves resistant to chemical penetration		
Eye protection:		
Safety glasses or goggles are recommended when using product.		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.		
Other information:		

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Colourless
Odour	: Characteristic
Odour threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: Not applicable
Flash point	: <-18 °C (<-0.4 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

Gas group	: Press. Gas (Liq.)
Flame projection length	: >75cm <100cm
Flashback	: Possible

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sparks. Open flame. Direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents. Acids. Alkali.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	 Not classified. Not classified. Not classified.
n-Butane (106-97-8)	
LC50 inhalation rat	658 g/m³ (Exposure time: 4 h)
ATE CA (vapours)	658 mg/l/4h
ATE CA (dust,mist)	658 mg/l/4h
Propane (74-98-6)	
LC50 inhalation rat	> 800000 ppm (Exposure time: 15 min)
Hydrocarbons, C9-10, n-alkanes, isoalkanes	s, cyclics, aromatics (2-25%) (1174921-73-3)
LD50 oral rat	> 5000 mg/kg (OECD TG 401)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg (OECD TG 402)
C8-9 Isoparaffin (246538-71-6)	
LD50 oral rat	7100 – 7800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	2200 – 2500 mg/kg
LC50 inhalation rat	> 9.4 mg/l/4h
ATE CA (oral)	7100 mg/kg bodyweight
ATE CA (Dermal)	2200 mg/kg bodyweight
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity	 Causes skin irritation. Not classified. Not classified. Not classified. Not classified. Not classified.
Carcinogenicity Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbons, C9-10, n-alkanes, isoalkanes	s, cyclics, aromatics (2-25%) (1174921-73-3)
STOT-single exposure	May cause drowsiness or dizziness.
C8-9 Isoparaffin (246538-71-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
C8-9 Isoparaffin (246538-71-6)	
NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90- Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Surface Control Spray	
Vaporizer	Aerosol
20/02/0202	

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	 May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
C8-9 Isoparaffin (246538-71-6)	
LC50 - Fish [1]	0.11 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	0.4 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
12.2. Persistence and degradability	
Surface Control Spray	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Surface Control Spray	
Bioaccumulative potential	Not established.
n-Butane (106-97-8)	
Partition coefficient n-octanol/water	2.89
Propane (74-98-6)	
Partition coefficient n-octanol/water	2.3
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Other information	: No other effects known.

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use. Flammable vapours may accumulate in the container. Hazardous waste due to potential risk of
	explosion.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 14: Transport information	
In accordance with DOT / TDG	
14.1. UN number	
DOT NA No UN-No. (TDG)	: UN1950 : UN1950
14.2. UN proper shipping name	
Proper Shipping Name (DOT/TDG)	: Aerosols
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 2.1 : 2.1
TDG Transport hazard class(es) (TDG) Hazard labels (TDG)	: 2.1 : 2.1
14.4. Packing group	
Packing group (DOT) Packing group (TDG)	Not applicableNot applicable
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
DOT UN-No.(DOT) DOT Special Provisions (49 CFR 172.102) DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) DOT Vessel Stowage Location DOT Vessel Stowage Other	 UN1950 N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols. 306 None None 75 kg 150 kg A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except
-	Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

TDG	
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General
	Provisions and Special Cases), a person must not offer for transport or transport these
	dangerous goods unless they are in a means of containment that is in compliance with the
	requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These
	Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions
	and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport
	or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain
	dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a
	railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a
	capacity less than or equal to 50 mL.
	(2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger	: 75 L
Carrying Railway Vehicle Index	
Emergency Response Guide (ERG) Number	: 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Revision date : 03/22/2022 Other information : None. Prepared by : Nexreg Compliance Inc. www.Nexreg.com

Full text of H-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Aerosol 1	Flammable aerosols, Category 1
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3 Specific target organ toxicity — Single exposure, Category 3, Narcosis	
Indication of c	hanges:

SDS update.

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.