

# SAFETY DATA SHEET.

Issuing date 14-May-2015

Revision Date 10-Jun-2015

Version 2

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product name** TEX COAT CHIPGUARD WHITE  
**Product code** 4303

**Product Type**

Extremely flammable aerosol

**Synonyms**

None

**Supplier's details**

**Recommended Use**

Chip guard. For Professional and Industrial Use Only.

**Uses advised against**

Not for sale to the general public.

**Manufacture/Supplier:**

Transtar Autobody Technologies  
2040 Heiserman Drive  
Brighton, MI 48116  
800-824-2843

**Emergency telephone number**

**Chemical Emergency Phone Number**

CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

**Company Emergency Phone Number**

1-800-424-9300 (NORTH AMERICA)  
800-824-2843

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Causes skin irritation  
 Causes serious eye irritation  
 May cause cancer  
 May damage fertility or the unborn child  
 May cause drowsiness or dizziness  
 May cause damage to organs (Central Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, and Skin) through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways  
 Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated



**Appearance** opaque

**Physical state** Aerosol

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

#### Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention  
 Specific treatment (see first aid on this label)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.  
 Take off contaminated clothing and wash before reuse  
 If skin irritation occurs: Get medical advice/attention  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

#### Precautionary Statements - Storage

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None

#### Other information

• Toxic to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
DIMETHYLETHER	115-10-6	20-30
METHYL ETHYL KETONE	78-93-3	20-30
CALCIUM CARBONATE	1317-65-3	10-20
TOLUENE	108-88-3	10-20
BUTYL BENZYL PHTHALATE	85-68-7	1-10
TITANIUM DIOXIDE	13463-67-7	1-10
BUTYL ACETATE	123-86-4	1-10
SILICA, CRYSTALLINE	14808-60-7	0.1-1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### First aid measures for different exposure routes

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.

**Ingestion** Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately.

**Most important symptoms/effects, acute and delayed**

**Main Symptoms** Causes skin and eye irritation. Irritating to respiratory system. May cause drowsiness or dizziness. May damage to fertility or the unborn child. May cause cancer. Harmful or fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Water fog. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

**Specific hazards arising from the chemical**

Extremely flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Risk of ignition.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** none.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with water. Remove all sources of ignition. Avoid contact with the skin and the eyes. Evacuate personnel to be safe areas. Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cans. Wear protective gloves/clothing and eye/face protection.

**Environmental precautions**

**Environmental precautions** Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Advice on safe handling** Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges.

**Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, or oxidizing agents.

**Aerosol Level** 2

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ETHYL KETONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m <sup>3</sup> (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
BUTYL ACETATE 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
SILICA, CRYSTALLINE 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	(vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (30)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (250)/( %SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls**

**Engineering Measures**                      Showers  
 Eyewash stations  
 Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**                      Safety glasses with side-shields.

**Skin and body protection**                Chemical resistant apron. Protective gloves.

**Respiratory protection**                    If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**                            Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical and chemical properties**

<b>Physical state</b>	Aerosol	<b>Odor</b>	Solvent
<b>Appearance</b>	opaque	<b>Odor Threshold</b>	No information available
<b>Color</b>	white		

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
<b>pH</b>	0	
<b>Melting/freezing point</b>	No information available	
<b>Boiling point/boiling range</b>	No information available	
<b>Flash Point</b>	-41.1 °C / -42 °F	Based on propellant
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limits in Air</b>		
<b>upper flammability limit</b>	No information available	
<b>lower flammability limit</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	No information available	
<b>Specific Gravity</b>	1.017	
<b>Water solubility</b>	Practically insoluble	
<b>Partition coefficient: n-octanol/water</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	

**Other information**

<b>VOC Content(%)</b>	59.1
<b>MIR Value</b>	1.14

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Strong acids, alkalis, or oxidizing agents.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.
<b>Eye contact</b>	Irritating to eyes. Avoid contact with eyes.
<b>Skin contact</b>	Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.
<b>Ingestion</b>	May be harmful or fatal if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIMETHYLETHER 115-10-6	-	-	= 308.5 mg/L ( Rat ) 4 h
METHYL ETHYL KETONE 78-93-3	= 2483 mg/kg ( Rat )	= 5000 mg/kg ( Rabbit )	= 11700 ppm ( Rat ) 4 h
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
BUTYL BENZYL PHTHALATE 85-68-7	= 2330 mg/kg ( Rat )	= 6700 mg/kg ( Rat )	> 6.7 mg/L ( Rat ) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg ( Rat )	-	-
BUTYL ACETATE 123-86-4	= 14000 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
SILICA, CRYSTALLINE 14808-60-7	= 500 mg/kg ( Rat )	-	-

**Information on toxicological effects**

<b>Symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting. Causes skin and eye irritation. May cause respiratory system irritation. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.
-----------------	--

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Irritating to skin.
<b>Eye damage/irritation</b>	Irritating to eyes.
<b>Irritation</b>	Irritating to eyes, respiratory system and skin.
<b>Sensitization</b>	None known.
<b>Germ Cell Mutagenicity</b>	None known.
<b>Carcinogenicity</b>	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-

BUTYL BENZYL PHTHALATE 85-68-7	-	Group 3	-	-
TITANIUM DIOXIDE 13463-67-7	-	2B	-	-
SILICA, CRYSTALLINE 14808-60-7	A2	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

<b>Reproductive toxicity</b>	Product is or contains a chemical which is a known or suspected reproductive hazard.
<b>Specific target organ systemic toxicity (single exposure)</b>	May cause respiratory irritation. May cause drowsiness and dizziness.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Chronic toxicity</b>	May cause adverse liver effects.
<b>Target Organ Effects</b>	Central nervous system, Eyes, Kidney, Liver, Lungs, Respiratory system, Skin.
<b>Neurological effects</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.

#### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	24746 mg/kg
<b>ATEmix (dermal)</b>	13350 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	33.9 mg/l
<b>ATEmix (inhalation-vapor)</b>	34654 mg/l

## 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
METHYL ETHYL KETONE 78-93-3	-	3130 - 3320 mg/L LC50 Pimephales promelas 96h flow-through	-	4025 - 6440 mg/L EC50 Daphnia magna 48h Static 5091 mg/L EC50 Daphnia magna 48h 520 mg/L EC50 Daphnia magna 48h

TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static 12.6 mg/L LC50 Pimephales promelas 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 54 mg/L LC50 Oryzias latipes 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
BUTYL BENZYL PHTHALATE 85-68-7	0.02 - 0.25 mg/L EC50 Pseudokirchneriella subcapitata 96h 0.2 - 28.2 mg/L EC50 Pseudokirchneriella subcapitata 72h	1.0 - 10.0 mg/L LC50 Lepomis macrochirus 96h static 1.0 - 10.0 mg/L LC50 Oncorhynchus mykiss 96h static 1.39 - 3.88 mg/L LC50 Pimephales promelas 96h flow-through 0.82 mg/L LC50 Oncorhynchus mykiss 96h flow-through 0.78 mg/L LC50 Pimephales promelas 96h static	-	0.9 - 1.1 mg/L EC50 Daphnia magna 48h Static 0.97 mg/L EC50 Daphnia magna 48h 1.28 mg/L EC50 Daphnia magna 48h semi-static 0.76 mg/L EC50 Daphnia magna 48h Flow through
BUTYL ACETATE 123-86-4	674.7 mg/L EC50 Desmodesmus subspicatus 72h	17 - 19 mg/L LC50 Pimephales promelas 96h flow-through 100 mg/L LC50 Lepomis macrochirus 96h static	-	-

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	log Pow
DIMETHYLETHER 115-10-6	-0.18
METHYL ETHYL KETONE 78-93-3	0.29
TOLUENE 108-88-3	2.65
BUTYL BENZYL PHTHALATE 85-68-7	4.91
BUTYL ACETATE 123-86-4	1.81

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging**

Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

<b>DOT Ground</b>	CONSUMER COMMODITY ORM-D or LIMITED QUANTITY
<b>IATA</b>	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.
<b>IMDG</b>	UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
DIMETHYLETHER	X	X	X	X	X	X	X	X
METHYL ETHYL KETONE	X	X	X	X	X	X	X	X
CALCIUM CARBONATE	X	X	X	X	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
BUTYL BENZYL PHTHALATE	X	X	X	X	X	X	X	X
TITANIUM DIOXIDE	X	X	X	X	X	X	X	X
BUTYL ACETATE	X	X	X	X	X	X	X	X
SILICA, CRYSTALLINE	X	X	X	X	X	X	X	X

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

#### U.S. Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	10-20	1.0

##### SARA 311/312 Hazard Categories

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes

**Sudden Release of Pressure Hazard  
Reactive Hazard**Yes  
no**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
BUTYL BENZYL PHTHALATE 85-68-7		X	X	
BUTYL ACETATE 123-86-4	5000 lb			X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
METHYL ETHYL KETONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
BUTYL BENZYL PHTHALATE 85-68-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental Female Reproductive
BUTYL BENZYL PHTHALATE - 85-68-7	Developmental
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
SILICA, CRYSTALLINE - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
DIMETHYLETHER 115-10-6	X	X	X
METHYL ETHYL KETONE 78-93-3	X	X	X
CALCIUM CARBONATE 1317-65-3	X	X	X
TOLUENE 108-88-3	X	X	X
BUTYL BENZYL PHTHALATE 85-68-7	X	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X
BUTYL ACETATE 123-86-4	X	X	X
SILICA, CRYSTALLINE 14808-60-7	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazard 2</b>	<b>Flammability 4</b>	<b>Instability 0</b>	<b>Physical and chemical hazards -</b>
<b>HMIS</b>	<b>Health Hazard 2*</b>	<b>Flammability 4</b>	<b>Physical Hazard 1</b>	<b>Personal protection B</b>
<i>Chronic Hazard Star Legend</i>		<i>Chronic Health Hazard Repeated or prolonged exposure may cause central nervous system damage</i>		

**Prepared By** Transtar Autobody Technologies  
**Issuing date** 14-May-2015  
**Revision Date** 10-Jun-2015

**Revision Note**  
 No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**