

# TECHNICAL DATA SHEET – SUPER CHARGER™

PRODUCT: SUPER CHARGER™ Resin Additive  
TECHNICAL CALLS: 1-800-321-0672



## DESCRIPTION:

SUPER CHARGER™ Resin Additive is formulated with premium resins to bring fillers and polyester putties back to life by reviving and thinning without compromising performance. Reduced viscosity provides for improved spreading, featheredging and sanding. SUPER CHARGER is best used in applications where you are concerned about, or want to maintain bleedthrough properties and galvanized adhesion.

## PART NUMBER:

- 40154 SUPER CHARGER 16 oz. bottle      6 units / case      5 lbs / case

## PRODUCT USES:

Use to thin and revive body filler and putties as well as to improve performance.



**MIXING:** Add a small amount of SUPERCHARGER to body filler and mix until homogenous. Continue to make small additions with mixing until desired smoothness and consistency is achieved. (Typical mix ratio: 1 oz. SUPERCHARGER for every pint of body filler).



## TECHNICAL INFORMATION:

Appearance as Packaged:  
Viscosity @ 77 F:  
VOC

Amber Brown  
450 cps (Average)  
Packaged: 425 g./l. = 3.55 lbs./gal.  
Applied: 1.6 g./l.

**ASSOCIATED MSDS:** "Supercharger-40154"



## HEALTH & SAFETY:

Read all warnings, first aid and safety for all components before using. Keep out of reach of children and animals. Protect hands with impervious rubber gloves. Wear face, skin and eye protection. When sanding, we recommend the use of a respiratory covering device to protect from dust (MSA mask P/N 459029 with MSA cartridge 464029 or equivalent). When using power equipment, refer to power tool manufacturer's recommendations for safety equipment. USC products are for industrial use by trained professionals only.

## Emergency Medical or Spill Control Information:

In U.S. and Canada call CHEMTREC at 1-800-424-9300