

# SAFETY DATA SHEET

Revision date 28-Jun-2018

Version 4

Supersedes Date: 05-May-2018

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

**Product Code** 

G134.Q01

**Product Name** 

YELLOW SHADE GREEN

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Tint, colorant

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number
United States of America 1-888-345-5732

# **Section 2: HAZARDS IDENTIFICATION**

# Classification

Skin sensitization	Category 1
Carcinogenicity	3 7
	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

## Label elements



Signal word

WARNING

#### **HAZARD STATEMENTS**

Flammable liquid and vapor May cause an allergic skin reaction Suspected of causing cancer May cause drowsiness or dizziness

## **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

## **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

## Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

## HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

## **OTHER HAZARDS**

spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

## **UNKNOWN ACUTE TOXICITY**

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
n-Butyl acetate	123-86-4	10 - 25

Methyl n-amyl ketone	110-43-0	5 - 10
2-Butanone, oxime	96-29-7	0.1 - 0.3

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## **Section 4: FIRST AID MEASURES**

#### **First Aid Measures**

#### General advice

IF exposed or concerned: Get medical advice/attention.

#### Eve contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

## Indication of any immediate medical attention and special treatment needed

# **Section 5: FIRE FIGHTING MEASURES**

## Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

#### Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

#### Section 6: ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

## **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

## For emergency responders

Use personal protection recommended in Section 8.

## Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so.

#### Methods and material for containment and cleaning up

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically, placing in appropriate containers for disposal. Pick up and transfer to properly labeled containers.

## Section 7: HANDLING AND STORAGE

## Precautions for safe handling

## Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

## **General Hygiene Considerations**

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

## Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep tightly closed in a dry and cool place.

## Incompatible materials

Water. Strong oxidizing agents. Strong acids. Strong reducing agents. Combustible material.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

# **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
n-Butyl acetate	STEL: 150 ppm	TWA: 150 ppm	IDLH: 1700 ppm
123-86-4	TWA: 50 ppm	TWA: 710 mg/m <sup>3</sup>	TWA: 150 ppm
			TWA: 710 mg/m <sup>3</sup>
			STEL: 200 ppm
			STEL: 950 mg/m <sup>3</sup>
Methyl n-amyl ketone	TWA: 50 ppm	TWA: 100 ppm	IDLH: 800 ppm
110-43-0		TWA: 465 mg/m <sup>3</sup>	TWA: 100 ppm
			TWA: 465 mg/m <sup>3</sup>

## Appropriate engineering controls

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### **Thermal Protection**

No information available

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state liquid

Appearance No information available

Odor Solvent Color green

Odor Threshold
PH value
No information available
No information available
No information available
No information available

Boiling point / boiling range No information available °C / °F

flash point 27 °C / 81 °F

evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 8.96 specific gravity 1.07

Solubility(ies)

Partition coefficient

Autoignition temperature

Decomposition temperature

Kinematic viscosity

No information available

Other information

# **Section 10: STABILITY AND REACTIVITY**

**Reactivity** No information available.

**Chemical stability** Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

**Hazardous polymerization** None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

Incompatible materials Water. Strong oxidizing agents. Strong acids. Strong reducing agents. Combustible

material.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Chlorine gas.

## Section 11: TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Eye contact Not applicable Skin Contact

May cause an allergic skin reaction

Ingestion Not applicable Inhalation

May cause drowsiness or dizziness

# Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12600 μL/kg(Rabbit)= 12.6 mL/kg(Rabbit)	2000 - 4000 ppm (Rat) 6 h
2-Butanone, oxime 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg (Rabbit)	> 4800 mg/m³ (Rat) 4 h

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5236 Mg/kg
ATEmix (inhalation-dust/mist) 15.7 mg/l
ATEmix (inhalation-vapor) 115 mg/l

**UNKNOWN ACUTE TOXICITY** .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not applicable

Serious eye damage/eye irritation Not applicable Skin sensitization May cause an allergic skin reaction

Respiratory sensitization Not applicable Germ cell mutagenicity Not applicable Carcinogenicity Suspected of causing cancer Reproductive Toxicity Not applicable

Specific target organ toxicity (single exposure) May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure) Not applicable

Aspiration hazard Not applicable

#### Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity** 

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

# **Bioaccumulation**

No information available

**Mobility** 

No information available

Other adverse effects No information available

# **Section 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

# **Section 14: TRANSPORT INFORMATION**

 DOT
 IMDG
 IATA

 14.1 UN/ID no
 UN1263
 UN1263
 UN1263

**14.2 Proper shipping name** Paint related material Paint related material Paint related material

 14.3 Hazard Class
 3
 3

 14.4 Packing Group
 III
 III

14.5 Environmental hazard

**14.6 Special Provisions** B1, B52, IB3, T2, TP1, TP29, 367 163, 223, 367 955 A3, A72, A192

Emergency Response Guide EmS-No Number F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

## **Section 15: REGULATORY INFORMATION**

## **International Inventories**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing.

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

# **US Federal Regulations**

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			Х

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate	5000 lb		RQ 5000 lb final RQ
123-86-4			RQ 2270 kg final RQ

## **US State Regulations**

#### Rule 66 status of product

Not photochemically reactive.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

## **U.S. State Right-to-Know Regulations**

Chemical Name
Proprietary Non-Hazardous Ingredient - Proprietary CAS
n-Butyl acetate
123-86-4
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Methyl n-amyl ketone
110-43-0
C.I. Pigment Green 36
14302-13-7
2-Butanone, oxime
96-29-7

# **Section 16: OTHER INFORMATION**

HMIS

Health hazards
\* = Chronic Health Hazard

Flammability 3
Physical hazards 1
Personal Protection X

**Supplier Address** 

Valspar Coatings 701 Shiloh Rd. Garland, TX 75042 972-276-5181

Prepared By Product Stewardship

Revision date 28-Jun-2018

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**