valspar if it matters, we're on it.®

SAFETY DATA SHEET

Revision date 17-Apr-2018

Version 5

Supersedes Date: 12-Dec-2016

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier Product Code

RS695

Product Name

REDUCER SOLVENT -VERY SLOW

Other means of identification No information available

Recommended use of the chemical and restrictions on use Paint remover, Solvents/thinner

Details of the supplier of the safety data sheet See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address

msds@valspar.com

Emergency telephone number United States of America 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Highly flammable liquid and vapor Causes skin irritation Causes serious eye irritation May cause cancer May cause drowsiness or dizziness May be fatal if swallowed and enters airways

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

OTHER HAZARDS

Not applicable.

UNKNOWN ACUTE TOXICITY

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%

Solvent naphtha, petroleum, heavy aromatic	64742-94-5	25 - 50
Ethylene glycol monobutyl ether acetate	112-07-2	10 - 25
Acetone	67-64-1	10 - 25
Solvent naphtha, petroleum, light aromatic	64742-95-6	5 - 10
1,2,4-Trimethylbenzene	95-63-6	5 - 10
Naphthalene	91-20-3	3 - 5
Dimethyl succinate	106-65-0	3 - 5
Cumene	98-82-8	0.1 - 0.3

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians

Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Incompatible materials

Strong oxidizing agents.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene glycol monobutyl ether	TWA: 20 ppm		TWA: 5 ppm
acetate 112-07-2			TWA: 33 mg/m ³
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
			TWA: 590 mg/m ³
1,2,4-Trimethylbenzene	TWA: 25 ppm		TWA: 25 ppm
95-63-6			TWA: 125 mg/m ³
Naphthalene	TWA: 10 ppm	TWA: 10 ppm	IDLH: 250 ppm
91-20-3	S*	TWA: 50 mg/m ³	TWA: 10 ppm

			TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³	IDLH: 900 ppm TWA: 50 ppm
		S*	TWA: 245 mg/m ³

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance	liquid No information available
Odor	Solvent
Color	clear
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	56.05 °C / 133 °F
flash point	-1 °C / 30 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (Ibs per US gallon)	7.59
specific gravity	.91
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous polymerization	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2).

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact Causes serious eye irritation Skin Contact Causes skin irritation Ingestion May be fatal if swallowed and enters airways Inhalation May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	>2 mL/kg (Rabbit)	> 590 mg/m³ (Rat)4 h
Ethylene glycol monobutyl ether acetate 112-07-2	= 2400 mg/kg (Rat)	= 1500 mg/kg (Rabbit)	> 400 ppm (Rat)4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³(Rat)8 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat)4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³(Rat)4 h
Naphthalene 91-20-3	= 490 mg/kg (Rat)= 1110 mg/kg (Rat)	> 20 g/kg (Rabbit)= 1120 mg/kg (Rabbit)	> 340 mg/m³(Rat)1 h
Dimethyl succinate 106-65-0	> 5 g/kg (Rat)	> 5 g/kg (Rabbit)	-
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat)6 h = 39000 mg/m³ (Rat)4 h

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal)	6430 Mg/kg
ATEmix (inhalation-dust/mist)	6.6 mg/l
ATEmix (inhalation-vapor)	48 mg/l

UNKNOWN ACUTE TOXICITY .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	IARC	NTP	OSHA	
Ethylene glycol	A3				
monobutyl ether acetate					
112-07-2					
Naphthalene	A3	Group 2B	Reasonably Anticipated	Х	
91-20-3					
Cumene		Group 2B	Reasonably Anticipated	Х	
98-82-8 ACGIH (American Conference A3 - Animal Carcinogen. IARC (International Agence Group 2B - Possibly Carcin NTP (National Toxicology Reasonably Anticipated - R OSHA (Occupational Safe X - Present. Skin corrosion/irritation C Serious eye damage/eye ir Skin sensitization Not app Respiratory sensitization I Germ cell mutagenicity Not Carcinogenicity May cause Reproductive Toxicity Not Specific target organ toxic	cy for Research on Cance ogenic to Humans. Program) easonably Anticipated to b ety and Health Administra rauses skin irritation ritation Causes seriou licable Not applicable of applicable e cancer applicable ity (single exposure)	er) e a Human Carcinogen. ation of the US Departmen s eye irritation May cause drowsiness o			
Specific target organ toxic Aspiration hazard May be	ity (repeated exposure fatal if swallowed and e	 Not applicable nters airways 			
	Section 12	: ECOLOGICAL IN	FORMATION		
Ecotoxicity Environmental precautions		Prevent product from entering drains.			
Marine pollutant	DOT	This product contains a chemical which is listed as a severe marine pollutant according to DOT			
Marine pollutant	This materia	This material meets the definition of a marine pollutant			
Persistence and degradabing the second secon	ility				
Bioaccumulation No information available					
<u>Mobility</u> No information available					
Other adverse effects	No information	on available			
	Section 13	: DISPOSAL CONS	IDERATIONS		
Waste treatment methods					
Disposal of wastes	Disposal sho regulations.	ould be in accordance wit	h applicable regional, national a	nd local laws and	
Contaminated packaging	aging Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.				
	Section 1	4: TRANSPORT INF	FORMATION		
	DOT				
14.1 UN/ID no	<u>DOT</u> UN1263	<u>IMDG</u> UN1263	<u>IATA</u> UN1263		
	0111200	011200	011200		

14.2 Proper shipping name	Paint related material	Paint related material	Paint related material
	0	<u> </u>	
14.3 Hazard Class	3	3	3
14.4 Packing Group	II	II	II
14.5 Environmental hazard			
Marine pollutant This produ	uct contains a chemical which is lis	sted as a severe marine pollutar	t according to DOT
Marine pollutant This mate	rial meets the definition of a marin	e pollutant	
Marine pollutant Solvent na	aphtha, petroleum, heavy aromatio	c, Solvent naphtha, petroleum,	light aromatic
14.6 Special Provisions	149, B52, IB2, T4, TP1, TP8,	TP28, 163, 367	A3, A72, A192
	367	EmS-No	
	Emergency Response Guide	e F-E, S-E	
	Number		
	128		
14.7 Transport in bulk according	-	3 and the IBC Code	No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

All components are listed or exempt from listing. All components are listed or exempt from listing

US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Ethylene glycol monobutyl ether acetate	1		Present
112-07-2			
10 - 25			
1,2,4-Trimethylbenzene	1		
95-63-6			
5 - 10			
Naphthalene	0.1		Present
91-20-3			
3 - 5			
Cumene	1		Present
98-82-8			
0.1 - 0.3			

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene 91-20-3	100 lb	Х	Х	Х

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Naphthalene	100 lb		RQ 100 lb final RQ
91-20-3			RQ 45.4 kg final RQ
Cumene	5000 lb		RQ 5000 lb final RQ

98-82-8 RQ 22	70 kg final RQ
---------------	----------------

US State Regulations

Rule 66 status of product

Photochemically reactive.

California Proposition 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name
Solvent naphtha, petroleum, heavy aromatic
64742-94-5
Ethylene glycol monobutyl ether acetate
112-07-2
Acetone
67-64-1
Solvent naphtha, petroleum, light aromatic
64742-95-6
Proprietary Non-Hazardous Ingredient - Proprietary CAS
1,2,4-Trimethylbenzene
95-63-6
Naphthalene
91-20-3
Dimethyl succinate
106-65-0
Cumene
98-82-8

Section 16: OTHER INFORMATION

HMIS	
Health hazards	3*
* = Chronic Health Hazard	
Flammability	3
Physical hazards	0
Personal Protection	Х

Supplier Address

Valspar Coatings 701 Shiloh Rd. Garland, TX 75042 972-276-5181

Prepared By

Product Stewardship

No information available

17-Apr-2018

Revision date Revision Note Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL,

INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet